

# **MATERIAL SAFETY DATA SHEET**

Page 1 of 4

## 1. PRODUCT AND COMPANY IDENTIFICATION

NAME: UHS FLOOR FINISH
USE: HIGH SPEED FLOOR FINISH

MSDS# 101296U

USCHEMICAL, 316 HART STREET, WATERTOWN, WI 53094 USA

MEDICAL EMERGENCY #: 1-800-851-7145 EXT. 075 USA

SPILL EMERGENCY #: 1-800-424-9300 USA

PRODUCT INFORMATION #: 1-800-558-9566 (8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)

INTERNET ADDRESS: www.uschemical.com

REVIEWED 3-17-05 REVISED 3-17-05 SECTION REVISED: 1

### 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: CAUTION! MAY BE MILDLY IRRITATING TO EYES.

PRINCIPLE ROUTES OF EXPOSURE: EYES, INGESTION

POTENTIAL ACUTE HEALTH EFFECTS

EYES: MAY BE MILDLY IRRITATING TO EYES.

**SKIN:** MAY BE MILDLY IRRITATING TO SKIN.

INHALATION: NONE KNOWN.

**INGESTION:** MAY CAUSE ABDOMINAL DISCOMFORT, NAUSEA, VOMITING AND DIARRHEA.

MEDICAL CONDITIONS AGGRAVATED: PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE

MORE SUSCEPTABLE TO IRRITATING EFFECTS.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS#	% BY WT	LC50/LD50
DIETHYLENE GLYCOL MONOETHYL ETHER	111-90-0	1.0 - 5.0	N.AV.
DIPROPYLENE GLYCOL METHYL ETHER	34590-94-8	1.0 – 5.0	N.AV.

STATE RIGHT TO KNOW: THIS PRODUCT CONTAINS:

WATER/7732-18-5, ACRYLIC POLYMERS/N.AV., DIPROPYLENE GLYCOL METHYL ETHER/34590-94-8,

DIETHYLENE GLYCOL MONOETHYL ETHER/111-90-0

### 4. FIRST AID MEASURES

Page 2 of 4

**EYES:** FLOOD WITH LUKEWARM (NOT HOT) WATER POURED FROM A LARGE GLASS 2 OR 3 INCHES FROM EYES. REMOVE CONTACTS. HAVE PATIENT BLINK AS MUCH AS POSSIBLE WHILE FLOODING THE EYES. CONTINUE FOR AT LEAST 15 MINUTES.

**SKIN:** REMOVE CONTAMINATED CLOTHES, THEN FLOOD WITH WATER.

**INHALATION:** N.AP.

INGESTION: DO NOT INDUCE VOMITING. IF PATIENT IS CONSCIOUS AND CAN SWALLOW,

ADMINISTER MILK OR WATER.

ADMINISTER FIRST AID TREATMENT AS STATED ABOVE, THEN CALL 1-800-851-7145 EXT.

075 OR CONTACT PHYSICIAN FOR FURTHER MEDICAL INSTRUCTIONS.

NOTE TO PHYSICIAN: CALL 1-800-851-7145 EXT. 075 FOR ASSISTANCE WITH THE MANAGEMENT OF EXPOSURES.

### 5. FIRE-FIGHTING MEASURES

FLAMMABILITY: NO HAZARD.

FLASH POINT: N.AP.

**PRODUCTS OF COMBUSTION: SEE SECTION 10.** 

**SUITABLE EXTINGUISHING MEDIA:** FOR FIRES IN AREA, USE APPROPRIATE MEDIA. FOR EXAMPLE: WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, OR ALCOHOL FOAM.

SPECIFIC HAZARDS: N.AP.

SPECIFIC METHODS: NORMAL FIRE FIGHTING PROCEDURES MAY BE USED.

### 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: SEE SECTION 8.

**SPILL RESPONSE:** EVACUATE UNPROTECTED PERSONNEL FROM AREA. WEAR PROPER PROTECTIVE EQUIPMENT INCLUDING RUBBER BOOTS. VENTILATE AREA IF NEEDED. STOP LEAK IF YOU CAN DO SO WITHOUT RISK. DIKE OR DAM LARGE SPILLS. AVOID DIRECT DISCHARGE TO SEWER AND SURFACE WATERS. PUMP TO CONTAINER OR SOAK UP WITH NON-COMBUSTIBLE INERT ABSORBENT MATERIALS. AFTER SPILL COLLECTION, FLUSH AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES. BE CAREFUL AS SPILLS ARE SLIPPERY.

### 7. HANDLING AND STORAGE

HANDLING: FOLLOW ALL LABEL DIRECTIONS. INSTRUCT PERSONNEL ABOUT PROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES. AVOID INGESTION AND CONTACT WITH EYES. DO NOT TASTE OR SWALLOW. PRODUCT RESIDUE MAY REMAIN ON OR IN EMPTY CONTAINERS. HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER.

**STORAGE:** ROTATE STOCK REGULARLY. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID TEMPERATURES BELOW 35°F OR ABOVE 120°F. PROTECT FROM FREEZING. STORAGE AT AMBIENT TEMPERATURES IN A DRY AREA OUT OF DIRECT SUNLIGHT IS RECOMMENDED. KEEP AWAY FROM FOOD AND DRINK. KEEP OUT OF CHILDREN'S REACH.

Page 3 of 4

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**EXPOSURE LIMITS:** 

DIPROPYLENE GLYCOL METHYL ETHER = 100 PPM TWA-SKIN (ACGIH/OSHA), 150 PPM STEL-SKIN (ACGIH) **ENGINEERING CONTROLS:** NONE REQUIRED. GENERAL ROOM VENTILATION IS ADEQUATE.

PERSONAL PROTECTION

EYES: NONE REQUIRED WITH NORMAL USE.

HANDS: FOR PROLONGED OR REPEATED CONTACT WITH SKIN: RUBBER GLOVES.

**RESPIRATORY:** N.AP.

FEET: N.AP. BODY: N.AP.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

COLOR: OPAQUE WHITE FLASH POINT: N.AP.

ODOR:MILD AMMONIAUEL:N.AP.ph concentrate:8.6Lel:N.AP.

pH @ 2500 PPM SOLUTION: N.AP.
pH @ USE DILUTION: N.AP.
PHYSICAL STATE: LIQUID
SPECIFIC GRAVITY: 1.030

EVAPORATION RATE: N.AP.
ODOR THRESHOLD: N.AP
VAPOR PRESSURE: N.AP
VAPOR DENSITY: N. AP.

VISCOSITY: N.AV. COEFF. OIL/WATER: N.AP.

BOILING POINT: N.AP. WATER SOLUBILITY: DISPERSIBLE

MELTING POINT: N.AP. OTHER: N.AP.

### 10. STABILITY AND REACTIVITY

STABLE: YES

CONDITIONS TO AVOID: AVOID TEMPERATURES BELOW 35°F OR ABOVE 120°F.

MATERIALS TO AVOID: AVOID MIXING DIRECTLY WITH ANY OTHER CLEANING

PRODUCT. AVOID OXIDIZING AGENTS. MIX ONLY WITH WATER.

**DECOMPOSITION PRODUCTS:** FIRE OR MIXING WITH INCOMPATIBLE MATERIALS MAY

PRODUCE OXIDES OF CARBON AND OTHER TOXIC OR IRRITATING FUMES.

POSSIBILITY OF HAZARDOUS REACTIONS: N.AP.

# 11. TOXICOLOGICAL INFORMATION

**ACUTE EFFECTS: SEE SECTION 2.** 

**CHRONIC EFFECTS:** NONE KNOWN. NO REPORTABLE CARCINOGENS, MUTAGENS, SENSITIZERS, SYNERGISTIC MATERIALS, TERATOGENS, OR REPRODUCTIVE TOXINS.

LC50/LD50: N.AV.

TARGET ORGANS: NONE KNOWN.

OTHER TOXIC EFFECTS: NONE KNOWN.

### 12. ECOLOGICAL INFORMATION

Page 4 of 4

NOT AVAILABLE.

#### 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS. CONSULT STATE AND LOCAL AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. MANAGE CHEMICAL WASTES THROUGH AN APPROVED WASTE TREATMENT FACILITY. DO NOT REUSE EMPTY CONTAINER. RINSE EMPTY CONTAINER THOROUGHLY WITH WATER BEFORE DISCARDING CONTAINER IN ACCORDANCE WITH CURRENT LOCAL COMMUNITY CODES. PLEASE RECYCLE EMPTY CONTAINER WHENEVER POSSIBLE.

### 14. TRANSPORT INFORMATION

**DOT/TDG: NOT REGULATED** 

DOT RQ: N.AP.
DOT ERG #: N.AP.

### 15. REGULATORY INFORMATION

EPA REGISTERED: NO

**EPA %VOC:** 5.20

EPA VOC RULE: PRODUCT COMPLIES WITH THE EPA VOC EMISSIONS STANDARD.

KOSHER (CRC): NO

**OSHA HAZARDOUS**: YES

PHOSPHORUS CONTENT: SEE LABEL

PROPOSITION 65: N.AP.

SARA 311/312 HAZARDS: ACUTE

SARA 313 CHEMICALS: DIETHYLENE GLYCOL MONOETHYL ETHER

**STATE RIGHT TO KNOW:** SEE SECTION 3 FOR STATE RTK CHEMICAL NAMES.

TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY.

WHMIS CLASS: D-2B

### 16. OTHER INFORMATION

NFPA RATING: HEALTH-1/FLAMMABILITY-0/REACTIVITY-0/SPECIAL HAZARD-N.AP.

HMIS RATING: HEALTH-1/FLAMMABILITY-0/REACTIVITY-0/PERSONAL PROTECTION-SEE 8.0

N.AV. = NOT AVAILABLE N.AP. = NOT APPLICABLE PREPARED BY: HEALTH AND SAFETY

#### **NOTICE TO READER**

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.