Quick & Clean Jell Baseboard Stripper

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:

Quick & Clean Jell Baseboard Stripper

Product Number:

A00807

Product Use:

Wax Remover.

Manufacturer/Supplier:

HILLYARD INDUSTRIES 302 North Fourth Street, St.

Joseph, MO 64502

Phone Number:

(816) 233-1321 (Ext, 8285)

D.O.T. Emergency Phone:

(800) 424-9300

Date of Preparation:

January 16, 2008

Revision #: 1.0

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS: See Section 15

DANGER

CORROSIVE MATERIAL - CAUSES BURNS.

CONTENTS UNDER PRESSURE. CONTAINER MAY EXPLODE IF HEATED.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye:

Causes burns.

Skin:

Causes burns.

Indestion:

Not a normal route of exposure. Harmful: may cause lung damage if

swallowed.

Inhalation:

May cause respiratory tract irritation. May cause asphyxiation. This product

may be aspirated into the lungs and cause chemical pneumonitis.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, drying, defatting and cracking of the skin. Vapours may cause drowsiness and dizziness.

Medical Conditions Aggravated By Exposure: Asthma. Allergies,

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS#	Wt. %
Ethylene glycol monobutyl ether	111-76-2	10 - 30
Isobutane	75-28-5	7 - 13
Monoethanolamine	141-43-5	1 - 5
Propane	74-98-6	1 - 5

Quick & Clean Jell Baseboard Stripper

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. If easy to do, remove contact lenses, if worn. Get medical attention

immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Remove

contaminated clothing and shoes. Wash clothing before reuse. Call a

physician if irritation develops and persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon, oxides of

nitrogen.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Containers may explode when heated. Keep upwind of fire. Wear

full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

Environmental Precautions: Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). This material is a water pollutant. Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Vacuum or sweep material and place in a disposal container. Allow gas to dissipate harmlessly into the atmosphere.

Other Information: Not available.

Quick & Clean Jell Baseboard Stripper

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Handle and open container with care. When using, do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container in a well-ventilated place. Do not store at temperatures above 49°C / 120°F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Exposure Limits Ingredient OSHA-PEL **ACGIH-TLV** Ethylene glycol monobutyl ether 50 ppm 20 ppm Isobutane Not available. Not available. Monoethanolamine 3 ppm 3 ppm Propane 1000 ppm 1000 ppm

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

HMIS: See Section 15

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory

equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Opaque. Color: Straw.

Odour: Mint.

Odour Threshold: Not available.

Physical State: Gas/Pressurized Liquid.

pH: 12

Viscosity: Not available. Freezing Point: Not available.

Boiling Point: Not available. Flash Point: Not available.

Evaporation Rate: Not available.

Lower Flammability Limit: Not available.

Quick & Clean Jell Baseboard Stripper

Upper Flammability Limit:

Not available.

Vapor Pressure:

Not available.

Vapor Density:

Not available.

Specific Gravity:

0.990 (Liquid Concentrate)

Solubility in Water:

Complete.

Coefficient of Water/Oil Distribution:

Not available.

Auto-ignition Temperature:

Not available.

Percent Volatile, wt. %:

Not available.

VOC content, wt. %:

34.8% (US federal/CARB/OTC/LADCO)

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Acids. Alkaline metals. Copper.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon,

oxides of nitrogen.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of

normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Anaylsis

Ingredient	LD ₅₀ (oral)	LC ₅₀
Ethylene glycol monobutyl ether	470 mg/kg, rat	450 ppm 4 hrs, rat
Isobutane	Not available.	Not available.
Monoethanolamine	1720 mg/kg, rat	Not available.
Propane	Not available.	Not available.

Eye:

Causes burns. Symptoms may include discomfort or pain, excess blinking and

tear production, with marked redness and swelling of the conjunctiva.

Skin:

Causes burns. Handling can cause dry skin.

Ingestion:

Not a normal route of exposure. Harmful: may cause lung damage if swallowed.

Inhalation:

May cause respiratory tract irritation. May cause asphyxiation. This product may

be aspirated into the lungs and cause chemical pneumonitis. Vapours may

cause drowsiness and dizziness.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: (Effects due to excessive exposure to the raw materials of this mixture) May cause nasal and respiratory irritation, diarrhea and vomiting. Lab animals have experienced anemia, liver, kidney, lung and blood damage due to Ethylene glycol monobutyl ether.

Carcinogenicity: Not hazardous by WHMIS/OSHA criteria.

Quick & Clean Jell Baseboard Stripper

Ingredient

Chemical Listed as Carcinogen or Potential Carcinogen *

Ethylene glycol monobutyl ether

Isobutane

Monoethanolamine

Propane

Not listed. Not listed.

Not listed.

Not listed.

Mutagenicity: Not hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Not hazardous by WHMIS/OSHA criteria.

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Classification

ORM-D

TDG Classification

Limited Quantity

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200).

^{*} See Section 15 for more information.

Quick & Clean Jell Baseboard Stripper

SARA Title III

Ingredient	Section 302 (EHS) TPQ	Section 304	CERCLA	Section
•	(lbs.)	EHS RQ (lbs.)	RQ (lbs.)	313
Ethylene glycol monobutyl ether	Not listed.	Not listed.	Not listed.	Yes.
Isobutane	Not listed.	Not listed.	Not listed.	Not listed.
Monoethanolamine	Not listed.	Not listed.	Not listed.	Not listed.
Propane	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	Canada	USA
	DSL/NDSL	TSCA
Ethylene glycol monobutyl ether	DSL	Yes.
Isobutane	DSL	Yes.
Monoethanolamine	DSL	Yes.
Propane	DSL	Yes.

HMIS - Hazardous Materials Identification System

Health - 2 Flammability - 1 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 2 Fire - 1 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class A - Compressed Gas Class E - Corrosive Material

WHMIS Hazard Symbols:



Quick & Clean Jell Baseboard Stripper

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen. A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in

humans and sufficient evidence of carcinogenicity in experimental animals.
2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in

humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: January 16, 2011

Prepared by: Nexreg Compliance Inc.
Prepared for: HILLYARD INDUSTRIES

(816) 233-1321 (Ext, 8285)