



MATERIAL SAFETY DATA SHEET

REVISION DATE: 10/28/2008
 DATE PRINTED: 11/11/2008

REVISION NUMBER: 6
 PREPARED BY: EH&S DEPARTMENT

1. CHEMICAL PRODUCT

PRODUCT NAME: **REPEEL, Floor Finish Remover**
 PRODUCT CODE: 104400

NFPA/HMIS HAZARD CODES (minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health: 3/3
 Reactivity: 0/0
 Fire: 0/0
 Special/Protective Equipment: ALK/B

NAME OF THE MANUFACTURER: Rochester Midland Corporation
 333 Hollenbeck Street
 Rochester, New York 14621
 Information: 585-336-2200
 Emergency Phone:
 INFOTRAC: 1-800-535-5053
 OUTSIDE US: 1-352-323-3500

2. HAZARDS IDENTIFICATION

EFFECTS FROM ACUTE EXPOSURE:

INGESTION: Harmful if swallowed. May cause burns to mucous membranes of mouth, throat, and digestive tract.
SKIN CONTACT: Prolonged contact causes severe burns which may not be immediately painful or visible.
INHALATION: Inhalation of spray mist may be irritating. Possible damage to mucous membranes of nose and throat. Excessive inhalation causes headache, dizziness, nausea and incoordination.
EYE CONTACT: Causes severe eye burns which may not be immediately painful or visible.
CHRONIC EFFECTS: Dermatitis. Possible respiratory damage from inhalation of dust or mist. 2-Butoxyethanol is readily absorbed through the skin; frequent or widespread contact may absorb harmful amounts. Repeated overexposure may cause damage to liver, kidney, and red blood cells.
EFFECTS/CARCINOGENICITY: None listed under OSHA, IARC, or NTP.
ROUTES OF ENTRY: Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION CAS#	%	ACGIH TLV	OSHA PELs
Sodium metasilicate 6834-92-0	1 max.	NA	NA
2-Butoxy ethanol 111-76-2	15	20 ppm	240 mg/m ³ 50 ppm

4. FIRST AID MEASURES

INGESTION: DO NOT INDUCE VOMITING. Drink several glasses of water or milk. Get immediate medical attention. Never give anything by mouth to an unconscious person.
SKIN: Flush with water for at least 15 minutes while removing all contaminated clothing and shoes. Continue rinsing until "slippery" feeling is gone. Get medical attention if irritation or burns develop.
INHALATION: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.
EYES: In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.
NOTES TO PHYSICIAN: None.

REPEEL, Floor Finish Remover

5. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (F): None (C): NA
METHOD: None

FLAMMABLE LIMITS IN AIR

- LOWER (%): None
- UPPER (%): None

SENSITIVITY TO MECHANICAL IMPACT(Y/N):
SENSITIVITY TO STATIC DISCHARGE:
SUITABLE EXTINGUISHING MEDIA:
FIRE FIGHTING PROCEDURES:

NO
Sensitivity to static discharge is not expected.
As for surrounding fire. Product will not burn.
Corrosive material. Avoid exposure to mist and splashes. Fire-
fighters should wear self-contained breathing apparatus and full
protective clothing when fighting chemical fires. Cool exposed
containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:

SMALL SPILLS:

LARGE SPILLS:

Flush with water.

Dike to contain. Pick up with absorbant material. Put in suitable container for disposal. Flush
remainder with water. Releases of some glycol ethers may be CERCLA reportable.

PERSONAL PRECAUTIONS:

ENVIRONMENTAL PRECAUTIONS:

METHODS FOR CLEANING UP:

NA

NA

NA

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN
IN HANDLING AND STORAGE:

OTHER PRECAUTIONS:

SPECIFIC USE(S):

DANGER: Concentrated, alkaline liquid. Avoid contact with eyes, skin and clothing. Do not
breathe mist or vapors. Store only in original container and keep closed. Store in a cool, dry
area. Store in a well ventilated area. Mix only with cool water.

Do not reuse container. Empty containers may retain product residue, follow MSDS/label
precautions even after container is emptied. Read and follow label instructions.

NA

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



EXPOSURE CONTROLS:

RESPIRATORY PROTECTION:

PROTECTIVE GLOVES:

EYE PROTECTION:

OTHER PERSONAL PROTECTION

EQUIPMENT:

VENTILATION:

Use in a well ventilated area.

Not normally required. If product is used in a manner which creates dust or mist above
recommended exposure limits, a NIOSH/MSHA approved respirator with dust/mist filter may be
needed in the absence of proper environmental controls.

Rubber or plastic gloves recommended to minimize skin contact.

Goggles.

Rubber boots. Appropriate protective clothing as needed to prevent skin contact. Eyewash
fountains and safety showers must be easily accessible.

General mechanical and/or local exhaust as needed to meet exposure limits if mist in air.

Corrosion resistant equipment recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR:

Blue liquid. Soapy odor.

REPEEL, Floor Finish Remover

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F):	212 F	(C) NA
VAPOR PRESSURE:	15.7 mm Hg @ 22.2 C	
VAPOR DENSITY (AIR=1):	0.625	
SOLUBILITY IN WATER:	NA	
SPECIFIC GRAVITY:	1.002 +/- 0.005; 8.35#/gal.	
VOC Content (%):	NE	
VOV Content (%):	NE	
EVAPORATION RATE:	(BuAc = 1) : 1.26	
PH:	12.5 +/- 0.5	

10. STABILITY AND REACTIVITY

STABILITY DATA:	STABLE
POLYMERIZATION:	Will Not Occur.
HAZARDOUS DECOMPOSITION:	If evaporated to dryness, as in a fire, may release: Soot. Smoke. Carbon Monoxide. Traces of: Sulfur compounds.
INCOMPATIBILITY (MATERIALS TO AVOID):	Do not mix with acidic materials. Neutralizes active ingredients. May release acid fumes.
CONDITIONS/HAZARDS TO AVOID:	None.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY:	NE
EFFECTS OF CHRONIC EXPOSURE:	NE
OTHER TOXIC EFFECTS:	NE

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:	No data at this time
CHEMICAL FATE INFORMATION:	No data at this time.
MOBILITY:	NA
PERSISTENCE/DEGRADABILITY:	NA
BIOACCUMULATIVE POTENTIAL:	NA
OTHER ADVERSE EFFECTS:	NA

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/Receiving documents for up to date shipping information.

15. REGULATORY INFORMATION

PRODUCT COMPOSITION CAS#	%	TSCA:	EINECS:	Canada DSL:	CA PROP 65:
Sodium metasilicate 6834-92-0	1 max.	Listed	Listed	Listed	Not Listed
2-Butoxy ethanol 111-76-2	15	Listed	Listed	Listed	Not Listed

REPEEL, Floor Finish Remover

PRODUCT COMPOSITION CAS#	%	CERCLA:	SARA 302:	SARA 313:
Sodium metasilicate 6834-92-0	1 max.	Not Listed	Not Listed	Not Listed
2-Butoxy ethanol 111-76-2	15	Not Listed	Not Listed	Listed

PRODUCT COMPOSITION CAS#	%	Canada WHMIS:
Sodium metasilicate 6834-92-0	1 max.	Listed
2-Butoxy ethanol 111-76-2	15	Listed

The following components of this material are included in the Massachusetts Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	MARTK:
2-Butoxy ethanol 111-76-2	15	Listed

The following components of this material are included in the New Jersey Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	NJRTK:
2-Butoxy ethanol 111-76-2	15	Listed

The following components of this material are included in the Pennsylvania Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	PARTK:
2-Butoxy ethanol 111-76-2	15	Listed

16. OTHER INFORMATION

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

*** END OF MSDS ***