

Information for doctor
Treatment Symptomatic treatment

5 Fire fighting measures

Suitable extinguishing agents

The product is not combustible and does not support combustion.

Use fire fighting measures that suit the environment.

Special hazards caused by the material, its products of combustion or resulting gases:

No hazards known

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Person-related safety precautions:

Ensure adequate ventilation

Wear protective clothing.

Keep unprotected persons away.

Measures for environmental protection:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to Item 13.

7 Handling and storage

Handling

Information for safe handling:

No special precautions are necessary if used correctly.

Information about protection against explosions and fires:

No special measures required.

Storage

Requirements to be met by storerooms and receptacles:

Store receptacles tightly closed at a cool and dry place with sufficient ventilation

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Protect from frost.

8 Exposure controls and personal protection

Additional information about design of technical systems:

No further data; see Item 7.

Components with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

PEL: 980 mg/m³, 400 ppm

REL: short-term value: 1225 mg/m³, 500 ppm

long-term value: 980 mg/m³, 400 ppm

TLV: short-term value: 984 mg/m³, 400 ppm

long-term value: 492 mg/m³, 200 ppm