

Section 5. Fire fighting measures

- Flash point** : > 100°C
Product does not support combustion.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
halogenated compounds
metal oxide/oxides
- Fire-fighting media and instructions** : Use an extinguishing agent suitable for the surrounding fire.

Dike area of fire to prevent runoff.
In a fire or if heated, a pressure increase will occur and the container may burst.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Stop leak if without risk. Use suitable protective equipment. Keep unnecessary personnel away. Do not touch or walk through spilled material.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain it to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Section 7. Handling and storage

- Handling** : Do not ingest. Do not get in eyes, on skin, or on clothing. Avoid breathing vapors, spray or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
- Storage** : Keep out of reach of children. Keep container in a cool, well-ventilated area. Keep container tightly closed.
Store between the following temperatures: 0 and 50°C

Section 8. Exposure controls/personal protection

- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Personal protection:

- Eyes** : Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.
- Hands** : Use chemical-resistant, impervious gloves.
- Skin** : Wear suitable protective clothing.
- Respiratory** : Avoid breathing vapors, spray or mists.

Name **Exposure limits**