SAFETY DATA SHEET AXCGL ANTIQUAX CHANDELIER & GLASS CLEANER

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME: AXCGL ANTIQUAX CHANDELIER & GLASS CLEANER

PART No.: XCGL

SUPPLIER: James Briggs Ltd

Salmon Fields Industrial Estate

Royton, Oldham England OL2 6HZ Tel: 0161 627 0101 Fax: 0161 627 0971

EMERGENCY TELEPHONES: (+0044) (0) 161 620 5400

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME			CONTENT
CAS No.: PROPAN-2-OL 67-63-0	EINECS Nr.: 200-661-7	CLASSIFICATION Xi ,F R-11, 36, 67	30-60 %
ISOBUTANE 75-28-5	200-857-2	F+ R-12	1-5 %
BUTANE 106-97-8	203-448-7	F+ R-12	1-5 %
AMMONIA GAS 7664-41-7	231-635-3	T ,N R-10, 23, 34, 50	0-1 %
PROPANE 74-98-6	200-827-9	F+ R-12	5-10 %

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION

Extremely flammable. Irritating to eyes. Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES

GENERAL: Move the exposed person to fresh air at once. Get medical attention if any discomfort

continues.

INHALATION: Move the exposed person to fresh air at once. When breathing is difficult, properly

trained personnel may assist affected person by administering 100% oxygen. Keep

the affected person warm and at rest. Get prompt medical attention.

INGESTION: DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large

amounts of milk or water to people not unconscious. Get medical attention if any

discomfort continues.

SKIN: Wash the skin immediately with soap and water. Get medical attention if any

discomfort continues.

EYES: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash

eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

PROCEDURES: fire exposed conta

UNUSUAL FIRE & EXPLOSION

HAZARDS:

Aerosol cans may explode in fires.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEANUP METHODS: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks,

flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces

because of explosion risk. If leakage cannot be stopped, evacuate area.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination

is above accepted level.

STORAGE PRECAUTIONS: Aerosol cans: Must not be exposed for direct sunlight or temperatures above 50°C.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME: CAS No.: **STD** LT EXP 8 Hrs ST EXP 15 Min AMMONIA GAS **OES** 35 ppm 7664-41-7 25 ppm PROPAN-2-OL 67-63-0 **OFS** 400 ppm 500 ppm **BUTANE** 106-97-8 **OFS** 600 ppm 750 ppm **PROPANE** 74-98-6 Asphyxiating Asphyxiating

INGREDIENT COMMENTS: OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

PROTECTIVE EQUIPMENT:





VENTILATION: Provide adequate general and local exhaust ventilation.

RESPIRATORS:No specific recommendation made, but respiratory protection must be used if the

general level exceeds the Occupational Exposure Level (OEL). Use chemical

cartridge protection with appropriate cartridge.

PROTECTIVE GLOVES: Use protective gloves.

EYE PROTECTION: Use approved safety goggles or face shield.

OTHER PROTECTION: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

HYGIENIC WORK PRACTICES: DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before

eating, smoking and using the toilet. Promptly remove any clothing that becomes

contaminated. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Aerosol.

COLOUR: Colourless.

ODOUR/TASTE: Characteristic.

SOLUBILITY DESCRIPTION: Soluble in water.

FLAMMABILITY LIMIT - LOWER(%): 0.8

FLAMMABILITY LIMIT - UPPER(%): 12.0

10. STABILITY AND REACTIVITY

STABILITY: Normally stable.

CONDITIONS TO AVOID: Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising

agents. Strong alkalis. Strong mineral acids.

HAZARDOUS DECOMP. PRODUCTS: Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

INHALATION: May cause irritation to the respiratory system. Solvent vapours are hazardous and may

cause nausea, sickness and headaches. Prolonged inhalation of high concentrations

may damage respiratory system. Irritating to respiratory system.

INGESTION: May cause discomfort if swallowed. May cause stomach pain or vomiting.

Gastrointestinal symptoms, including upset stomach.

SKIN: Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent

on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema.

May cause sensitisation by skin contact. Irritating to skin.

EYES: Irritating to eyes. May cause chemical eye burns.

ROUTE OF ENTRY: Inhalation. Skin and/or eye contact.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Empty containers must not be burned because of explosion hazard. Dispose of in

accordance with Local Authority requirements.

14. TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



UN No. ROAD: 1950

UK ROAD TRANSPORT CLASS: 2.1

UK ROAD PACK GR.: Not Applicable

ADR CLASS No.: 2

ADR CLASS: Class 2: Gases; Compressed, liquefied or dissolved under pressure.

ADR PACK GR. Not Applicable

ADR LABEL No.: 2.1

CEFIC TEC(R) No.: 20G53

PROPER SHIPPING NAME I: AEROSOLS

RID CLASS No.: 2

RID PACK GR. Not Applicable

UN No. SEA: 1950

IMDG CLASS: 2.1

IMDG PACK GR.: Not Applicable

EmS No.: 2-13

MFAG TABLE No.: See Guide

MARINE POLLUTANT: No.

UN No., AIR: 1950

ICAO CLASS: 2.1

AIR PACK GR.: Not Applicable

15. REGULATORY INFORMATION

LABEL FOR SUPPLY:





RISK PHRASES: R-12 Extremely flammable.

R-36 Irritating to eyes.

R-67 Vapours may cause drowsiness and dizziness.

SAFETY PHRASES: S-16 Keep away from sources of ignition - No Smoking.

S-2 Keep out of the reach of children. S-23C Do not breathe vapour/spray

S-25 Avoid contact with eyes.

S-26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S-51 Use only in well-ventilated areas.

UK REGULATORY REFERENCES: The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

STATUTORY INSTRUMENTS: The Control of Substances Hazardous to Health Regulations 2002. The Chemicals

(Hazard Information and Packaging for Supply) Regulations 2002.

APPROVED CODE OF PRACTICE: Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES: Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation

HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

PRINTING DATE: 2003-07-17

R-PHRASES (Full Text): R-10 Flammable. R-23 Toxic by inhalation. R-34 Causes burns. R-50 Very toxic to

aquatic organisms. R-11 Highly flammable. R-36 Irritating to eyes. R-67 Vapours may

cause drowsiness and dizziness. R-12 Extremely flammable.