3M MATERIAL SAFETY DATA SHEET 3M(TM) STANCE (TM) FLOOR FINISH 03/74/2005

Moderate Eye Irritation: Signs/symptoms may include rodness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Mild Skin Irritation; Signs/symptoms may include localized redness, swelling, and itching.

Inhalation:

Single exposure, above recommended guidelines, may cause: Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhea and vomiting. May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Single exposure, above recommended guidelines, may cause: Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, sturred speech, giddiness, and unconsciousness. Prolonged or repeated exposure, above recommended guidelines, may cause: Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness and tremors.

3.3 POTENTIAL ENVIRONMENTAL EFFECTS

Not determined.

SECTION ATTEMPT AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperature
Flash Point
Flammable Limits - LEL,
Flammable Limits - UEL
OSHA Flammability Classification:

No Data Available > 200 °F [Test Method: Closed Cup] No Data Available No Data Available Class IIIB Combustible Liquid

A 10

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).