

Gloves made from the following material(s) are recommended: Butyl Rubber, Polyvinyl Chloride.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
DIETHYLENE GLYCOL MONOETHYL ETHER	AIHA	TWA	25 ppm	
DIETHYLENE GLYCOL MONOETHYL ETHER	CMRG	TWA	25 ppm	
STEARATES	ACGIH	TWA, as total dust	10 mg/m3	Table A4

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Liquid
Odor, Color, Grade:	Opaque white, acrylic odor.
General Physical Form:	Liquid
Autoignition temperature	No Data Available
Flash Point	> 200 °F [Test Method: Closed Cup]
Flammable Limits - LEL	No Data Available
Flammable Limits - UEL	No Data Available
Boiling point	> 95 °F
Density	1.03 g/ml
Vapor Density	No Data Available
Vapor Pressure	< 27 psia (@ 131 °F)
Specific Gravity	Approximately 1.03 [Ref Std: WATER=1]
pH	8.5 - 9.3
Melting point	Not Applicable
Solubility in Water	Complete
Evaporation rate	No Data Available
Volatile Organic Compounds	5 - 10 [Test Method: calculated per CARB title 2]
Percent volatile	65 - 100 %
VOC Less H2O & Exempt Solvents	100 - 700 g/l [Test Method: calculated per CARB title 2]
Viscosity	< 15 centipoise [Test Method: ACS METHOD]

SECTION 10: STABILITY AND REACTIVITY