



MATERIAL SAFETY DATA SHEET

28- GLEME

1. Product and Company Identification

Product number 049
Product name Gleme Glass Cleaner
Effective date 10-Mar-2009
Company information Claire Manufacturing
500 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 14
Supersedes date 04-Mar-2009

2. Hazards Identification

Emergency overview CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when exposed to heat or flame. Prolonged exposure may cause chronic effects. May be ignited by heat, sparks or flames.

Potential health effects

Routes of exposure Ingestion. Skin contact.

Eyes Health injuries are not known or expected under normal use.

Skin This product may be harmful if it is absorbed through the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Ingestion Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion.

Target organs 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans.

Chronic effects Blood. Liver.

Unconsciousness. Liver injury may occur.

3. Composition / Information on Ingredients

Components	CAS #	Percent
2-Butoxyethanol	111-76-2	3 - 5
Ethyl Alcohol	64-17-5	3 - 5
Propane	74-98-6	1 - 3
n-Butane	106-97-8	1 - 3
Non-hazardous and other components below reportable levels		80 - 90

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

Inhalation If symptoms develop move victim to fresh air. If symptoms persist, get medical attention.

Ingestion Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back.
Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Protection of firefighters	
Protective equipment and precautions for firefighters	Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.
Storage	Level 1 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. Keep away from heat, sparks, and flame. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	50 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection	Wear chemical goggles.
Skin protection	Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
-------------------	---------------------------

Boiling point	206.6 °F (97.2 °C) estimated
Color	Colorless.
Flammability (HOC)	3.7946 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C)
Form	Aerosol.
Odor	Butyl
pH	9.5 - 10.5
Physical state	Liquid.
Pressure	66 - 76 psig @ 70F
Solubility	Completely
Specific gravity	0.9572 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological Information

Acute effects	Acute LD50: 5684 mg/kg estimated, Rat, Dermal
Sensitization	Not expected to be hazardous by OSHA criteria.
Reproductive effects	Not expected to be hazardous by OSHA criteria.
Teratogenicity	Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity	Components of this product have been identified as having potential environmental concerns. LC50 28957 mg/L estimated, Fish, 96.00 Hours, EC50 43419 mg/L estimated, Daphnia, 48.00 Hours, IC50 12207 mg/L estimated, Algae, 72.00 Hours,
-------------	--

13. Disposal Considerations

Waste codes	D001: Waste Flammable material with a flash point <140 F
Disposal instructions	Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:	
Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Item 5F
Labels required None
Transport Category 2

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required 2.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

2-Butoxyethanol	111-76-2	1.0 % de minimis concentration (applies to R-(OCH ₂ CH ₂) _n -OR', where n = 1, 2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)
-----------------	----------	---

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations**U.S. - Pennsylvania - RTK (Right to Know) List**

2-Butoxyethanol	111-76-2	Present
Ethyl Alcohol	64-17-5	Present
n-Butane	106-97-8	Present
Propane	74-98-6	Present

Product name: Glème Glass Cleaner

Product #: 049 Glème Glass Cleaner

MSDS US

4 / 5

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 1

Flammability: 1

Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

This document has undergone significant changes and should be reviewed in its entirety.