

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): **PREMIUM WOOD POLISH (RTU)**

Product Division: **Janitorial**

Product Number: 3028

Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee OH 43537 Product/Technical Information: 1-(800)-537-8990

Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spill Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Non-Hazardous Products

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight	Health: 1- Slight
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

				Table Z-1-A		
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	NTP, IARC or OSHA Carcinogen
Polydimethyl siloxane Dimethyl siloxane,	5-10 1-5	63148-62-9 70131-67-8	Not Established Not Established	Not Established Not Established	Not Established Not Established	No No
hvdroxv-terminated	-	-	-	_	_	-

SECTION III: PHYSICAL DATA

 Boiling Point: 210-212 °F	Vapor Pressure:	Not determined
Vapor Density (AIR = 1): Unknown	Solubility in Water:	Forms an emulsion
pH: 7.2 - 7.8	Specific Gravity (H ₂ O=1):	0.975
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight:	7.5 - 8.5
Physical State: Liquid		
Appearance & Odor: Milky-white liquid, citrus fragrance		

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°F	Method Used: ASTM-D56	
Flammable Limits: Not Established	Flame Extension: N/A	
Extinguishing Media: Product does not support combo	ustion. Use extinguishing media appropriate for surrounding fire.	
	Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed	
Unusual Fire & Explosive Hazards: Combustion products are toxic.		

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes and Oral	
Effects of Overexposure-			
Conditions to Avoid:	d: May be harmful if swallowed. Symptoms may include abdominal pain and diarrhea.		
	Inhalation of product mist may cause respiratory irritation.		
	Avoid contact with eyes . Avoid prolonged or repeated contact with skin . Do not swallow. Avoid		
	breathing product mist. Wash thoroughly after handling.		
Conditions Aggravated by Use:	: Use of this product may aggravate preexisting skin; eye; and respiratory disorders including asthma and		
	dermatitis.		
Emergency & First Aid Procedures:			
Eyes:	: Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses. Get medical attention if		
	irritation persists.		
Skin:	kin: Wash skin thoroughly with soap and water. Get medical attention if irritation persists. Wash		
	contaminated clothing before reuse.		
Ingestion:	on: Do not induce vomiting. Drink one or two glasses of water to dilute product. Get medical attention. Do		
	not give anything by mouth to an unc		
Inhalation:	1: In case of respiratory irritation; move person to fresh air. Get medical attention if irritation persists.		

SECTION VI: REACTIVITY DATA

Stability: Stable	Incompatible Materials: Strong oxidizers
Hazardous Decomposition Products: Silicon dioxide, CO, CO2	Hazardous Polymerization: Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case

Material is Released or Spilled: Small spills of one gallon or less may be flushed with plenty of water to sanitary sewer system (If

permitted by local sewer regulations). Dike and contain large spills with inert material and transfer liquid

to containers for disposal. Keep spill out of storm sewers and waterways.

Waste Disposal Method: Dispose of in compliance with all federal, state and local laws and regulations

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection: None required

Ventilation: Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.

Protective Gloves(Specify Type): Rubber or other impervious gloves are recommended for prolonged or repeated skin contact.

Eye Protection(Specify Type): Splash goggles or safety glasses are recommended.

Other Protective Equipment: See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep out of reach of children.

Other Precautions: Keep from freezing.

© SCC 06/08/2012 Name: Title: Ronald T. Cook

Manager, Regulatory Affairs Effective Date: 06/08/2012 Supercedes:

06/08/2009 PREMIUM WOOD POLISH (RTU)

Ref. 29 CFR 1910.1200 (OSHA) Changes: General Review

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.