

V<sub>3</sub>


MSDS Information

VERONA MARBLE COMPANY  
TECHNICAL ASSISTANCE CORPORATION8311 EASTPOINT DRIVE, SUITE 800  
DALLAS, TX 75227TELEPHONE  
(214)381-8456FAX  
(214)381-4896WEB  
www.vmctac.com**Material Safety Data Sheet****Product Name: V3**

24 Hour Emergency Number - Chem-Tel: 1-800-255-3924

Revision Date: 07/19/2013

Pages: 3

**SECTION 1****OSHA HAZARD CLASSIFICATIONS**

NONE

**SECTION 2****PRINCIPAL AND/OR HAZARDOUS COMPONENTS**

TRICHLOROETHYLENE

**SECTION 3****PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE:	GOLDEN WITH STRONG ODOR
VAPOR DENSITY (Air):	N/A
VAPOR PRESSURE (mm Hg):	N/A
BOILING POINT:	86.7°C
FLASH POINT:	410°C
SOLUBILITY (Water):	IS NOT

**SECTION 4****FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT:	410°C
FLAMMIBILITY LIMITS:	N/A
EXTINGUISHING MEDIA:	NONE REQUIRED
SPECIAL FIRE FIGHTING PROCEDURES:	NONE REQUIRED

**SECTION 5****REACTIVITY DATA**

STABILITY:	STABLE
CONDITIONS TO AVOID:	NONE KNOWN
INCOMPATIBILITY:	
HAZARDOUS DECOMPOSITION PRODUCTS:	NONE KNOWN

**SECTION 6****HEALTH HAZARD DATA**

INHALATION:	NONE KNOWN
CHRONIC EXPOSURE:	CONTINUED CONTACT MAY IRRITATE THE SKIN. INGESTION MAY RESULT IN NAUSEA, VOMITING, AND/OR DIARRHEA.
EYE CONTACT:	CAN PRODUCE SLIGHT IRRITATION AND STING
SKIN CONTACT:	CAN PRODUCE SLIGHT IRRITATION ON THE SKIN
INGESTION:	CAN IRRITATE THE DIGESTIVE SYSTEM
PRIMARY ROUTE OF ENTRY:	INGESTION AND SKIN - IN SOME CASES

V<sub>3</sub> MSDS INFORMATION

V<sub>3</sub>

MSDS Information

**Material Safety Data Sheet**VERONA MARBLE COMPANY  
TECHNICAL ASSISTANCE CORPORATION8311 EASTPOINT DRIVE, SUITE 800  
DALLAS, TX 75227TELEPHONE  
(214)381-8456FAX  
(214)381-4896WEB  
www.vmctac.com**SECTION 7****HANDLING PRECAUTIONS**

HANDLING: IT IS ADVISABLE TO USE GLOVES. ENVIROMENT ALWAYS VENTILATED.

STORING: KEEP IT IN THE CAN OF ORIGIN, CLOSED, IN A DRY PLACE AND SHADED PLACE. NOT TO BE EXPOSED TO THE SUNLIGHT.

PACKING MATERIAL: IN SPECIAL PVC CANS, COEX APPROVED FOR SOLVENT PRODUCTS ( MAX. 2 YEARS ) OR IN METAL CANS.

**SECTION 8****EMERGENCY AND FIRST AID INFORMATION**

EYE EXPOSURE: IMMEDIATELY FLUSH EYES WITH COOL RUNNING WATER FOR AT LEAST 15 MINUTES OCCASIONALLY HOLDING EYELIDS OPEN TO INSURE FLUSHING THE ENTIRE EYEBALL. SEE A PHYSICIAN, PREFERABLY AN OPHTHALMOLOGIST.

SKIN EXPOSURE: WASH OFF SKIN WITH SOAP AND WATER. SEE A PHYSICIAN IF IRRITATION PERSISTS.

INGESTION: DRINK WATER, PREFERABLY IN SMALL AMOUNTS, BUT FREQUENT DOSES. DO NOT INDUCE VOMITING.

**SECTION 9****SPILL AND LEAK PROCEDURES**

IMPORTANT: BEFORE RESPONDING TO A SPILL OR LEAK OF THIS PRODUCT, REVIEW EACH SECTION OF THIS MSDS. FOLLOW THE RECOMMENDATIONS GIVEN IN THE HANDLING PRECAUTION SECTION. CHECK THE FIRE AND EXPLOSION DATA SECTION TO DETERMINE IF THE USE OF NON-SPARKING TOOLS IS MERITED. IF IRRITATING FUMES ARE PRESENT, CONSIDER EVACUATION OF ENCLOSED AREAS.

EMERGENCY RESPONSE ASSISTANCE: EMERGENCY RESPONSE TECHNICAL INFORMATION IS AVAILABLE 24 HOURS A DAY FROM CHEM-TEL AT 1-800-255-3924.

SPILLS: TABSORB ON AN ABSORBENT MATERIAL AND DISPOSE OF IN AN APPROVED CONTAINER. NEUTRALIZE ANY RESIDUAL WITH SODIUM CARBONATE OR SODIUM BICARBONATE AND FLUSH TO SEWER.

NOTE: FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS GOVERNING THE RELEASE OR DISPOSAL OF HAZARDOUS WASTES. HOWEVER, INSURE PROPER MANAGEMENT OF ANY RESIDUALS REMAINING IN THE CONTAINER.

**MSDS INFORMATION**V<sub>3</sub>

V<sub>3</sub>

MSDS Information

**Material Safety Data Sheet**VERONA MARBLE COMPANY  
TECHNICAL ASSISTANCE CORPORATION8311 EASTPOINT DRIVE, SUITE 800  
DALLAS, TX 75227TELEPHONE  
(214)381-8456FAX  
(214)381-4896WEB  
www.vmctac.com**SECTION 10****REGULATORY PROCEDURES**

DOT PROPER SHIPPING NAME: TRICHLOROETHYLENE  
 HAZARD CLASS: UN# 1710  
 PACKING GROUP: III  
 EPA REGISTRATION: NOT REQUIRED  
 TSCA INVENTORY: ALL COMPONENTS INCLUDED IN THE INVENTORY  
 FDA REGULATION(S): NONE KNOWN  
 SARA 302 EXTREMELY HAZARDOUS SUBSTANCE LIST: NO  
 SARA 312 HAZARD CLASSIFICATION(S): NO  
 SARA 313 TOXIC CHEMICALS LIST: NO  
 NFPA RATINGS: HEALTH 2, FLAMMABILITY 0, REACTIVITY 0  
 NPCA/HMIS RATINGS: HEALTH 2, FLAMMABILITY 0, REACTIVITY 0  
 HAZARD RATING KEY: 4-SEVERE, 3-SERIOUS, 2-MODERATE, 1-SLIGHT, 0-MINIMAL

The information on this Material Safety Data Sheet reflects the latest information and data that we have on hazards, properties and handling of this product under the recommended conditions of use. Any use of this product or method or application which is not described in the Product Data Sheet is the responsibility of the user.

This MSDS was prepared to comply with the OSHA Hazard Communication Standards

V<sub>3</sub> MSDS INFORMATION