Material Safety Data Sheet

		(1)	15D 5)					
Product Number: # 451, 452, 455 467, 468, 469 476, 478, 482 Product Name: Glisten Metered A		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.						
Section I – Product and Co	mpany In	formation						
F kutkdwqt 'Name:F gugtv'Xcmg{ 'U	tkdwikpi"""Go ۽	wkpi"'''''Go ggti gpe{ 'Telephone Number: (800) 535-5053 ''''''(800) 654-4752						
Address: 55825"RqmiUtggv."Eqcej gmc"EC";	Telephone N	Telephone Number for Information: (800) 654-4752 (405) 682-2541						
53603 Polk Street	Date Prepared	Date Prepared: 03/08/2011						
Coachella, CA 92236	Signature of	Signature of Preparer (optional)						
HMIS Ratings Heal	y: 4 Read	4 Reactivity: 1 Personal Protection: A						
Section II - Hazardous Ing	edients/I	dentity Info	rmation					
Hazardous Components	CAS #		OSHA PEL	ACGIH TLV	Other Limit	s %(op	otional)	
Acetone	CAS	# 67-64-1	750 ppm	750 ppm	N/A	>10	.0%	
Liquefied Petroleum Gas	CAS	# 68476-86-8	1000 ppm	800 ppm	N/A	>10	.0%	
Fragrance	No C	AS #	N/A	N/A	N/A	<5	5.0%	
Benzene***	71	-43-2	N/A	N/A	N/A	tra	ace	
Cumene***	98	8-82-8	N/A	N/A	N/A	tı	race	
Acetaldehyde***	75	-07-0	N/A	N/A	N/A	tra	ace	
Toluene***	10	8-88-3	N/A	N/A	N/A	tra	ace	
Ethylene Oxide*** ##	75-21-8		N/A	N/A	N/A		ace	
*** Indicates a product known to the s	tate of Califo	rnia to cause car	ncer per Proposition 6	55 ## is only foun	d in products 460	and 483		
Section III - Physical/Chem	ical Char	acteristics						
Boiling Point	oiling Point N/D		Specific Gravity ($H_2O = 1$)				0.70 - 0.80	
Vapor Pressure (mm Hg.)	Vapor Pressure (mm Hg.) N/D		Melting Point				N/A	
Vapor Density (AIR = 1)	Vapor Density (AIR = 1) >1		Evaporation Rate				<1	
Solubility in Water: N/E								
Appearance and Odor: Fine mist spra	with various	s fragrances.						
Section IV - Fire and Explo	sion Haza	ard Data						
Flash Point (Method Used) -156°F TCC CPR Section 40 Division 5, Class B, Flammable Aerosol						LEL 0.6%	UE 19%	
Extinguishing Media: Foam, dry che	nical, water,	or carbon dioxid	e (CO2)					
Special Fire Fighting Procedures: Wa explosion when exposed to extreme here								
Unusual Fire and Explosion Hazards:	CAUTION:	Contents under	pressure. Exposure	to temperatures above	120°F may cause l	oursting.		
J/A = Not Applicable $N/D = Not Determ$		= Not Established		Page 1 of 2	-	-	Sept. 1985	

Section V - Reactivity Data										
Stability	Unstable	Co	onditions to Avoid: Avoid o	pen flames and te	emperatures > 120F					
	Stable	X								
Incompatibility (Materials to Avoid): Avoid contact with strong oxidizing agents and strong acids.										
Hazardous Decomposition or Byproducts: Combustion may produce carbon monoxide.										
Hazardous Polymerizatio n	May Occur	Co	Conditions to Avoid: N/A							
	Will Not Occur	Х								
Section VI - Health Hazard Data										
Route(s) of Entry: Inhalation: Yes Skin: Yes Ingestion: Yes										
Health Hazards (Acute and Chronic): Acute – High vapor concentrations can cause irritation of the eyes and respiratory system. Chronic – Skin irritation can occur among sensitive individuals following repeated contact.										
Carcinogenicity: NTP: No IARC Monographs: No OSHA Regulated: No										
Signs and Symptoms of Exposure: INHALATION - Shortness of breath, dizziness and light headedness. EYES – Irritation and redness. SKIN – Irritation. INGESTION - May cause chemical pneumonia if aspired into lungs.										
Medical Conditions Generally Aggravated by Exposure: None Known										
Emergency and First Aid Procedures: INHALATION: Move to fresh air. SKIN: Wash with plenty of soap and water and seek medical attention if irritation persists. INGESTION: Seek medical attention or call your nearest poison control center.										
Section VII - Precautions for Safe Handling and Use										
Steps to be Taken in Case Material is Released or Spilled: If container is ruptured and begins to leak, place in a well ventilated area. Eliminate all ignition sources. Wash spills with soap and water. For large spills soak up with inert absorbent material such as sand.										
Waste Disposal Method: Landfill for absorbent material. Do not incinerate. Dispose of in accordance with local, state and federal regulations.										
Precautions to be Taken in Handling and Storing: Do not store near heat or open flame or temperatures exceeding 120°F.										
Other precautions: Handle as a flammable liquid										
Section VIII - Control Measures										
Respiratory Protection (Specify Type): None required										
Ventilation			Local Exhaust	Adequate	Special: N/A					
			Mechanical (General)	Adequate	Other: N/A					
Protective Glove contact	es: Rubber or plastic	for prolonge	Eye Protection: Safety goggles for splash protection							
Other Protective Clothing or Equipment: Eye wash/shower facility nearby										
Work/Hygienic	Work/Hygienic Practices: Good housekeeping practices. Avoid skin/eye contact.									