Material Safety Data Sheet

CLENACORP

1200 industrial Road #3, San Carlos, CA 94070

Product: CLENA POWDERED WAX **JANUARY 2011 SECTION 1** Product: CLENA POWDERED WAX Manufacturers Name/Address: **Emergency Phone Numbers** (650) 591-1733 Clenacorp **Information Phone Number** 1200 Industrial Road #3 San Carlos, CA 94070 (650) 591-1733 **SECTION II – HAZARDOUS INGREDIENTS** Hazardous Components-specific Chemical Identity: (Common Names) OSHAACGIH TLVOTHER LIMITS % OPTIONAL NO HAZARDOUS INGREDIENTS **SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS Boiling Point:** 600°F Specific Gravity (H20=1): 0.55 Vapor Pressure (mm Hg): Negligible **Melting Point:** 130°F Vapor Density (Air=1): Non-volatile Evaporation Rate (Butyl Acetate=1) Negligible Solubility in Water: Insoluble Appearance and Odor: Off white solid, mild fatty odor How to Detect this Substance: (Warning properties of substance as a gas, vapor, dust, or mist) Not Applicable **SECTION IV - FIRE AND EXPLOSION HAZARD DATA** Flash point (Method Used): 565°F (C.O.C.) Flammable Limits in Air, Volume % Autoignition temperature: Unknown LEL: Unknown **UEL:** Unknown **Extinguishing Media:** Water Spray X Carbon Dioxide X Foam __X_ Dry Chemical __X_ Other: Water Fog Special Fire Fighting Procedures: Do not use water stream, material floats. Unusual Fire and Explosion Hazards: Only usual hazards associated with organic dust. **SECTION V - HEALTH HAZARD DATA** Symptoms of Overexposure for each potential route of exposure. Inhaled: May cause slight irritation to nose and throat Contact with skin or eyes: May cause slight irritation Absorbed through skin: May cause slight irritation **Swallowed:** Unlikely to occur

Health Hazards:

Acute: Swallowed Powdered Wax has a mild laxative effect which can lead to nausea, vomiting and diarrhea. **Chronic:** Prolonged skin contact, along with poor personal hygiene, can lead to mild skin dermatitis.

Powdered Wax 1

Carcinogenicit X No This	s product's ingredients are not found in the lists below.	Osha regulated?
Signs and Syn	nptoms of Exposure: Molten material can cause therr	nal burns
Medical Condi	itions Generally Aggravated by Exposure: None	
Eye Contact: F Skin: Wash ha Inhaled: None	rst Aid Procedures: Flush with water for 15 minutes, contact physician and water after each use and at the end contact physician, hospital or poison control center for in	
SECTION VI	- REACTIVITY DATA	
,		ditions to Avoid: None
Incompatibility	_Stable y (Materials to Avoid): Strong Oxidizing Agents composition or Byproducts: Carbon Dioxide, Carbor	ı Monoxide
Hazardous Polymerization	n: X_Will Not Occur Will Occur	
Conditions to	Avoid: None	
Steps to Be Ta procedures.	- SPILL, LEAK, AND DISPOSAL PROCEDURES aken in Case Material is Released or Spilled: Materia al Method: No special measures necessary. Dispose of	
_	Be Taken in Handling and Storing: No special prec	autions necessary.
Other Precauti		
SECTION VIII	I - SPECIAL HANDLING INFORMATION	
Respiratory Pr	rotection (Specify Type): Disposal dust respirator. 3M mo	odel 8710 is recommended.
Ventilation:	Local Exhaust: If needed for heated fumes Mechanical (General): None required	Special: No special equipment
Other Handling	g and Storage Requirements: Material is combustible	e. Do not store near strong oxidizing agents.
Protective Gloves: None required		Eye Protection: Chemical safety glasses
Other Protection	ve Clothing or Equipment: None required	
	Practices: Use good personal hygiene practices whe ean running water is readily available.	n handling. Wash hands after using product. Ensure

Powdered Wax 2