

MATERIAL SAFETY DATA SHEET

Page 1 of 4

1. PRODUCT AND COMPANY IDENTIFICATION

NAME: BLUE STAR

USE: ALKALINE LAUNDRY DETERGENT

LABEL BRAND: U S CHEMICAL

MSDS # 101256B CODE # 057734, 057736

USCHEMICAL. 316 HART STREET. WATERTOWN, WI 53094 USA

MEDICAL EMERGENCY #: 1-866-923-4913 USA SPILL EMERGENCY #: 1-800-424-9300 USA

PRODUCT INFORMATION #: 1-800-558-9566 (8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)

INTERNET ADDRESS: www.uschemical.com

REVIEWED 4-19-12 REVISED 4-19-12 SECTION REVISED: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

DANGER. CORROSIVE LIQUID. CAUSES EYE AND SKIN BURNS.

HARMFUL OR FATAL IF SWALLOWED.

PRINCIPLE ROUTES OF EXPOSURE: EYES, SKIN, INGESTION, INHALATION.

POTENTIAL ACUTE HEALTH EFFECTS

EYES: CORROSIVE. CAUSES EYE BURNS. MAY CAUSE PERMANENT DAMAGE INCLUDING BLINDNESS

WITHOUT IMMEDIATE FIRST AID TREATMENT.

SKIN: CORROSIVE. CAUSES SKIN BURNS. MAY CAUSE PERMANENT DAMAGE.

HARMFUL CONTACT MAY NOT CAUSE IMMEDIATE PAIN.

INHALATION: CORROSIVE. INHALATION OF MISTS MAY CAUSE CORROSIVE EFFECTS TO NOSE, THROAT.

AND RESPIRATORY SYSTEM.

INGESTION: CORROSIVE. MAY CAUSE BURNS TO MOUTH, THROAT AND STOMACH.

HARMFUL OR FATAL IF SWALLOWED.

MEDICAL CONDITIONS AGGRAVATED: NONE KNOWN.

3. COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS#	% BY WT	LC50/LD50
SODIUM HYDROXIDE	1310-73-2	11.0	SEE 11.0

STATE RIGHT TO KNOW: THIS PRODUCT CONTAINS:

WATER/7732-18-5. SODIUM XYLENESULFONATE/1300-72-7. SODIUM HYDROXIDE/1310-73-2.

NONOXYNOL/9016-45-9, SODIUM 1-OCTANE SULFONATE/5324-84-5

4. FIRST AID MEASURES

Page 2 of 4

EYES: IMMEDIATELY FLUSH EYES WITH RUNNING WATER FOR 15-20 MINUTES, KEEPING EYELIDS OPEN. **SKIN:** IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15-20 MINUTES. REMOVE AND WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE RE-USE. **IF SWALLOWED:** RINSE MOUTH. GIVE A CUPFUL OF WATER OR MILK. THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT INDUCE VOMITING. NEVER GIVE

ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

INHALATION: IF BREATHING IS AFFECTED: REMOVE TO FRESH AIR.

ADMINISTER FIRST AID TREATMENT AS STATED ABOVE, THEN CALL 1-866-923-4913 OR

CONTACT PHYSICIAN FOR FURTHER MEDICAL INSTRUCTIONS.

NOTE TO PHYSICIAN: CALL 1-866-923-4913 FOR ASSISTANCE WITH THE MANAGEMENT OF EXPOSURES.

5. FIRE-FIGHTING MEASURES

FLAMMABILITY: NO HAZARD.

FLASH POINT: N.AP.

PRODUCTS OF COMBUSTION: SEE SECTION 10.

SUITABLE EXTINGUISHING MEDIA: FOR FIRES IN AREA, USE APPROPRIATE MEDIA. FOR EXAMPLE: WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, OR ALCOHOL FOAM. **SPECIFIC HAZARDS:** CORROSIVE PRODUCT MAY REACT WITH CERTAIN METALS. SEE 8. AND 10.

SPECIFIC METHODS: NORMAL FIRE FIGHTING PROCEDURES MAY BE USED.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: CORROSIVE. PUT ON PERSONAL PROTECTIVE EQUIPMENT. SEE 8.

SPILL RESPONSE: EVACUATE UNPROTECTED PERSONNEL FROM AREA. WEAR PROPER PROTECTIVE EQUIPMENT INCLUDING RUBBER BOOTS. VENTILATE AREA IF NEEDED. STOP LEAK IF YOU CAN DO SO WITHOUT RISK. DIKE OR DAM LARGE SPILLS. AVOID DIRECT DISCHARGE TO SEWER AND SURFACE WATERS. PUMP OR SCOOP TO CONTAINER OR SOAK UP WITH NON-COMBUSTIBLE INERT ABSORBENT MATERIALS. AFTER SPILL COLLECTION, RINSE AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES. BE CAREFUL AS SPILLS ARE SLIPPERY.

7. HANDLING AND STORAGE

HANDLING: FOLLOW ALL LABEL DIRECTIONS. INSTRUCT PERSONNEL ABOUT PROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES. AVOID INHALATION, INGESTION, AND CONTACT WITH SKIN, EYES AND CLOTHING. DO NOT TASTE OR SWALLOW. REMOVE AND WASH CONTAMINATED CLOTHING AND FOOTWEAR BEFORE RE-USE. PRODUCT RESIDUE MAY REMAIN IN EMPTY CONTAINERS. HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER.

STORAGE: ROTATE STOCK REGULARLY. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID TEMPERATURES BELOW 35°F OR ABOVE 120°F. PROTECT FROM FREEZING. STORAGE AT AMBIENT TEMPERATURES IN A DRY AREA OUT OF DIRECT SUNLIGHT IS RECOMMENDED. KEEP AWAY FROM FOOD AND DRINK. KEEP OUT OF CHILDREN'S REACH.

BLUE STAR MSDS # 101256B

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS:

SODIUM HYDROXIDE = 2 MG/M3 CEILING (ACGIH), 2 MG/M3 TWA (OSHA)

ENGINEERING CONTROLS: NONE REQUIRED, GENERAL ROOM VENTILATION IS TYPICALLY ADEQUATE.

Page 3 of 4

PERSONAL PROTECTION

EYES: SPLASH PROOF SAFEY GLASSES, SAFETY GOGGLES AND AN EYE WASH STATION. HANDS: CHEMICAL RESISTANT GLOVES: RUBBER OR NEOPRENE. LONG TYPE IF NEEDED. **RESPIRATORY:** IF MISTS/VAPORS ARE NOT CONTROLLED BY VENTILATION, WEAR SUITABLE RESPIRATOR. FEET: TYPICALLY NOT NEEDED. WEAR BOOTS DURING SPILL & WHEN EXPOSURE IS POSSIBLE. **BODY:** IF MAJOR EXPOSURE IS POSSIBLE, WEAR FULL-COVER PROTECTIVE CLOTHING.

9. PHYSICAL AND CHEMICAL PROPERTIES

FLASH POINT: N.AP. COLOR: BLUE

ODOR: LEMON UEL: N.AP. ph concentrate: Greater than 13.0 (BASIC) LEL: N.AP.

pH @ 2500 PPM SOLUTION: N.AP. **EVAPORATION RATE:** N.AP. pH @ USE DILUTION: N.AP. **ODOR THRESHOLD: N.AP** PHYSICAL STATE: LIQUID **VAPOR PRESSURE:** N.AP **SPECIFIC GRAVITY**: 1.189 VAPOR DENSITY: N. AP. **VISCOSITY: NON-VISCOUS** COEFF. OIL/WATER: N.AP.

BOILING POINT: N.AP. **WATER SOLUBILITY: COMPLETE**

MELTING POINT: N.AP. OTHER: N.AP.

10. STABILITY AND REACTIVITY

STABLE: YES

CONDITIONS TO AVOID: AVOID TEMPERATURES BELOW 35°F OR ABOVE 120°F.

MATERIALS TO AVOID: AVOID MIXING DIRECTLY WITH ANY OTHER CLEANING PRODUCT. AVOID ACIDS AND VARIOUS METALS (ALUMINUM, ZINC, TIN, BRASS OR BRONZE) WHICH CAN GENERATE FLAMMABLE HYDROGEN GAS. MIX ONLY WITH WATER.

DECOMPOSITION PRODUCTS: FIRE OR MIXING WITH INCOMPATIBLE MATERIALS MAY PRODUCE OXIDES OF CARBON AND OTHER TOXIC OR IRRITATING FUMES.

POSSIBILITY OF HAZARDOUS REACTIONS: AVOID MIXING DIRECTLY WITH ACIDS.

11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS: CORROSIVE. SEE SECTION 2.

CHRONIC EFFECTS: NONE KNOWN. NO REPORTABLE CARCINOGENS, MUTAGENS. SENSITIZERS, SYNERGISTIC MATERIALS, TERATOGENS, OR REPRODUCTIVE TOXINS.

LC50/LD50: SODIUM HYDROXIDE 50%: 350 MG/KG ORAL-RAT LD50

TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM.

OTHER TOXIC EFFECTS: NONE KNOWN.

12. ECOLOGICAL INFORMATION

Page 4 of 4

NOT AVAILABLE.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: UNDILUTED PRODUCT IS REGULATED UNDER ENVIRONMENTAL AND TRANSPORTATION LAWS AS A CORROSIVE WASTE (RCRA CLASS D002). DISPOSE OF ACCORDING TO ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS. CONSULT STATE AND LOCAL AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. MANAGE CHEMICAL WASTES THROUGH AN APPROVED WASTE TREATMENT FACILITY. DO NOT REUSE EMPTY CONTAINER. RINSE EMPTY CONTAINER THOROUGHLY WITH WATER BEFORE DISCARDING CONTAINER IN ACCORDANCE WITH CURRENT LOCAL COMMUNITY CODES. PLEASE RECYCLE EMPTY CONTAINER WHENEVER POSSIBLE.

14. TRANSPORT INFORMATION

DOT/TDG:

UN3266, CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (SODIUM HYDROXIDE), 8, II

DOT RQ: N.AP.
DOT ERG #: 154

15. REGULATORY INFORMATION

EPA CERCLA RQ: SODIUM HYDROXIDE = 1000 LB

EPA REGISTERED: NO OSHA HAZARDOUS: YES

PHOSPHORUS CONTENT: 0.00%

PROPOSITION 65: N.AP.

SARA 311/312 HAZARDS: ACUTE SARA 313 CHEMICALS: N.AP.

STATE RIGHT TO KNOW: SEE SECTION 3 FOR CHEMICAL NAMES.

TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY.

VOC: 0.40% CALCULATION METHOD USED IS BASED ON CALIFORNIA ARB STANDARD.

WHMIS CLASS: E

16. OTHER INFORMATION

NFPA RATING: HEALTH-3/FLAMMABILITY-0/REACTIVITY-1/SPECIAL HAZARD-N.AP.

HMIS RATING: HEALTH-3/FLAMMABILITY-0/REACTIVITY-1/PERSONAL PROTECTION-SEE 8.0

N.AV. = NOT AVAILABLE N.AP. = NOT APPLICABLE PREPARED BY: HEALTH AND SAFETY

NOTICE TO READER

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.