



Spartan Chemical Company, Inc.
Material Safety Data Sheet

683179

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):
FOAMING CAUSTIC CLEANER FP
Product Number: 3179

Product Division:
Janitorial

Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee OH 43537

Product/Technical Information: **1-(800)-537-8990**
Medical Emergency: **1-(888)-314-6171 (24 hours)**
Chemical Leak/Spill Emergency: **CHEMTREC 1-(800) 424-9300 (24 hours)**

Shipping Description: Corrosive liquids, n.o.s., 8, UN 1760, II (contains sodium hydroxide)

NFPA Ratings:	HMIS Ratings:
Health: 3 - Serious Fire: 0 - Minimal Reactivity: 1- Slight	Health: 3 - Serious Fire: 0 - Minimal Reactivity: 1- Slight Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	%Wt	CAS Registry No.	Table Z-1-A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
Sodium hydroxide	20-30	1310-73-2	2	Not Established	Not Established	No
Sodium glucoheptonate	1-5	31138-65-5	Not Established	Not Established	Not Established	No
Sodium silicate	1-5	1344-09-8	Not Established	Not Established	Not Established	No

SECTION III: PHYSICAL DATA

Boiling Point: 255 °F	Vapor Pressure: Unknown
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 14	Specific Gravity (H ₂ O=1): 1.345
Evaporation Rate (but.ac.=1): <1	Percent Solid by Weight: 30-35
Physical State: Liquid	
Appearance & Odor: Dark brown liquid, pungent odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 255 °F	Method Used: ASTM-D56
Flammable Limits: N/A	Flame Extension: N/A
Extinguishing Media: Product does not support combustion. Use extinguishing media appropriate for surrounding fire.	
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.	
Unusual Fire & Explosive Hazards: Products of combustion are toxic. Contact with aluminum or other reactive metals may release hydrogen gas. Heat is generated when mixed with water. This reaction may be violent.	

SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established	Primary Routes of Entry:	Inhalation, Skin Contact, Eyes & Oral
Effects of Overexposure- Conditions to Avoid:	CORROSIVE: Causes eye burns: Causes severe eye damage or irritation with symptoms of pain, redness and chemical burns. Eye contact may cause blindness. Causes skin burns: Causes severe skin damage or irritation with symptoms of pain, redness and chemical burns. Harmful contact may not cause immediate pain. Harmful or fatal if swallowed: Causes damage or chemical burns to esophagus and mucous membranes with symptoms of pain, nausea, vomiting and diarrhea. Harmful if inhaled: Breathing product vapor or mist may cause irritation or damage of the respiratory tract, with symptoms of nasal discomfort and discharge with chest pain and coughing. Do not get in eyes, on skin or on clothing. Do not breathe product vapors or mist. Do not swallow. Use with adequate ventilation. Wash thoroughly after handling.		
Conditions Aggravated by Use:	Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis.		

Emergency & First Aid Procedures:

Eyes:	Immediately flush eyes with water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Remove contaminated clothing and shoes. Flush skin with water for at least 15 minutes. Get medical attention. Wash contaminated clothing before reuse. Destroy contaminated shoes.
Ingestion:	Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting. Drink one or two glasses of water to dilute product. Do not give anything by mouth to an unconscious person.
Inhalation:	In case of respiratory irritation; move person to fresh air. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

SECTION VI: REACTIVITY DATA

Stability:	Stable	Incompatible Materials:	Oxidizing agents; acids; chlorinated solvents; reactive metals such as aluminum; zinc and tin.
Hazardous Decomposition Products:	Carbon dioxide, Carbon monoxide	Hazardous Polymerization:	Will Not Occur

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	Dike and contain spill with inert material (sand, earth, etc.) and transfer the liquid and solid separately to containers for recovery and disposal. Keep spill out of sewers and open bodies of water.
Waste Disposal Method:	Dispose of in compliance with all Federal, state and local laws and regulations. Incineration is the preferred method.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not normally required when good general ventilation is provided. However, if exposure limits (see Section II) are exceeded or respiratory irritation occurs, use of a NIOSH approved respirator suitable for the use conditions and chemicals in Section II should be considered.
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Rubber or other impervious gloves are recommended to prevent skin contact.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent contact.
Other Protective Equipment:	Use of impervious apron, boots, face shield and other protective equipment should be considered in order to prevent or minimize contact with this product. Eye wash stations and washing facilities should be readily accessible in areas where product is handled.. See 29 CFR 1910.132-138 for further guidance.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	Keep from freezing. Keep container closed when not in use.
Other Precautions:	Heat is generated when mixed with water. Add product to water to reduce the possibility of splattering. Keep out of reach of children.

© SCC 03/15/2005

FOAMING CAUSTIC CLEANER FP
Ref: 29 CFR 1910.1200 (OSHA)

Name: Ronald T. Cook

Effective Date: 03/15/2005

Changes: Update Sections I, II, IV, V, VII, VIII & IX

Title: Manager, Regulatory Affairs

Supercedes: 11/15/2000

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.