

If the product is not used with the Twist 'n Fill system or if there is an accidental release, the following eye protection is recommended: Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, skin contact with the concentrate is not expected to occur.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material is recommended: Gloves made from the following material(s) are recommended: Butyl Rubber, Neoprene.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, respiratory protection is not required.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

None Established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------|--|
| Specific Physical Form: | Liquid |
| Odor, Color, Grade: | Bright clear green-yellow liquid very slight soapy odor |
| General Physical Form: | Liquid |
| Flash Point | 197 °F [Test Method: Closed Cup] [Details: Will not sustain combustion (ASTM D-4206).] |
| Boiling point | > 200 °F |
| Vapor Pressure | < 27 psia [@ 131 °F] |
| Specific Gravity | Approximately 1 [Ref Std: WATER=1] |
| pH | 7 - 8 |
| Solubility in Water | Complete |
| Evaporation rate | Approximately 1 [Ref Std: WATER=1] |
| Volatile Organic Compounds | < 0.1 % [Test Method: calculated per CARB title 2] |
| Percent volatile | 55 - 100 % |
| VOC Less H2O & Exempt Solvents | < 5 g/l [Test Method: calculated per CARB title 2] |
| Viscosity | < 100 centipoise |