

Material Safety Data Sheet

FULL COURT WOOD FLOOR CLEANER

6102 1049
Squeaky Wood Floor Cl.
ECOLAB

61027049

Section 1. Chemical product and company identification

Trade name : FULL COURT WOOD FLOOR CLEANER
Product use : Floor Cleaner
Supplier : Ecolab Inc. Professional Products Division
370 N. Wabasha St.
St. Paul, MN 55102
1-800-247-5362
Code : 903733
Date of issue : 01-July-2005

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (In USA)

Section 2. Composition, Information on Ingredients

Name	CAS number	% by weight
propan-2-ol	67-63-0	2
alcohols, c10-14, ethoxylated	66455-15-0	5 - 20
acetic acid, (ethylenedinitrilo)tetra-, tetrasodium salt	64-02-8	1 - 5

Section 3. Hazards identification

Physical state : Liquid. (Liquid.)
Emergency overview : CAUTION!

MAY CAUSE EYE IRRITATION.

Repeated or prolonged contact with irritants may cause dermatitis.

Avoid contact with eyes. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Moderately irritating to the eyes.
Skin : Slightly irritating to the skin.
Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.
See toxicological information (section 11)

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention if irritation persists.
Skin contact : Wash with soap and water. Get medical attention if irritation develops. Wash clothing before reuse.
Inhalation : If inhaled, remove to fresh air.
Ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Section 5. Fire fighting measures

Flash point : > 100°C
Fire fighting media and instructions : Use an extinguishing agent suitable for surrounding fires.

Dike area of fire to prevent product run-off.
No specific hazard.

Special protective equipment for fire-fighters : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions** : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.--

Section 7. Handling and storage

- Handling** : Avoid contact with eyes. Wash thoroughly after handling.
- Storage** : Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area.
Store between -5 and 50°C

Section 8. Exposure Controls, Personal Protection

- Engineering controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protection

- Eyes** : Eye protection recommended.
- Hands** : No protective equipment is needed under normal use conditions.
- Skin** : No protective equipment is needed under normal use conditions.
- Respiratory** : No protective equipment is needed under normal use conditions.

Name

propan-2-ol

Exposure limits

OSHA PEL (United States, 6/1993).

TWA: 980 mg/m³ 8 hour(s). Form: All forms

TWA: 400 ppm 8 hour(s).

Section 9. Physical and chemical properties

- Physical state** : Liquid. (Liquid.)
- Color** : Orange.
- Odor** : Alcohol like.
- pH** : 9 (100%)
- Boiling/condensation point** : 100 °C
- Specific gravity** : 1.005 (Water = 1)

Section 10. Stability and reactivity

- Stability** : The product is stable.
- Reactivity** : Slightly reactive to reactive with acids.

Section 11. Toxicological information

Potential acute health effects

- Eyes** : Moderately irritating to the eyes.
- Skin** : Slightly irritating to the skin.
- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Chronic effects on humans** : Contains material which causes damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Section 12. Ecological information

Products of degradation : These products are carbon oxides (CO, CO₂) and water, nitrogen oxides (NO, NO₂ ...). Some metallic oxides.

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	Not regulated.	-	-	-	-

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

HCS Classification : Irritating material
Target organ effects

U.S. Federal regulations : SARA 302/304/311/312 extremely hazardous substances: None.
SARA 302/304 emergency planning and notification: None.

TSCA 8(b) Inventory : All materials are listed or exempt.

SARA 313 : Product name Concentration
Form R - Reporting requirements: propan-2-ol 2.476

California prop. 65 : No products were found.

Section 16. Other information

Hazardous Material Information System (U.S.A.)	Health	1
	Fire hazard	0
	Reactivity	0
	Personal protection	A

Date of issue : 01-July-2005.
Responsible name : Regulatory Affairs
Date of previous issue : 16-March-2005.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.