

Material Safety Data Sheet



PHAZER MULTI 25 FLOOR FINISH

Section 1. Chemical product and company identification

Trade name : PHAZER MULTI 25 FLOOR FINISH
Product use : Floor care product
Supplier : Ecolab Co.
5105 Tomken Road
Mississauga ON L4W 2X5
1-800-352-5326
Code : 908083-03
Date of issue : 15-November-2007

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

Name	CAS number	% by weight
ethanol, 2-(2-ethoxyethoxy)-	111-90-0	5- 10

Section 3. Hazards identification

Physical state : Liquid. [Liquid.]
Emergency overview : CAUTION!
MAY CAUSE EYE IRRITATION.
Repeated or prolonged contact with irritants may cause dermatitis.
Avoid contact with eyes. Wash thoroughly after handling.
Routes of entry : Skin contact, Eye contact, Inhalation, Ingestion
Potential acute health effects
Eyes : Slightly irritating to the eyes.
Skin : Slightly irritating to the skin.
Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

See toxicological information (section 11)

Section 4. First-aid measures

Eye contact : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin Contact : Flush contaminated skin with plenty of water. Wash clothing before reuse.
Inhalation : If inhaled, remove to fresh air.
Ingestion : Do not induce vomiting. Never give anything by mouth to an unconscious person. If irritation persists, get medical attention.

Section 5. Fire-fighting measures

Auto-ignition temperature : Not available.
Flash point : >93.333 °C (Closed cup)
Flammable limits
Upper: Not available.
Lower: Not available.
Products of combustion : Not available.
Fire-fighting media and instructions : Use an extinguishing agent suitable for the surrounding fire.
Dyke liquid for later disposal.

Special protective equipment for fire-fighters : No specific hazard.
: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Risk of explosion of the product in the presence of mechanical impact: Not available.

Risk of explosion of the product in the presence of static discharge: Not available.

Section 6. Accidental release measures

Personal Precautions : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.

Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up : If emergency personnel are unavailable, contain spilt material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain material to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal.

Section 7. Handling and storage

Handling : Wash thoroughly after handling.

Storage : Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area.
Store between the following temperatures: 15 and 45°C

Section 8. Exposure controls, personal protection

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protection :

Eyes : No protective equipment is needed under normal use conditions.

Hands : No protective equipment is needed under normal use conditions.

Skin : No protective equipment is needed under normal use conditions.

Respiratory : A respirator is not needed under normal and intended conditions of product use.

Consult local authorities for acceptable exposure limits.

Section 9. Physical and chemical properties

Physical state : Liquid. [Liquid.]

Colour : opaque

Odour : Acrylic.

pH : 8.55 [Conc. (% w/w): 100%]

Boiling/condensation point : Not available.

Melting/freezing point : Not available.

Specific gravity : 1.038

Vapour pressure : Not available.

Vapour density : Not available.

Odour threshold : Not available.

Evaporation rate : Not available.

LogK_{ow} : Not available.

Solubility : Easily soluble in cold water, hot water.

Section 10. Stability and reactivity

Stability : The product is stable.
Conditions of instability : Not available.
Reactivity : Reactive with metals.
Hazardous Decomposition : Not available.
Products

Section 11. Toxicological information

Potential acute health effects

Eyes : Slightly irritating to the eyes.
Skin : Slightly irritating to the skin.
Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.
Irritancy of Product : Hazardous by WHMIS criteria.

Potential chronic health effects

Carcinogenic effects : No known significant effects or critical hazards.
Mutagenic effects : No known significant effects or critical hazards.
Teratogenic effects : No known significant effects or critical hazards.
Reproductive effects : No known significant effects or critical hazards.
Sensitization to Product : No known significant effects or critical hazards.
Synergistic products (toxicologically) : Not available.

Toxicity data

<u>Ingredient name</u>	<u>Test</u>	<u>Route</u>	<u>Result</u>	<u>Species</u>
ethanol, 2-(2-ethoxyethoxy)-	LD50	Oral	7500 mg/kg	Rat
	LD50	Oral	5500 uL/kg	Rat

Target organs : Not available.

Section 12. Ecological information

Ecotoxicity

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
ethanol, 2-(2-ethoxyethoxy)-	Fish	96 hours	Acute LC50 26500 mg/L
	Fish	96 hours	Acute LC50 21400 mg/L
	Fish	96 hours	Acute LC50 13900 mg/L
	Fish	96 hours	Acute LC50 13400 mg/L
	Fish	96 hours	Acute LC50 >10000 mg/L
	Fish	96 hours	Acute LC50 9650 mg/L

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
TDG Classification	Not regulated.	-	-	-	-

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

WHMIS : Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*.

Section 16. Other information

Date of issue : 15-November-2007.
Responsible name : Regulatory Affairs
1-800-352-5326
Date of previous issue : No previous validation.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.