MSDS

Material Safety Data Sheet 1530 Conforms to ANSI Z-400.1-1993

Chemtel 24 Hour Emergency Response (800) 255-3924

Fulton Distributing Co.

53-603 Polk Street Coachella, CA 92236

(760) 262-6200

1 Chem	ical Produc	ct and Con	npany Iden	tification
--------	-------------	------------	------------	------------

Product: Glisten Traffic Lane Carpet Cleaner Classification: Carpet Spot Remover D20

2 Composition/Information on Hazardous Ingredients

-					
Material	CAS#	%	OSHA(PEL)	TLV(ppm)	Other
2- Butoxyethanol*	111-76-2	<10	25 ppm	25 ppm	N/A
Sodium Metasilicate	1344-09-8	<4	N/E	N/E	N/A
Sodium Hydroxide	1310-73-2	<2	2mg/m³	N/A	N/A

3 Hazards Identification

Emergency Overview: Irritant. Causes skin and eye irritation. Avoid contact with skin and eyes.

Contact with Eyes: This product is destructive to eye tissues. Will cause burns that result in damage to the eyes and

even blindness if the solution remains in contact with the eye for a prolonged period.

Contact with Skin: Prolonged or repeated contact may cause irritation and drying of skin.

Skin Absorption: No data.

Ingestion Symptoms: Swallowing will irritate throat, esophagus and digestive tract. Product may cause burns to mucous

membranes of the mouth, throat, esophagus and stomach.

Inhalation Symptoms: Airborne concentrations of mist/vapor may cause damage to the upper respiratory tract and even

lung tissue. If the product is heated, vapors are acutely toxic.

Chronic Effects: Respiratory tract damage may result in increased succeptability to respiratory illness. Excessive

inhalation exposure may result in liver and kidney injury.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult,

give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute

remaining residue. Seek medical attention.

5/25/2011 0001 1530 Glisten Traffic Lane Carpet Cleaner Page 1 of 3

5 Fire Fighting Measures

Flash Point(F° TCC): >200°F Flammable Limits: LEL No Data UEL No Data

Auto Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

If used according to directions respirator not required.

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

Corrosive

Dailing Dain4/E0\	04005	Calubility in Mary	0.1.1.1.	Odam D. C.
Boiling Point(F°):	>212°F	Solubility in Water:	Soluble	Odor: Butyl
Specific Gravity: Appearance:	1.05 Clear	Volatiles(% by Wt.): Vapor Density:	82 >1	pH: 13 - 14 VOC: <130 g/L
vaporation Rate:	<1	Vapor Pressure:	>1 <17 mm Hg	VOC: <130 g/L Freezing Point(F°): <32°F
vaporation Nate.	<1	< means less than	> means greater th	• , ,
Typical va	alues should not	typical values based on mat	erial tested but ma	y vary from sample to sample. specific lot or as specific items.
10 Stability and Re	activity			
Stability: Stable	Cor	ditions to Avoid: Temp. Ex	ktremes	
Materials to Avoid:	Strong Oxidize	rs		
Hazardous Decom Carbon oxides	position Produ	cts:		
Hazardous Polymei Will Not Occur	rization:			
11 Toxicological In				
No Toxicology Inforn		le.		
12 Ecological Infor	mation			
No data available.				
13 Disposal Consid	derations			
Waste Disposal Me Dispose of waste		vith federal, state and local r	egulations	
14 Transport Inforr	nation			
HAZMAT: Yes	Hazard (Code: 1760	ID Number: UN17	760 Hazard Class: 8
Hazardous Division	on: Corrosive li	quid, n.o.s.		Packaging Group: III
Hazardous Conten	ts: Sodium hyd	droxide, Sodium silicate		
15 Regulatory Info	rmation			
Proposition 65: No	ot Listed.			
* This product is s	ubject to the re	porting requirements of S	ARA Title III.	
EPA: No				
	n .			
16 Other Information	711			
		alth 1 Flammabili	ty <u> </u>	tivity 0
HMIS/NFPA Hazard The information contains implied, is made re	Rating: He ained herein is begarding the acc	ased on the data available t uracy of this data or the resu	o us. It is believed	tivity 0 to be correct. No warranty, expressed from the use thereof. For further
	Rating: He ained herein is be agarding the acception stributor, Fulto	ased on the data available t uracy of this data or the resu	o us. It is believed	to be correct. No warranty, expressed