

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

SPARCLEAN SILVERWARE PRE-SOAK [57]

Product Number: 7657

Product Division: Janitorial

Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee OH 43537 Product/Technical Information: 1-(800)-537-8990

Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spill Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Non-Hazardous Products

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight	Health: 1- Slight
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
· ·	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing

on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z-1-A			
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	NTP, IARC or OSHA Carcinogen
Alcohol ethoxylate	1-5	68439-46-3	Not Established	Not Established	Not Established	No
Triethanolamine	1-5	102-71-6	5 (ACGIH)	Not Established	Not Established	No
Alcohol ethoxylate	1-5	34398-01-1	Not Established	Not Established	Not Established	No
Dicarboxylic fatty acid	1-5	53980-88-4	Not Established	Not Established	Not Established	No
Alpha-amylase	< 1.0	9000-90-2	Not Established	Not Established	Not Established	No
Protease	< 1.0	9014-01-1	Not Established	Not Established	0.00006 ACGIH	No
Mannanase	< 1.0	37288-54-3	Not Established	Not Established	Not Established	No

SECTION III: PHYSICAL DATA

	Boiling Point: 212 °F	Vapor Pressure:	Not determined
	Vapor Density (AIR = 1): Unknown	Solubility in Water:	Complete
	pH: _{7.5} -8.0	Specific Gravity (H ₂ O=1):	1.007
Eva	aporation Rate (but.ace.=1): <1	Percent Solid by Weight:	5-10
	Physical State: Liquid		
	Appearance & Odor: Green liquid, mild odor		<u> </u>

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°F	Method Used: ASTM-D56
Flammable Limits: Not Established	Flame Extension: N/A
Extinguishing Media: Product does not so	upport combustion. Use extinguishing media appropriate for surrounding fire.
Special Fire Fighting Procedures: Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.	
Unusual Fire & Explosive Hazards: Combustion produc	cts are toxic.

Threshold Limit Value:	Not Established	Primary Routes of Entry: Inhalation, Skin Contact, Eyes and Oral
Effects of Overexposure- Conditions to Avoid:	May cause skin irritation: Symptoms May be harmful if swallowed: Symptoms Inhalation of product mist may cause coughing. Contains enzymes which may cau breath, wheezing and coughing.	y include pain, redness, swelling and tearing may include pain, redness and swelling. oms may include nausea, vomiting, pain and diarrhea. respiratory irritation: Symptoms may include nasal discomfort and se allergic respiratory reactions with symptoms of shortness of othing. Do not swallow. Avoid breathing product mist. Wash
Conditions Aggravated by Use:	Use of this product may aggravate pr dermatitis.	eexisting skin; eye and respiratory disorders including asthma and
Emergency & First Aid Procedures:		
Eyes:	Flush eyes with plenty of water for at	least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Remove contaminated clothing. Was irritation persists. Wash contaminate	h skin thoroughly with soap and water. Get medical attention if d clothing before reuse.
Ingestion:	Do not induce vomiting. Drink one or not give anything by mouth to an unc	two glasses of water to dilute product. Get medical attention. Do onscious person.
Inhalation:		·
SECTION VI: REACTIVITY DATA Stability:	Stable	Incompatible Materials: Strong oxidizing agents
Hazardous Decomposition Products:		Hazardous Polymerization: Will Not Occur
SECTION VII: SPILL OR LEAK PROC Steps to be Taken in Case Material is Released or Spilled:		be flushed with plenty of water to sanitary sewer system (If

SECTION VIII:	SPECIAL PRO	TECTION IN	FORMATION

 Respiratory Protection:	respirator suitable for the use-conditions and chemicals in Section II should be considered.		
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.		
Protective Gloves(Specify Type):	Rubber or other impervious gloves are recommended when handling product.		
	: Splash goggles are recommended when handling product.		
Other Protective Equipment:	:: See 29 CFR 1910.132-138 for further guidance.		

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	Wash thoroughly with soap and water after handling.
Other Precautions:	Keep out of reach of children.

© SCC 06/08/2012 Ronald T. Cook Title: Manager, Regulatory Affairs

Waste Disposal Method: Dispose of in compliance with all federal, state and local laws and regulations.

Effective Date: 06/08/2012 Supercedes: 09/01/2009 SPARCLEAN SILVERWARE PRE-SOAK

Ref: 29 CFR 1910.1200 (OSHA) Changes: General Review

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.