

885160



MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label): SoBreeze® Citrus Breeze 9000 Fragrance Aerosol Canister-5160		EMERGENCY TELEPHONE NO.: 1-800-535-5053 INFOTRAC
MANUFACTURER'S NAME: Rubbermaid Commercial Products Inc.		DATE OF LAST REVISION: 05/12/05
ADDRESS (Number, Street, City, State and Zip Code): 3124 Valley Avenue, Winchester, VA 22601		MANUFACTURER'S D-U-N-S NO.: NA
HAZARDOUS MATERIAL DESCRIPTION (49 CFR 172.101) Consumer Commodity, ORM-D		
ADDITIONAL HAZARD CLASSES (as applicable): NFPA Rating System: Fire-3/Health-1/Reactivity-0		
CHEMICAL FAMILY: Aerosol Mixture	FORMULA: NA	

SECTION II - INGREDIENTS (list all ingredients) 100% Needed

CAS REGISTRY NO.	%V	CHEMICAL NAME(S)	Listed as a Carcinogen in NTP IARC or OSHA 1910(z) (specify)
Fragrance Mixture*	12-18	Proprietary	NE
75-37-6	45-65	Dymel 152A	NE
67-84-1	25-35	2-Propanone *	** 750ppm (1750 mg/m ³) TLV; 1000 ppm (2300 mg/m ³) STEL (ACGIH); 750 ppm (1800 mg/m ³) PEL; 1000 ppm (2400 mg/m ³) STEL (OSHA); 250 ppm (550 mg/m ³) TWA (NIOSH)
111-90-0	5-10	Ethoxydiglycol *	NE
NE	<1	Odor Neutralizer	NE

*This product contains the following toxic chemicals subject to reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act and 40 CFR 372:

- Glycol Ether (Cas #: NA, Concentration: 8 %)
- Acetone (Cas # 67-84-1, Concentration: 29.5 %)

SECTION III - PHYSICAL DATA

BOILING POINT: ND	SPECIFIC GRAVITY (H ₂ O=1):	0.900-1.00 g/ml	
VAPOR PRESSURE: NA	PERCENT VOLATILE BY VOLUME (%):	NA	PERCENT SOLID BY WEIGHT (%): 0
VAPOR DENSITY (AIR = 1): NA	EVAPORATION RATE (n-butyl acetate=1):	ND	
SOLUBILITY IN WATER: Insoluble	pH=:	NA	
APPEARANCE AND ODOR: Clear liquid, pleasantly scented.	IS MATERIAL:	LIQUID	
		GAS	PASTE
		GEI	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	METHOD USED:	FLAMMABLE LIMITS:	LEL	UEL
(deg C): < -20 C	TCC		ND	ND
EXTINGUISHING MEDIA: chemical, foam or carbon dioxide.				
SPECIAL FIRE FIGHTING PROCEDURES: The use of self-contained breathing apparatus and protective clothing is recommended for fire fighters. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. Avoid spreading burning liquid with water used to cooling purposes.				
Unusual Fire & Explosion Hazards: Prolonged exposure to temperatures above 130°F may cause cans to burst.				