

Material Safety Data Sheet: AR-19 AEROSOL SAMPLE, NC

Supersedes Date 08/29/2006

Issuing Date 08/08/2008

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name AR-19 AEROSOL SAMPLE, NC
Recommended Use Water-borne coatings
Information on Manufacturer
 CHEMSEARCH DIV. OF NCH CORP.
 BOX 152170
 IRVING, TX 75015

Product Code 5002
Chemical Nature Alcoholic solution
Emergency Telephone Number
 CHEMTREC ® 800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview

Danger
 Extremely flammable
 May be harmful if inhaled
 May cause skin irritation
 Causes eye irritation
 Harmful or fatal if swallowed
 Contents under pressure

Color White

Physical State Liquid

Odor Alcoholic

Potential Health Effects

Principle Route of Exposure

Inhalation, Skin contact, Eye contact.

Primary Routes of Entry

Inhalation, Skin Absorption.

Acute Effects

Eyes

Causes eye irritation.

Skin

May cause skin irritation. The product may be absorbed through the skin. Repeated exposure may cause skin dryness or cracking.

Inhalation

May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause headache and dizziness.

Ingestion

Ingestion may cause irritation to mucous membranes. Causes headache, drowsiness or other effects to the central nervous system. Aspiration hazard if swallowed - can enter lungs and cause damage.

Chronic Effects

Liver and kidney injuries may occur.

Target Organ Effects

Skin, Eyes, Liver, Heart, Central nervous system, Respiratory system, Kidney.

Aggravated Medical Conditions

Skin disorders. Cardiovascular. Neurological disorders. Respiratory disorders. Kidney disorders.

Potential Environmental Effects

See Section 12 for additional Ecological information

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No	Weight %
Butane	106-97-8	1-5
Polydimethylsiloxane	63148-62-9	1-5
Isopropyl alcohol	67-63-0	10-15
Propane	74-98-6	1-5

4. FIRST AID MEASURES

General Advice

Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.

Eye Contact

Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.

Skin Contact

Wash off with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops and persists.

Inhalation

If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion

Drink 1 or 2 glasses of water. Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

Notes to Physician

Aspiration hazard if swallowed - can enter lungs and cause damage.

5. FIRE-FIGHTING MEASURES

Flash Point 75°F / 24°C

Method

Seta closed cup

Autoignition Temperature No information available

Flammability Limits in Air Mixture

Upper 12.7

Lower 1.8

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO2). Foam. Alcohol-resistant foam . Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific Hazards Arising from the Chemical

Solvent vapors are heavier than air and may spread along floors . Vapors may ignite and explode. Flame extension: >36 inches / >91.4 cm and Burnback: 6 inches / 15 cm

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health

2

Flammability

4

Instability

0

HMIS

Health

2

Flammability

4

Instability

0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13)
Methods for Cleaning Up	Pick up and transfer to properly labelled containers.
Neutralizing Agent	Not applicable

7. HANDLING AND STORAGE

Handling	Keep away from open flames, hot surfaces and sources of ignition. Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.			
Storage	Keep away from heat and sources of ignition.			
Storage Temperature	Minimum	35°F / 2°C	Maximum	120°F / 49°C
Storage Conditions	Indoor	X	Outdoor	Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Butane	TWA: 1000 ppm	no data available	TWA: 1900 mg/m ³ TWA: 800 ppm
Polydimethylsiloxane	No data available	no data available	no data available
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m ³	IDLH: 2000 ppm STEL 500 ppm STEL 1225 mg/m ³ TWA: 980 mg/m ³ TWA: 400 ppm
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1800 mg/m ³ TWA: 1000 ppm

Engineering Measures	Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment	
Eye/Face Protection	Safety glasses with side-shields.
Skin Protection	Impervious gloves.
Respiratory Protection	Use NIOSH approved respiratory protection.
General Hygiene Considerations	Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Viscosity	Non viscous
Color	White	Odor	Alcoholic
Appearance	Opaque	pH	11.2
Specific Gravity	0.93	Bulk Density	7.67
Evaporation Rate	9.3 (Butyl acetate=1)	Percent Volatile (Volume)	100
VOC Content (%)	19.9	Vapor Pressure	77.6 mmHg @ 70 °F
Vapor Density	1.6	Solubility	Completely soluble
Boiling Point/Range	176°F / 80°C		

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur .
Conditions to Avoid	Heat, flames, and sparks.
Incompatible Products	Bases. Acids. Strong oxidizing agents. Halogenated hydrocarbon. Aldehydes. Ketones. and. Aluminium. at high temperatures.
Hazardous Decomposition Products	Nitrogen oxides (NOx). Carbon oxides.
Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information	No information available
----------------------------	--------------------------

Component Information

Acute toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Butane	no data available	no data available	658 g/m ³ (Rat) 4 h	no data available	no data available
Polydimethylsiloxane	17 g/kg (Rat)	2 g/kg (Rabbit)	no data available	no data available	no data available
Isopropyl alcohol	4396 mg/kg (Rat)	12800 mg/kg (Rabbit) 12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h	no data available	no data available
Propane	no data available	658 mg/kg (Rat)	no data available	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Butane	no data available	no data available	no data available	no data available	CNS, liver, heart
Polydimethylsiloxane	no data available	no data available	no data available	no data available	no data available
Isopropyl alcohol	no data available	no data available	no data available	no data available	eyes, skin, respiratory system, kidney
Propane	no data available	no data available	no data available	no data available	CNS, liver, heart

Carcinogenicity

Component	ACGIH	IARC	NTP	OSHA	Other
Butane	not applicable	not applicable	not applicable	not applicable	not applicable
Polydimethylsiloxane	not applicable	not applicable	not applicable	not applicable	not applicable
Isopropyl alcohol	not applicable	not applicable	not applicable	not applicable	not applicable
Propane	not applicable	not applicable	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information No information available

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Butane	no data available	no data available	no data available	no data available	2.89
Polydimethylsiloxane	no data available	no data available	no data available	no data available	N/A
Isopropyl alcohol	EC50> 1000 mg/L Scenedesmus subspicatus 72 h EC50> 1000 mg/L Scenedesmus subspicatus 96 h	LC50= 61200 mg/L Pimephales promelas 96 h LC50= 94900 mg/L Pimephales promelas 96 h LC50= 9640 mg/L Pimephales promelas 96 h	EC50 = 35390 mg/L 5 min	EC50 = 13299 mg/L 48 h	0.05
Propane	no data available	no data available	no data available	no data available	2.3

Persistence and Degradability No information available
 Bioaccumulation No information available
 Mobility No information available

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of as hazardous waste in compliance with local and national regulations
 Container Disposal Contents under pressure Do not puncture. Empty containers should be taken for local recycling, recovery or waste disposal

14. TRANSPORT INFORMATION

DOT
 Proper Shipping Name
 Hazard Class
 Description
 DOT
 Consumer commodity
 ORM-D
 Consumer commodity ,ORM-D,

TDG
 Proper shipping name
 Hazard Class
 UN-No
 Description
 Aerosols
 2.1
 UN1950
 AEROSOLS,2.1,UN1950 LTD. QTY.

ICAO
 UN-No
 Proper Shipping Name
 Hazard Class
 Shipping Description
 UN1950
 Aerosols
 2.1
 Aerosols,UN1950 2.1 LTD. QTY.

IATA
 UN-No
 Proper Shipping Name
 Hazard Class
 ERG Code
 Shipping Description
 UN1950
 Aerosols, flammable
 2.1
 10L
 UN1950,Aerosols, flammable,2.1 LTD. QTY.

IMDG/IMO
 Proper Shipping Name
 Hazard Class
 UN-No
 EmS No.
 Shipping Description
 Aerosols
 2
 UN1950
 F-D, S-U
 UN1950, Aerosols,2.1 LTD QTY.

15. REGULATORY INFORMATION

Inventories

TSCA Complies
 DSL Complies
 U.S. Federal Regulations
 SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Isopropyl alcohol	67-63-0	10-15	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Butane	Not applicable	Not applicable
Polydimethylsiloxane	Not applicable	Not applicable
Isopropyl alcohol	Not applicable	Not applicable
Propane	Not applicable	Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

A Compressed gases, B5 Flammable aerosol, D2B Toxic materials .



16. OTHER INFORMATION

Prepared By Kamal Singh
 Supercedes Date 08/29/2006
 Issuing Date 08/08/2008
 Reason for Revision No information available
 Glossary No information available
 List of References No information available

CHEMSEARCH DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.