

MATERIAL SAFETY DATA SHEET

NFPA RATING: Health = 3, Flammability = 0, Reactivity = 0

HMIS RATING: Health = / 3, Flammability = 0, Reactivity = 0

SECTION I – IDENTITY AND MANUFACTURER'S INFORMATION (960A)

Manufacturer's Name: HILLYARD INDUSTRIES

Address: 302 North Fourth Street
St. Joseph, MO 64501

Emergency Telephone No.: (800) 424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals.)

Product Name: ARSENAL RESTROOM CLEANER

Date Prepared: July 27, 2004

Prepared by: Regulatory Affairs Department

Other information calls: (816) 233-1321 (Ext. 8285)

<http://www.hillyard.com>

SECTION II – INGREDIENTS/IDENTITY INFORMATION

Components

(Specific Chemical Identity:

Common Name(s)	CAS#	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
Phosphoric acid*(1)	7664-38-2	1 mg./m ³	1 mg./m ³	3 mg/m ³	10-15%
Citric acid	77-92-9	not established	not established	not established	7-12
Water	7732-18-5	none	none	N.A.	---
1-Butoxy-2-Propanol	5131-66-8	not established	not established	N.A.	---
Linear Primary Alcohol Ethoxylate	68439-46-3	not established	not established	N.A.	---
Poly (oxy 1,2-EthanediyI)	9036-19-5	not established	not established	N.A.	---
Lauramine Oxide	1643-20-5	not established	not established	N.A.	---

*This product contains the following chemicals subject to the reporting requirements of SARA Title III, Sec. 313, and 40 CFR Part 372: Phosphoric acid.

(1) Regulated by OSHA, and the following states: CT, FL, IL, LA, MA, NJ, NY, PA, and RI. ; (2) Regulated by OSHA and the following states: FL, IL, LA, MA, NJ, PA, RI.

VOS = Less than 10%

SECTION III – PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: 208°F

Vapor Pressure (mm Hg.): 16.99

Vapor Density (AIR = 1): 1.32

Solubility in Water: complete

pH = 1.36

Specific Gravity (H₂O = 1): 25°C = 1.09 & 39°C = 1.09

Percent Volatile by Volume (%): 69.79%

Evaporation Rate (ethyl ether = 1): slower than 1

Appearance and Odor: Clear, pink liquid, cherry odor

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flash point: None to 200°F(T.C.C.) **Flammable Limits:** LEL = N.A. UEL = N.A.

Extinguishing Media: Foam, dry chemical, carbon dioxide, water spray.

Special Fire Fighting Procedures: Hot phosphoric acid is corrosive. Self contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

Unusual Fire and Explosion Hazards: May generate hydrogen gas in contact with some metals.

SECTION V – PHYSICAL HAZARDS

Stability: Stable **Conditions to Avoid:** None known to manufacturer.

Incompatibility (Materials to Avoid): Corrodes some metals and alloys; cyanides and strong alkalis (ammonia) or bleach.

Hazardous Decomposition Products or Byproducts: Hydrogen gas from contact with some metals.

Hazardous Polymerization: Will not occur **Conditions to Avoid:** N.A.

SECTION VI – HEALTH HAZARD DATA

Routes of entry: Inhalation? by mist Skin? yes Ingestion? yes

HEALTH HAZARDS (1. Acute and 2. Chronic)

1. Concentrate is harmful or fatal if swallowed. Concentrate was not considered to be a primary skin irritant per Federal Hazardous Substance Act; however, five out of six test subjects had curst formation by day seven. Concentrate was considered to be an eye irritant per FHSA. Neo-vacularization, an indication of corrosion, was observed in all six test subjects by day seven. Concentrate induced mortality in four of 10 test subjects at a dose of 5 g./kg. Inhalation - Overexposure may cause nose and throat irritation. Acute inhalation - 1 Hour Toxic Limit test - not toxic at nominal concentration of at least 44.69 mg/1 (actual concentration 62.04 mg./L). This was the maximum concentration that could be generated by this test. 2. None known by Hillyard Industries.

SECTION VI – HEALTH HAZARD DATA continued

Chemical listed as Carcinogen or Potential Carcinogen:

National Toxicology Program = No I.A.R.C. Monographs = No OSHA = No

This product has no carcinogens listed by IARC, NTP, NIOSH, or ACGIH as of this date, greater than or equal to 0.1%.

Signs and Symptoms of Exposure: Contact: burns of eyes, skin, and on mouth and lips after ingestion, with sour taste of acid, severe gastrointestinal irritation. Inhalation of high concentrations of vapors results in respiratory and eye irritation, narcosis, headache, nausea, dizziness.

Medical Conditions Generally Aggravated by Exposure: None known to manufacturer.

Emergency and First Aid Procedures: If swallowed get medical attention immediately. Inhalation - If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of contact, immediately flush eyes or skin with plenty of water for 15 minutes. Get medical attention immediately.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with Federal, State, and Local regulations. Use solvent-resistant eyewear with splash guards. Solvent-impermeable rubber gloves, rubber boots and rubber apron or suit to prevent skin contact. Avoid contamination of storm drains, sewers, or other unauthorized treatment drainage systems and natural waterways.

Waste Disposal Method: Disposal is regulated under the Resource Conservation and Recovery Act (40 CFR 261.22) as a corrosive waste. Regulated quantities should be neutralized by a permitted facility in accordance with applicable local, state, and federal regulations.

Precautions To Be Taken In Handling And Storing: Product residue may remain on or in empty containers. All precautions for handling the product must be used in handling the empty container or residue. Container disposal: Triple rinse (or equivalent) then offer clean, dry container for recycling or reconditioning. Waste from normal use may be sewered to a public-owned treatment works in compliance with applicable federal, state and local requirements.

Other Precautions: Avoid breathing vapors or fine fog spray mist. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe vapors or fine fog spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Do not take internally.

SECTION VIII – CONTROL MEASURES

Respiratory Protection (Specify Type):

Not usually necessary. If spraying in a fine fog mist use NIOSH approved respirator (TC-21C-279, TC-23C-736, or TC-23C-745).

Ventilation: At least 3 air exchanges per hour suggest in good public restrooms.

Local Exhaust = Recommended Mechanical (General) = Recommended Special = N.A. Other = N.A.

Protective Gloves: Impervious gloves (rubber). **Eye Protection:** Solvent resistant eyewear with splash shields.

Other Protective Clothing or Equipment: Not usually necessary. Where there is a danger of contact with concentrated cleaner use Solvent resistant rubber gloves, rubber boots and rubber apron or suit to prevent skin contact.

Work / Hygienic Practices: Wash thoroughly after handling. Upon contact remove contaminated clothing; wash before reuse.

SECTION IX – TRANSPORTATION INFORMATION

Applicable regulations: DOT = No; IMCO = No; IATA = No

Proper shipping name: Cleaning compound

UN No.: not applicable

Limited Qty.: not applicable

Hazard Class: not applicable

Labels required: not required

DOT Exception: not applicable

EPA Hazardous waste/number code: not listed

Hazardous waste characteristics:

Ignitability = not applicable; Corrosivity = yes; Reactivity = not applicable

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.