CEO/55

MSDS

Material Safety Data Sheet 1632 Conforms to ANSI Z-400, 1-1993

Chemtel 24 Hour Emergency Response (800) 255-3924

MAINTEX

13300 East Nelson Avenue City of Industry, CA 91746

(800) 446-1888

1. Chemical Product and Company Identification

Product: Power 92 Classification: Heavy Duty Cleaner/Degreaser F10

2. Composition/Information on Hazardous Ingredients

Material	CAS#	%	OSHA (PEL)	TVL (ppm)	Other
Potassium Hydroxide	1310-58-3	<15	N/A	2mg/m3	N/A
Tetrapotassium Pyrophosphate	7320-34-5	<12	N/A	10mg/m3	N/A
Phosphate Ester of Ethoxylated Alcohol	68130-97-2	<5	N/A	Irritant	N/A
Sodium Silicate	1344-09-8	<8	N/A	N/A	N/A

### 3. Hazards Identification

**Emergency Overview:** 

(Contains Potassium Hydroxide) Harmful or fatal if swallowed.

DANGER

Causes skin burns and severe eye damage. Avoid contact with

skin and eyes.

**Contact With Eyes:** 

This product is destructive to eye tissues. Will cause burns that result in damage to the eyes and even blindness if the solution

remains in contact with the eye for a prolonged period.

Contact With Skin:

Repeated or prolonged contact with skin may cause irritation,

drying and/or possible tissue damage.

Skin Absorption:

No data.

Ingestion Symptoms:

Swallowing will irritate throat, esophagus and digestive tract.

Product may cause burns to mucous membranes of the mouth,

throat, esophagus and stomach.

Inhalation Symptoms:

Airborne concentrations of mist/vapor may cause damage to the

upper respiratory tract and even lung tissue. If the product is

heated, vapors are acutely toxic.

Chronic Effects:

Respiratory tract damage may result in increased succeptability to

respiratory illness. Excessive inhalation exposure may result in

liver and kidney injury.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

## 4. First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek

medical attention.

**Skin:** If skin is contacted, wash affected area with soap and water. If irritation persists,

seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to

fresh air. If breathing is difficult, give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash

out mouth area and dilute remaining residue. Seek medical attention.

## 5. Fire Fighting Measures

Flash Point (F° TCC): >200°F Flammable Limits: LEL No Data UEL No Data

Auto-Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

**Special Fire Fighting Procedures:** 

Firefighters should wear a positive pressure NIOSH approved self-contained breathing

apparatus.

**Unusual Fire and Explosion Hazards:** 

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

#### 6. Accidental Release Measures

Large Spills (55 gallons or more): Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills: Mop up spill and rinse area.

### 7. Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

**Storage:** Store in original polyethylene container in a cool dry area, away from bleach and other chemicals.

## 8. Exposure Controls/Personal Protection

Ventilation and Engineering Controls: Local exhaust

Respiratory Protection: If used according to directions respirator not required.

Protective Gloves: Rubber Gloves

Eye Protection: Chemical Splash Goggles

#### 9. Physical and Chemical Properties

Boiling Point (F°): >212°F Solubility In Water: Soluble Odor: Neutral

Specific Gravity: 1.35 Volatiles (% by Wt.): 62 pH: 13.5 - 14

Appearance: Dark Brown

Vapor Density: >1

VOC: N/A

Evaporation Rate: <1

Vapor Pressure: <17 mm Hg

Freezing Point (F°): <40°F

**Key:** < means less than; > means greater than

These physical data are typical values based on material testing but may vary from sample

to sample.

Typical values should not be constructed as a guaranteed analysis of any specific lot or specific item.

### 10. Stability and Reactivity

Stability: Stable

Conditions to Avoid: Temp. Extremes

Materials to Avoid: Strong Oxidizers

Hazardous Decomposition Products: Carbon dioxide/monoxide

Hazardous Polymerization: Will Not Occur

### 11. Toxicological Information

No Toxicology Information is available.

### 12. Ecological Information

No Ecological Information is available.

### 13. Disposal Considerations

Waste Disposal Method: Dispose of waste in accordance with federal, state and local regulations.

#### 14. Transport Information

**HAZMAT:** Yes

Hazard Code: 1632

ID Number: UN1760

Hazard Class: 8

Hazardous Division: Corrosive Liquid n.o.s.

Packaging Group: II

Hazardous Contents: Potassium hydroxide, Sodium silicate

# 15. Regulatory Information

**Proposition 65:** Not Listed.

EPA: No

#### 16. Other Information

# **HMIS/NFPA Hazard Rating:**

Health 3

Flammability 0

Reactivity 1

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Maintex, Inc. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not

adhered to as stipulated in the data sheet. Additionally, Maintex, Inc. assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. For more information, contact Maintex, Inc.

MSDS Approval Date: 1/30/2007

For your safety, please ensure that you print and store all pages of this document together.