



Material Safety Data Sheet

Copyright, 2008, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) DEODORIZER - MOUNTAIN SPICE - CONCENTRATE (Product No. 14, Twist 'n Fill (tm) System)

MANUFACTURER: 3M

DIVISION: Building & Commercial Services Division

ADDRESS: 3M Center
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 06/11/2008

Supersedes Date: 07/27/2005

Document Group: 06-8476-1

Product Use:

Intended Use: Deodorizer

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYALKOXY ALCOHOLS	69013-18-9	30 - 60
FRAGRANCE (NJTSN 04499600-6518)	Trade Secret	10 - 30
WATER	7732-18-5	10 - 30
SORBITAN POLYETHOXY MONOLAURATE	9005-64-5	7 - 13
1-METHOXY-2-PROPANOL	107-98-2	1 - 5

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Liquid

Odor, Color, Grade: Clear; dark green color; strong spicy fragrance

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause severe eye irritation. May cause allergic skin reaction. May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Flash Point > 200 °F [*Test Method:* Closed Cup]

OSHA Flammability Classification: Class IIIB Combustible Liquid

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with water. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Keep out of the reach of children. This product is not intended to be used without prior dilution as specified on the product label. Avoid breathing of vapors, mists or spray. Avoid skin contact. Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid contact with oxidizing agents.

7.2 STORAGE

Keep container in well-ventilated area. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use in a well-ventilated area. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, special ventilation is not required.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, eye contact with the concentrate is not expected to occur.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, the following eye protection is recommended: Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, skin contact with the concentrate is not expected to occur.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select and use gloves and/or protective

clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material is recommended: Butyl Rubber. The following protective clothing material(s) are recommended: Apron - Neoprene.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, respiratory protection is not required.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
1-METHOXY-2-PROPANOL	ACGIH	TWA	100 ppm	
1-METHOXY-2-PROPANOL	ACGIH	STEL	150 ppm	
1-METHOXY-2-PROPANOL	OSHA	TWA	100 ppm	Table Z-1A
1-METHOXY-2-PROPANOL	OSHA	STEL	150 ppm	Table Z-1A
CADMIUM DUST	OSHA	TWA, as dust	0.2 mg/m3	Table Z-2
CADMIUM DUST	OSHA	CEIL, as dust	0.6 mg/m3	Table Z-2
COPPER COMPOUNDS	ACGIH	TWA, as Cu dust or mist	1 mg/m3	
COPPER COMPOUNDS	OSHA	TWA, as dust or mist	1 mg/m3	Table Z-1A
MANGANESE COMPOUNDS	OSHA	CEIL, as Mn	5 mg/m3	Table Z-1A
MANGANESE, INORGANIC COMPOUNDS	ACGIH	TWA, as Mn	0.2 mg/m3	
MERCURY NON-ALKYL, VAPOR	ACGIH	TWA, as Hg	0.05 mg/m3	Skin Notation*
MERCURY NON-ALKYL, VAPOR	OSHA	TWA, as Hg	0.05 mg/m3	Skin Notation*; Table Z-1A
MERCURY, ARYL & INORGANIC COMPOUNDS	OSHA	CEIL, as Hg	0.1 mg/m3	Skin Notation*; Table Z-1A
MERCURY, INORGANIC COMPOUNDS	ACGIH	TWA, as Hg	0.025 mg/m3	Skin Notation*; Table A4

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Liquid
Odor, Color, Grade:	Clear; dark green color; strong spicy fragrance
General Physical Form:	Liquid
Flash Point	> 200 °F [<i>Test Method:</i> Closed Cup]
Boiling point	Approximately 212 °F
Vapor Pressure	<=27 psia [@ 131 °F]

Specific Gravity
pH

1 [Ref Std: WATER=1]
6.5 - 8.5

Solubility in Water
Volatile Organic Compounds
VOC Less H2O & Exempt Solvents
Viscosity

Complete
11 - 35 % [Test Method: calculated per CARB title 2]
300 - 500 g/l [Test Method: calculated per CARB title 2]
< 100 centipoise

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

CHEMICAL FATE INFORMATION

A 3M Product Environmental Data Sheet (PED) is available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number

UPC

ID Number

UPC

70-0708-4014-8
70-0711-9213-5

00-48011-20120-2
00-48011-20120-2

70-0710-1410-7

00-48011-23897-0

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

STATE REGULATIONS

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

The components of this material are in compliance with the new chemical notification requirements for the Korean Existing Chemicals Inventory.

The components of this product are listed on the Australian Inventory of Chemical Substances.

All the components of this product are listed on China's Inventory of Chemical Substances.

The components of this product are in compliance with notification requirements in the Philippines.

The components of this product are listed on the Canadian Domestic Substances List.

INTERNATIONAL REGULATIONS

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Protection: X - See PPE section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency

situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 1: Product use information was modified.

Section 1: Division name was modified.

Copyright was modified.

Section 7: Handling information was modified.

Section 8: Skin protection phrase was modified.

Section 8: Respiratory protection information was modified.

Section 14: ID Number(s) and/or UPC(s) Template 1 was added.

Section 2: Ingredient table was added.

Section 8: Exposure guidelines ingredient information was added.

Section 8: Exposure guidelines data source legend was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com