# **Material Safety Data Sheet**



QUIK FILL 530 (NPE-FREE)

### Section 1. Chemical product and company identification

Trade name : QUIK FILL 530 (NPE-FREE)

Product use : Degreaser Supplier : Ecolab Inc.

370 N. Wabasha St. St. Paul, MN 55102 1-800-352-5326

Code : 903569

Date of issue : 15-October-2007

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

### Section 2. Composition, information on ingredients

<u>Name</u>	<u>CAS number</u>	% by weight
2-aminoethanol	141-43-5	5 - 20
alcohols, c10-14, ethoxylated	66455-15-0	1 - 5
xylenesulfonic acid, sodium salt	1300-72-7	1 - 5
disodium metasilicate	6834-92-0	1 - 5
acetic acid, (ethylenedinitrilo)tetra-, tetrasodium salt	64-02-8	1 - 5

### Section 3. Hazards identification

Physical state : Liquid. [Liquid.]
Emergency : DANGER!

overview

CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS.

HARMFUL IF SWALLOWED.

Do not ingest. Do not get in eyes, on skin or on clothing. Do not breathe vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Eyes : Corrosive to eyes.

Skin : Corrosive to the skin.

**Inhalation** : Corrosive to the respiratory system.

**Ingestion**: Harmful if swallowed. Causes burns to mouth, throat and stomach.

See toxicological information (section 11)

### Section 4. First aid measures

Eye contact: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and

continue flushing with plenty of water for at least 15 minutes. Get medical attention

immediately.

**Skin contact**: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes

thoroughly before reuse. Get medical attention immediately.

**Inhalation**: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

give oxygen. Get medical attention immediately.

**Ingestion**: Rinse mouth; then drink one or two large glasses of water. Do not induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention immediately.

# Section 5. Fire fighting measures

Flash point

: > 100°C

Fire-fighting media and

instructions

: Use an extinguishing agent suitable for the surrounding fire.

Dike liquid for later disposal.

No specific hazard.

for fire-fighters

Special protective equipment : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure

#### Section 6. Accidental release measures

Personal precautions : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.

**Environmental** precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

: If emergency personnel are unavailable, contain spilled material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

# Section 7. Handling and storage

Handling

: Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed. Use only with adequate ventilation. Do not breathe vapor or mist. Wash thoroughly after handling.

Storage

: Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, wellventilated area.

Store between the following temperatures: 10 and 45°C

# Section 8. Exposure controls, personal protection

**Engineering measures** 

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide eyewash and safety shower in area if contact or splash hazard exists.

#### Personal protection:

**Eyes** 

: Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.

Hands

: Use chemical-resistant, impervious gloves.

Skin

: Use synthetic apron, other protective equipment as necessary to prevent skin contact.

Respiratory

: Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are exceeded.

**Name** 

**Exposure limits** 

2-aminoethanol

ACGIH TLV (United States, 1/2006).

STEL: 15 mg/m<sup>3</sup> 15 minute(s). STEL: 6 ppm 15 minute(s). TWA: 7.5 mg/m<sup>3</sup> 8 hour(s). TWA: 3 ppm 8 hour(s).

OSHA PEL (United States, 11/2006).

TWA: 6 mg/m<sup>3</sup> 8 hour(s). TWA: 3 ppm 8 hour(s).

#### Page: 3/4

# Section 9. Physical and chemical properties

Physical state : Liquid. [Liquid.]
Color : fluorescent [Light]
Odor : Fragrance-like.

**pH** : 13.25 [Conc. (% w/w): 100%]

Specific gravity : 1.07

#### Section 10. Stability and reactivity

**Stability** : The product is stable.

**Reactivity** : Extremely reactive or incompatible with acids.

Reactive with metals.

# Section 11. Toxicological information

#### Potential acute health effects

Eyes : Corrosive to eyes.
Skin : Corrosive to the skin.

**Inhalation**: Corrosive to the respiratory system.

**Ingestion**: Harmful if swallowed. Causes burns to mouth, throat and stomach.

#### Potential chronic health effects

Chronic effects on humans

: Contains material which causes damage to the following organs: kidneys, liver, upper

respiratory tract, central nervous system (CNS).

# Section 12. Ecological information

#### Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Waste : Unused product is D002 (Corrosive)

classification

Consult your local or regional authorities.

### **Section 14. Transport information**

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	UN2491	Ethanolamine solutions	8	III	Not available.

#### APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

#### Section 15. Regulatory information

**HCS Classification** : Corrosive material

Target organ effects

U.S. Federal regulations : SARA 302/304/311/312 extremely hazardous substances: No products were

found

SARA 302/304 emergency planning and notification: No products were found.

**TSCA 8(b) inventory** : All materials are listed or exempt.

California Prop. 65 : No products were found.

# Section 16. Other information

Hazardous Material Information System (U.S.A.)



Date of issue : 15-October-2007.
Responsible name : Regulatory Affairs
Date of previous issue : 16-January-2006.

**Notice to reader** 

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.