

C030000

**MATERIAL SAFETY DATA SHEET**

This MSDS complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION					
NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special-0			HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B		
Manufacturer's Name: AMREP, INC.			DOT Hazard Classification: ORM-D		
Address: 990 Industrial Park Dr.			Identity (trade name as used on label):		
Address: Marietta, GA 30062			MISTY STAINLESS STEEL CLEANER		
Date Prepared: 03/29/96			Prepared By: LF		
Information Calls: (770)422-2071			MSDS Number: 141		
EMERGENCY RESPONSE NUMBER: 1-800-266-3924			Revision: 12		
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA					
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)
Hazardous Components 1% or greater; Carcinogens 0.1% or greater					Carcinogen Ref. Source **
PETROLEUM DISTILLATE		84742-54-7	Yes	5mg/M3	5mg/M3
PETROLEUM DISTILLATE		84742-88-7	No	100	100
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800
		74-98-6	No	1000	1000
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: N/A		Specific Gravity (H2O=1): Concentrate Only = .858			
Vapor Pressure: PSIG @ 70°F (Aerosols): Max 80		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E		Evaporation Rate ( = 1): N/E			
Solubility in Water: Insoluble		Water Reactivity: No			
Appearance and Odor: Clear liquid, lemon fragrance.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) FLAMMABLE >18 inches		Auto Ignition Temperature N/E		Flammability Limits in Air by % in Volume:	
				% LEL: N/E % UEL: N/E	
FLASH POINT AND METHOD USED (non-aerosols): N/A		EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.					
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [X] STABLE [ ] UNSTABLE		HAZARDOUS POLYMERIZATION [ ] WILL [X] WILL NOT OCCUR			
Incompatibility (Mix. to avoid): Strong oxidizers.		Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: CO, CO2.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [X] INHALATION [ ] INGESTION [X] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS					
ACUTE EFFECTS					
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.					
Eye Contact: Mild irritation.					
Skin Contact: Mild irritation.					
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.					
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, lung and kidney damage.					
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.					
Skin Contact: Wash with soap and water. If irritated, seek medical attention.					
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.					
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.					
Protective Gloves: Polyethylene gloves					
Eye Protection: Safety glasses recommended.					
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.					
Other Protective Clothing & Equipment: None					
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER.					
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.					
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.					
We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.					
** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only					

THIS MSDS IS CURRENT AS OF NOVEMBER 8, 1999. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at AMREP by these date codes and therefore must remain as the originating date.