MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

CQ0316 **Product number**

Product name Off the Wall Vandalism Mark & Stain Remover

Effective date 13-Sep-2011 **Brady Industries Company information**

Las Vegas, NV 89118 United States

General Assistance 702-876-3990 Company phone

800-424-9300 **Emergency telephone US Emergency telephone outside US** 703-527-3887

06 Version #

02-Aug-2011 Supersedes date

2. Hazards Identification

Emergency overview Aerosol. FLAMMABLE

CONTENTS UNDER PRESSURE.

VAPOR HARMFUL.

Harmful in contact with eyes. Irritating to skin. Irritating to respiratory system. Possible

cancer hazard - may cause cancer based on animal data.

Potential health effects

Routes of exposure Skin contact. Eye contact. Inhalation. Ingestion.

Contact may irritate or burn eyes. **Eyes**

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis. Irritating to skin.

Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Inhalation

Irritating to respiratory system. Prolonged inhalation may be harmful.

Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Ingestion

Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of

coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage.

May cause delayed lung injury.

Discomfort in the chest. Narcosis. Coughing. Jaundice. Conjunctivitis. Defatting of the Signs and symptoms

skin. Skin irritation.

3. Composition / Information on Ingredients			
Components	CAS#	Percent	
Methylene Chloride	75-09-2	40 - 50	
n-Butane	106-97-8	20 - 30	
Toluene	108-88-3	10 - 15	
Perchloroethylene	127-18-4	8 - 10	
Propane	74-98-6	8 - 10	
Propylene Oxide	75-56-9	0.1 - 0.5	
Non-hazardous and other components below reportable levels		1 - 2.5	

4. First Aid Measures

First aid procedures

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact Eye contact

lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation

develops and persists.

Product name: Off the Wall Vandalism Mark & Stain Remover

MSDS US Product #: 870-001 Revision date: 13-SEP-2011 Print date: 13-SEP-2011

Remove and isolate contaminated clothing and shoes. Wash off with warm water and Skin contact

soap. Get medical attention if irritation develops and persists.

Move to fresh air. Oxygen or artificial respiration if needed. Get medical attention if Inhalation

symptoms persist.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not Ingestion

induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Never give anything by mouth to a

victim who is unconscious or is having convulsions.

5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may

cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Foam. Dry chemical. Carbon dioxide (CO2).

Protection of firefighters

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the

leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid breathing

dust/fume/gas/mist/vapors/spray. Avoid contact with skin.

Storage

Contents under pressure. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Avoid exposure to long periods of sunlight. Keep out of the reach of children. Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS#	TWA	STEL	Ceiling
Methylene Chloride	75-09-2	50 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Toluene	108-88-3	20 ppm	Not established	Not established
Perchloroethylene	127-18-4	25 ppm	100 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Propylene Oxide	75-56-9	2 ppm	Not established	Not established

MSDS US Product #: 870-001 Revision date: 13-SEP-2011 Print date: 13-SEP-2011

OSHA

Components	CAS#	TWA	STEL	Ceiling
Methylene Chloride	75-09-2	25 ppm	125 ppm	Not established
Toluene	108-88-3	200 ppm	Not established	300 ppm
Perchloroethylene	127-18-4	100 ppm	Not established	200 ppm
Propane	74-98-6	1000 ppm	Not established	Not established
Propylene Oxide	75-56-9	100 ppm	Not established	Not established

Refer to the OSHA Standard 29 CFR 1910.1052 regarding requirements for employers to **Exposure guidelines**

control occupational exposure to methylene chloride.

Personal protective equipment

Eye / face protection Wear chemical goggles.

Skin protection Wear appropriate chemical resistant clothing.

When workers are facing concentrations above the exposure limit they must use Respiratory protection

appropriate certified respirators. If permissible levels are exceeded use NIOSH

mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas. 102.2 °F (38.9 °C) estimated **Boiling point**

Pale yellow Color

Density 0.8933 g/cm3 estimated Flammability (HOC) 18.61 kJ/g estimated

Flash back

-156 °F (-104.4 °C) Propellant Flash point

Form Aerosol. Not available Freezing point Solvent. Odor рΗ Not applicable

Physical state Liquid.

Pressure 40 - 55 psig @ 70F

Negligible Solubility 0.8934 estimated Specific gravity

10. Chemical Stability & Reactivity Information

Risk of ignition. Material is stable under normal conditions. **Chemical stability**

Conditions to avoid Heat, flames and sparks. Aerosol containers are unstable at temperatures above 49°C.

Hazardous decomposition products Hydrogen chloride. Irritants. Toxic gas.

11. Toxicological Information

Acute effects Acute LC50: 82 mg/l/4h estimated, Rat, Inhalation

Acute LD50: 55930 mg/kg estimated, Rat, Dermal

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Methylene Chloride 75-09-2 Oral LD50 Rat >2000 mg/kg; Inhalation LC50 Rat 76000 mg/m3 4 h

n-Butane 106-97-8 Inhalation LC50 Rat 658 mg/L 4 h

Perchloroethylene 127-18-4 Inhalation LC50 Rat 4000 ppm 4 h; Oral LD50 Rat 2629 mg/kg; Dermal LD50 Mouse

2800 mg/kg

Propane 74-98-6 Inhalation LC50 Rat 658 mg/L 4 h Propylene Oxide 75-56-9 Oral LD50 Rat 520 mg/kg

108-88-3 Inhalation LC50 Rat 12.5 mg/L 4 h; Inhalation LC50 Rat >26700 ppm 1 h; Oral LD50 Toluene

Rat 636 mg/kg; Dermal LD50 Rabbit 8390 mg/kg; Dermal LD50 Rat 12124 mg/kg

Sensitization Not expected to be hazardous by OSHA criteria.

MSDS US Product #: 870-001 Revision date: 13-SEP-2011 Print date: 13-SEP-2011

Carcinogenicity

Hazardous by OSHA criteria. Risk of cancer cannot be excluded with prolonged

exposure.

IARC - Group 2A (Probably Carcinogenic to Humans)

Perchloroethylene 127-18-4 Monograph 63 [1995]; Supplement 7 [1987]

IARC - Group 2B (Possibly Carcinogenic to Humans)

Methylene Chloride 75-09-2 Monograph 71 [1999]; Supplement 7 [1987] Propylene Oxide 75-56-9 Monograph 60 [1994]; Supplement 7 [1987] Teratogenicity Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity LC50 32.2 mg/L, Fish, 96.00 Hours,

EC50 30.14 mg/L, Daphnia, 48.00 Hours, IC50 633 mg/L, Algae, 72.00 Hours,

Not established. Components of this product are hazardous to aquatic life.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

D039: Waste Tetrachloroethylene

Disposal instructionsContents under pressure. Dispose of this material and its container to hazardous or

special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a

RCRA ignitable waste, D001.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306
Packaging non bulk 156, 306
Packaging bulk None

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class2.1Subsidiary hazard class6.1UN number1950

Marine pollutant Tetrachloroethylene

Additional information:

Packaging exceptions NOT a LTQ QTY

Labels required 2.1, 6.1

IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable, containing substances in Division

6.1, Packing Group III

Hazard class2.1Subsidiary hazard class6.1UN number1950

Additional information:

Packaging exceptions LTD QTY Labels required 2.1, 6.1





Product #: 870-001 Revision date: 13-SEP-2011 Print date: 13-SEP-2011

15. Regulatory Information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Methylene Chloride75-09-20.1 % de minimis concentrationPerchloroethylene127-18-40.1 % de minimis concentrationPropylene Oxide75-56-90.1 % de minimis concentrationTolluene108-88-31.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

Methylene Chloride: 1000.0000

Toluene: 1000.0000

Perchloroethylene: 100.0000 Propylene Oxide: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely No.

hazardous substance

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

On inventory (yes/no)* Country(s) or region Inventory name China Inventory of Existing Chemical Substances in China (IECSC) No European Inventory of New and Existing Chemicals (EINECS) Europe Nο Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains a chemical known to the State of California to cause

5/6

cancer and birth defects or other reproductive harm.

U.S. - Pennsylvania - RTK (Right to Know) List

Methylene Chloride75-09-2Environmental hazard; Special hazardous substancen-Butane106-97-8PresentPerchloroethylene127-18-4Environmental hazard; Special hazardous substancePropane74-98-6Present

Propylene Oxide 75-56-9 Environmental hazard; Special hazardous substance

Toluene 108-88-3 Environmental hazard

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 2*

Flammability: 2 Physical hazard: 0

Product name: Off the Wall Vandalism Mark & Stain Remover MSDS US

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication, The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification, The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

Product and Company Identification: Product Review

Hazards Identification: Emergency overview

Hazards Identification: Eyes
Hazards Identification: Inhalation
Hazards Identification: Target organs
Hazards Identification: Chronic effects
Hazards Identification: Main symptoms

Prepared by

Regulatory Compliance

Product #: 870-001 Revision date: 13-SEP-2011 Print date: 13-SEP-2011