Brady Industries HQ

MSDS

Material Safety Data Sheet 1609

Conforms to ANSI Z-400.1-1993

Chemtel 24 Hour Emergency Response (800) 255-3924

Las Vegas, NV 89103 (702) 876-3990

I Chemical Product and Company Identification

Product: H.D. Stone Scrubber Classification: Stone Care F43

2	Composition/Information on	Hazardous Ingredients
---	----------------------------	------------------------------

-					
Material	CAS#	%	OSHA(PEL)	TLV(ppm)	Other
2- Butoxyethanol*	111-76-2	<10	25 ppm	25 ppm	N/A
Sodium Metasilicate	1344-09-8	<5	N/A	N/A	N/A
Sodium Hydroxide	1310-73-2	<2	N/A	2 mg/m3	N/A

3 Hazards Identification

Emergency Overview: Irritant. Causes skin and eye irritation. Avoid contact with skin and eyes.

Control with Free

WARNING*

Contact with Eyes: This product is destructive to eye tissues. Will cause burns that result in damage to the eyes and

blindness if the solution remains in contact with the eye.

Contact with Skin: Contact with concentrate or solution will result in dry skin. Prolonged or repeated exposure may

cause irritation or possible tissue damage.

Skin Absorption: A single prolonged exposure may result in absorption of toxic amounts of product.

Ingestion Symptoms: Swallowing will irritate throat, esophagus and digestive tract. Product may cause burns to mucous

membranes of the mouth, throat, esophagus and stomach.

Inhalation Symptoms: Airborne concentrations of mists/vapors may cause damage to the upper respiratory tract and even

to lung tissue. If the product is heated, vapors are acutely toxic if inhaled.

Chronic Effects: Respiratory tract tissue damage may result in increased susceptibility to respiratory illness.

Excessive inhalation exposure may result in liver and kidney injury.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult,

give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute

remaining residue. Seek medical attention.

5 Fire Fighting Measures

Flash Point(F° TCC): >200°F Flammable Limits: LEL No Data UEL No Data

Auto Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

None

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

1/5/2010	0001	1609	H.D. Stone Scrubber P

9 Physical and Ch	emical Propert	ies			
Boiling Point(F°):	>212°F	Solubility in Water:	Soluble	Odor:	Butyl Solvent
Specific Gravity:	1.05	Volatiles(% by Wt.):	82	pH:	13+ 0.5
Appearance:	Green	Vapor Density:	>1	VOC:	120 g/L
vaporation Rate:	<1	Vapor Pressure:	<17 mm Hg	Freezing Point(F°):	<32°F
		< means less than typical values based on mater to be construed as a guarante		ary from sample to sai	
10 Stability and Re	activity				
Stability: Stable	Соі	nditions to Avoid: Heat			
Materials to Avoid	: Strong Oxidize	ers			
Hazardous Decon	nposition Prod	ucts:			
Oxides of carbon a	-				
Hazardous Polyme	rization:				
Will Not Occur					
11 Toxicological Ir	formation				
No Toxicology Infor	mation is availal	ole.			
2 Ecological Info	mation				
No data available.					
13 Disposal Consi	derations				
Waste Disposal Me Dispose of waste		with federal, state and local	regulations		
14 Transport Infor	mation				
HAZMAT: Si	Hazard	Code: 1127	ID Number: UN1760	Hazard Class	s: 8
Hazardous Divisi	on: Corrosive	_iquid n.o.s.		Packaging Group:	II
Hazardous Conter	ts: Sodium hy	droxide, Sodium silicate			
I5 Regulatory Info	rmation				
Proposition 65: N	ot Listed.				
Proposition 65: No. * This product is s		eporting requirements of S	SARA Title III.		
•		eporting requirements of S	SARA Title III.		
* This product is s	ubject to the re	eporting requirements of S	SARA Title III.		
* This product is s	ubject to the ro	eporting requirements of September 1 Flammabil		ity 0	
* This product is s EPA: No 16 Other Informati HMIS/NFPA Hazaro The information contor implied, is made re	on I Rating: He acide department is legarding the acide.	ealth 1 Flammabil based on the data available curacy of this data or the res	ity 0 Reactive to us. It is believed to	oe correct. No warrant	
* This product is s EPA: No 16 Other Informati HMIS/NFPA Hazaro The information cont	on I Rating: He acide ac	ealth 1 Flammabil based on the data available curacy of this data or the res	ity 0 Reactive to us. It is believed to	oe correct. No warrant	,