MSDS

Material Safety Data Sheet Conforms to ANSI Z-400.1-1993 4059

Las Vegas, NV 89118 (800) 293-4698

1 Chemical Product and Company Identification					
Product:Gum & Adhesion Remover	Classification: Specialty			E10	
2 Composition/Information on Hazardous Ingredients					
Material	CAS#	%	OSHA(PEL)	TLV(ppm)	Other
Isopropanol	67-63-0	< 6	400 ppm	400 ppm	N/A

3 Hazards Identification

Emergency Overview: Irritant. May cause skin and eye irritation. Avoid contact with skin and eyes.

CAUTION

.

Contact with Eyes: Direct contact with concentrated product may cause moderate irritation.

Contact with Skin: Prolonged or repeated contact may cause irritation and drying of skin.

Skin Absorption: No data.

Ingestion Symptoms: Irritation, nausea, vomiting and diarrhea.

Inhalation Symptoms: Excessive inhalation of the concentrate can cause nasal and respiratory irritation, dizziness,

headache and anesthetic effects.

Chronic Effects: No data.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult,

give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute

remaining residue. Seek medical attention.

5 Fire Fighting Measures

Flash Point(F° TCC): >140°F Flammable Limits: LEL No Data UEL No Data

Auto Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Eliminate all ignition sources and evacuate non-essential personnel. Wear protective clothing and rubber boots. Shut of source of leak if safe to do so. Dike and contain. Pump, vaccuum or scoop into salvage drum or container for disposal.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

If used according to directions respirator not required.

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

Combustible

Physical and Chemical Properties Boiling Point(F°)>212°F Solubility in WaterDisperses Odor: Citrus Volatiles(% by Wt.)96 Specific Gravity:0.85 **pH**: 7-8 Appearance:Clear Vapor Density:>1 VOC: 960 g/L Evaporation Rate:<1 Vapor Pressure:<17 mm Hq Freezing Point(F°);32°F < means greater than > means less than These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specific items. 10 Stability and Reactivity Stability: Stable Conditions to Avoid: Heat Materials to Avoid: Strong Oxidizers **Hazardous Decomposition Products:** Carbon oxides Hazardous Polymerization: Will Not Occur **Toxicological Information** No Toxicology Information is available. **Ecological Information** No data available. 13 **Disposal Considerations** Waste Disposal Method: Dispose of waste in accordance with federal, state and local regulations 14 Transport Information **HAZMAT:** Yes Hazard Code: 1624 ID Number: UN1993 Hazard Class: 3 Hazardous Division: Combustible liquid, n.o.s. Packaging Group: ■ Hazardous Contents: Isopropanol, D'limonene Regulatory Information Proposition 65: Not Listed. EPA: No 16 Other Information Flammability 2 HMIS/NFPA Hazard Rating: Health | 1 | Reactivity 0 The information contained herein is based on the data available to us. It is believed to be correct. No warranty, expressed or implied, is made regarding the accuracy of this data or the results to be obtained from the use thereof. For further information consult distributor, Brady Industries, HQ MSDS Approval Date: 2/28/2006 3/6/2006 0001 4059 Gum & Adhesion Remover Page 3 of 3