

CW1501
CW1505

MATERIAL SAFETY DATA SHEET



PRO STRIP Heavy Duty Stripper

HMIS		NFPA	Personal protective equipment
Health	3	3	
Fire Hazard	0	0	
Reactivity	0	0	

Version Number: 3

Preparation date: 2009-12-07

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PRO STRIP Heavy Duty Stripper

MSDS #: MS0300116

Product Code: 5032351, 5032360, 5117700

Recommended use: Industrial/Institutional. Floor stripper. This product is intended to be diluted prior to use.

Manufacturer, importer, supplier:

US Headquarters
Diversey, Inc.
8310 16th St.
Sturtevant, Wisconsin 53177-1964
Phone: 1-888-352-2249
MSDS Internet Address: www.diversey.com

Canadian Headquarters
Diversey, Inc. - Canada, Inc.
2401 Bristol Circle
Oakville, Ontario L6H 6P1
Phone: 1-800-668-3131

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

Principal routes of exposure:

Eye contact. Skin contact. Inhalation.

Eye contact:

Corrosive. Causes permanent eye damage, including blindness.

Skin contact:

Corrosive. Causes permanent damage.

Inhalation:

May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion:

Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS #	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Benzyl alcohol	100-51-6	5 - 10%	1230	2000 mg/kg	8.8 mg/L (4 h)
Diethylene glycol monoethyl ether	111-90-0	1 - 5%	1920	4200 µL/kg	>>5240 mg/m ³ (4 h)
Sodium hydroxide	1310-73-2	1 - 5%	Not available	1350 mg/kg	Not available
Monoethanolamine	141-43-5	10 - 20%	1720	1 mL/kg 1025 mg/kg	Not available

4. FIRST AID MEASURES

Eye contact:

Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical attention immediately.

Skin contact:

Immediately flush with plenty of water for 15-20 minutes. Get medical attention immediately.

Inhalation:

If breathing is affected, remove to fresh air. Get medical attention immediately.

Ingestion:

If swallowed, rinse mouth. Give a cupful of water or milk. THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Aggravated Medical Conditions:

Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects

PRO STRIP Heavy Duty Stripper

1 of 4

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: The product is not flammable. Extinguish fire using agent suitable for surrounding fire.
Specific hazards: Not applicable
Unusual hazards: None known
Specific methods: No special methods required

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Put on appropriate personal protective equipment (see Section 8.).
Environmental precautions and clean-up methods: Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection:

Chemical-splash goggles.

Hand protection:

Chemical-resistant gloves

Skin and body protection:

Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice

Ingredient(s)	CAS #	ACGIH	OSHA	Mexico
Sodium hydroxide	1310-73-2	2 mg/m ³ (Ceiling)	2 mg/m ³ (TWA)	2 mg/m ³ (Ceiling)
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m ³ (TWA)	6 ppm (STEL) 15 mg/m ³ (STEL) 3 ppm (TWA) 8 mg/m ³ (TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

Appearance: Aqueous solution

Specific gravity: 1.06

Vapor density: No information available

Boiling point/range: Not determined

Decomposition temperature: Not determined

Solubility: Completely Soluble

Solubility in other solvents: No information available

Partition coefficient (n-octanol/water): No information available

Elemental Phosphorus: 0.00 % by wt.

pH: 13.4

Explosion limits: - upper: Not determined - lower: Not determined

Bulk density: No information available

Evaporation Rate: No information available

Color: Clear

Odor: Cherry Almond

Melting point/range: Not determined

Autoignition temperature: No information available

Density: 8.84 lbs/gal 1.06 Kg/L

Flash point: > 200 °F > 93.4 °C

Viscosity: No information available

VOC: 12.3 % *

Dilution pH: 13 @ 1:4

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability: The product is stable
Polymerization: Hazardous polymerization does not occur
Hazardous decomposition products: None reasonably foreseeable.
Materials to avoid: Acids. Strong oxidising agents.
Conditions to avoid: Do not mix with any other product or chemical .

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Corrosive Oral LD50 estimated to be between 1000 - 2000 mg/kg Dermal LD50 estimated to be > 2000 mg/kg
Component Information: See Section 3
Chronic toxicity: None known
Specific effects
Carcinogenic effects: None known
Mutagenic effects: None known
Reproductive toxicity: None known
Target organ effects: None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:
Undiluted product is regulated under environmental and transportation laws as a corrosive waste.

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, <http://naextranet.diversey.com/dot/>, for up to date shipping information.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Benzyl alcohol	100-51-6	X	-	X	-
Diethylene glycol monoethyl ether	111-90-0	-	-	-	-
Sodium hydroxide	1310-73-2	X	X	X	X
Monoethanolamine	141-43-5	X	X	X	X
Water	7732-18-5	-	-	-	-

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Diethylene glycol monoethyl ether	111-90-0	1 - 5%			X
Sodium hydroxide	1310-73-2	1 - 5%	1000		

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
---------------	---------	---------	-------------------------

PRO STRIP Heavy Duty Stripper

3 of 4

Diethylene glycol monoethyl ether	X		
-----------------------------------	---	--	--

SARA 311/312 Hazard Categories

Immediate: X
 Delayed: -
 Fire: -
 Reactivity: -
 Sudden Release of Pressure: -

Canada

WHMIS hazard class: E Corrosive material



16. OTHER INFORMATION

Reason for revision: Not applicable
 Prepared by: NAPRAC
 Additional advice: Does not contain an added fragrance.

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.