[W4/22; CW23

MATERIAL SAFETY DATA SHEET



FASTRIP Floor Stripper

HMIS		NFPA	Personal protective equipment
Health	3	3	A .SS. 1975
Fire Hazard	0	0	
Reactivity	0	0	
Version Number: 4			

Preparation date: 2007-06-22

PRODUCT AND COMPANY IDENTIFICATION

Product name:

FASTRIP Floor Stripper

MSDS#:

MS0200002

Product Code:

4122398, 4122401, 4362447

Recommended use:

Industrial/Institutional. Floor stripper. This product is intended to be diluted prior to use.

Manufacturer, importer, supplier:

US Headquarters JohnsonDiversey, Inc.

8310 16th St.

Sturtevant, Wisconsin 53177-1964

Phone: 1-888-352-2249 MSDS Internet Address: www.johnsondiversey.com

Emergency telephone number:

Canadian Headquarters JohnsonDiversey - Canada, Inc. 2401 Bristol Circle Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131

1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER CURROSIVE CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

Principle routes of exposure:

Eye contact. Skin contact. Inhalation.

Eye contact:

Corrosive. Causes permanent eye damage, including blindness.

Skin contact:

Corrosive. Causes permanent damage.

Inhalation: Ingestion:

May cause irritation and corrosive effects to nose, throat and respiratory tract.

Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients					
Ingredient(s)	CAS#	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
<u>Monoethanolamine</u>	141-43-5	10 - 20%	1720	1 mL/kg	Not available
Potassium hydroxide	1310-58-3	.5 - 10%	214	Not available	Not available
Benzyl aicohol	100-51-6	20 - 30%	1230	2000 ma/ka	8.8 mg/L (4 h)
Glycerin	56-81-5	1 - 5%	10000	Not available	>570 mg/m³ (1 h)

4. FIRST AID MEASURES

Eye contact:

Immediately flush eyes with running water for at least 15-20 minutes, keeping eyelids open. Get medical

attention immediately. Skin contact:

THE WAY T

Inhalation: Ingestion: Flush immediately with plenty of water for at least 15-20 minutes. Get medical attention immediately.

If breathing is affected, remove to fresh air. Get medical attention immediately.

If swallowed, give a cupful of water or milk, THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON

CENTER, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person.

Aggravated Medical Conditions:

Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may

be more susceptible to irritating effects.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

The product is not flammable. Extinguish fire using agent suitable for surrounding fire. None known.

Specific hazards:

Corrosive material (See sections 8 and 10).

Unusual hazards: Specific methods:

No special methods required

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

FASTRIP Floor Stripper

5. FIRE-FIGHTING MEASURES

Extinguishing media which must not be used for safety reasons: None.

-364 JH

6. AGCIDENTAL RELEASE MEASURES

Personal precautions: Environmental precautions and clean-up methods:

Put on appropriate personal protective equipment (see Section 8.).

Use appropriate containment to avoid environmental contamination. Soak up with inert absorbent

material. Shovel into suitable container for disposal.

7. HANDLING AND STORAGE

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY. Storage:

Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection:

Chemical-splash goggles. Chemical-resistant gloves

Hand protection: Skin and body protection: Respiratory protection:

Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Hygiene measures:

Keep aw ay from food, drink and animal feeding stuffs . Handle in accordance with good industrial

hygiene and safety practice.

ingredient(s)	CAS#	ACGIH	OSHA	Mexico
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m³ (TWA)	6 ppm (STEL) 15 mg/m ³ (STEL) 8 mg/m ³ (TWA) 3 ppm (TWA)
Potassium hydroxide	1310-58-3	2 mg/m³ (Ceifing)		J Sports 1 4470
Glycerin	56-81-5	10 mg/m³ (TWA)	5 mg/m³ (TWA) 15 mg/m³ (TWA)	10 mg/m³ (TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Appearance:

Liquid

14

Aqueous solution

Color:

pH:

Yellow

Odor: Specific gravity:

Solvent 1.080

Density: VOC:

9.01 lbs/gal

Flash point;

17,45% 1

Solubility:

>200°F >99.3°C Completely Soluble

Viscosity:

No information available

Bulk density:

Dilution pH: Vapor density:

Evaporation Rate

Boiling point/range: Melting point/range:

Decomposition temperature:

Autoignition temperature: Partition coefficient (n-octanol/water): No information available Solubility in other solvents:

Not determined No information available

No information available

No information available.

No information available

No information available

Not determined

Not determined

No information available

Bemental Phosphorus: 0% by wt.

Explosion limits: - lower: Not determined- upper: Not determined

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability:

The product is stable

Polymerization:

Hazardous polymerization does not occur

Hazardous decomposition products: Materials to avoid:

None reasonably foreseeable. Strong exidising agents. Strong exothermic reaction with acids.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Corrosive. Oral LD50 estimated to be >1000 and <5000 mg/kg. Dermal LD50 estimated to be > 2000

mg/kg

11. TOXICOLOGICAL INFORMATION

Component Information:

See Section 3

Chronic toxicity:

None know n

Specific effects

Carcinogenic effects: Mutagenic effects:

None know n None know n

Reproductive toxicity:

None know n

Target organ effects:

None know n

12. ECOLOGICAL INFORMATION

Environmental Information:

When used for its intended purpose this product should not cause adverse effects in the environment.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

17 SARSA (2)

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of in compliance with all Federal, state, provincial, and local laws and regulations. Incineration is the preferred method. Relatively small quantities of product may be neutralized as stated above, and if in accordance with local laws and the operators of the local sewage treatment plant, the neutralized material may be discharged into the sewer system.

14. TRANSPORT INFORMATION

DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information

15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), New Zealand (NZloC).

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

STATE RIGHT TO KNOW

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Monoethanolamine	141-43-5	х	X	Х	X
Water	7732-18-5	*	-		
Potassium hydroxide	1310-58-3	Х	X	x	Х
Hexyloxyethanol	112-25-4	-	X	-	
Benzyl alcohol	100-51-6	X	X	X	
Glycerin	56-81-5	X	-	, , , , , , , , , , , , , , , , , , ,	X
Potassium tallate	61790-44-1	-	-		

CERCLA/ SARA

STITUTE OF STATE					
Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Potassium hydroxide	1310-58-3	5 - 10%	1000		
Hexyloxyethanol	112-25-4	10 - 20%	1		X

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Hexyloxyethanol	X		

SARA 311/312 Hazard Categories

immediate: Delayed: Fire: Ν Reactivity: Sudden Release of Pressure:

Canada

WHMIS hazard class: E Corrosive material

V-112		
Ingredient(s)	CAS#	NPRI
Glycerin	56-81-5	X



16. OTHER INFORMATION

Reason for revision: Prepared by: Additional advice:

Not applicable NAPRAC None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.