

Spartan Chemical Company, Inc. Material Safety Data Sheet

CW 2401

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

L.O.E. STRIPPER Product Number: 0061 Product Division: **Janitorial**

Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee OH 43537 Product/Technical Information: 1-(800)-537-8990

Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spil Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Corrosive liquids, n.o.s., 8, UN 1760, II, (contains potassium hydroxide)

NFPA Ratings:	HMIS Ratings:
Health: 3 - Serious	Health: *3 - Serious; Chronic Hazard
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from

listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z-1-A			
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	NTP, IARC or OSHA Carcinogen
*Diethylene glycol monobutyl	20-30	112-34-5	Not Established	Not Established	Not Established	No
ether	-	-	-	-	-	-
Monoethanolamine	5-10	141-43-5	7.5	15	Not Established	No
Potassium hydroxide	1-5	1310-58-3	Not Established	Not Established	2 (NIOSH)	No
Ethoxylated alcohols phosphate	1-5	68130-47-2	Not Established	Not Established	Not Established	No
ester	•	-	-	-	-	-

Comment: *This substance is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (SARA) and of 40 CFR 372.

SECTION III: PHYSICAL DATA

Boiling Point: 200 °F	Vapor Pressure: Unknown
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 13.0-13.7	Specific Gravity (H _. O=1): 1.02
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight: 3 - 5
Physical State: Liquid	
Appearance & Odor: Clear light orange liquid, mild odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 200°F	Method Used: ASTM-D56			
Flammable Limits: N/A	Flame Extension: N/A			
Extinguishing Media: Carbon dioxide, dry chemical, synthe	dia: Carbon dioxide, dry chemical, synthetic foam or water.			
Special Fire Fighting Procedures: Wear NIOSH approved self-contained	Wear NIOSH approved self-contained breathing apparatus and protective clothing. Cool fire-exposed			
containers with water spray.	L. C.			
Unusual Fire & Explosive Hazards: Combustion products are toxic.				

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond seliers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.

Update Section II

Ref; 29 CFR 1910.1200 (OSHA)

Changes: