Brady Industries, HQ

**MSDS** 

Material Safety Data Sheet 1132BRDY

Conforms to ANSI Z-400.1-1993

Chemtel 24 Hour Emergency Response (800) 255-3924

Las Vegas, NV 89118

(800) 293-4698

# 1 Chemical Product and Company Identification

Classification: Floor Finish Stripper	A30
	Classification: Floor Finish Stripper

2 Composition/Information on Ha	zardous Ingredients				
Material	CAS#	%	OSHA(PEL)	TLV(ppm)	Other
2- Butoxyethanol*	111-76-2	<5	25 ppm	25 ppm	N/A
1-Amino-2-Propanol	78-96-6	<8	3 ppm	3ppm	N/A
Sodium Hydroxide	1310-73-2	<6	N/A	2 mg/m3	N/A

#### 3 Hazards Identification

Emergency Overview: Causes severe chemical burns. Avoid skin and eye contact.

DANGER

Contact with Eyes: This product will cause burns that result in damage to the eyes and even blindness if the solution

remains in contact with the eye.

Contact with Skin: Contact with concentrate solution will result in dry skin. Prolonged or repeated contact causes

chemical burns and possible tissue damage.

Skin Absorption: No data.

**Ingestion Symptoms:** Swallowing will irritate throat, esophagus and digestive tract. Product may cause burns to mucous

membranes of the mouth, throat, esophagus and stomach.

Inhalation Symptoms: Mists/vapors may cause damage to the upper respiratory tract and even to the lung tissue. If the

product is heated, vapors are acutely toxic if inhaled.

Chronic Effects: Respiratory tract tissue damage may result in increased susceptibility to respiratory illness.

Excessive inhalation exposure may result in liver and kidney injury.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

### 4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

**Skin:** If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult,

give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute

remaining residue. Seek medical attention.

### 5 Fire Fighting Measures

Flash Point(F° TCC): >210F Flammable Limits: LEL No Data UEL No Data

# Auto Ignition TemperatureNo Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

### **Special Fire Fighting Procedures:**

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

### Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

### 6 Accidental Release Measures

# Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

# Small Spills:

Mop up spill and rinse area.

### 7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

**Storage:** Store in a cool, dry place.

### 8 Exposure Controls/Personal Protection

### **Ventilation and Engineering Controls:**

Local exhaust

### **Respiratory Protection:**

If used according to directions respirator not required.

### **Protective Gloves:**

**Rubber Gloves** 

#### **Eve Protection:**

Chemical Splash Goggles

# Other Protective Equipment:

Corrosive

9/16/201 0001 1132B

9 Physical and Chemical Propertion	es	
Boiling Point(F°):>212°F	Solubility in Water: Soluble	Odor: Butyl
Specific Gravity: 1.04	Volatiles(% by Wt.):81	<b>pH</b> : 13 - 14
Appearance: Yellow	Vapor Density: >1	<b>VOC:</b> 150 g/L
Evaporation Rate:<1	Vapor Pressure: <17 mm Hg	Freezing Point(F°) < 40° F
	< means less than > means greater that	
	al values based on material tested but may onstrued as a guaranteed analysis of any	
10 Stability and Reactivity		
Stability: Stable Conditions	to Avoid: Heat	
Materials to Avoid: Strong Oxidizers		
Hazardous Decomposition Products:		
Oxides of carbon and nitrogen		
exided of darbon and minegen		
Hazardous Polymerization:		
Will Not Occur		
11 Toxicological Information		
No Toxicology Information is available.		
12 Ecological Information		
No data available.		
13 Disposal Considerations		
Waste Disposal Method:		
Dispose of waste in accordance with fe	deral, state and local regulations	
14 Transport Information		
HAZMAT: Yes Hazard Code	:1132 ID Number:UN1	760 Hazard Class: 8
Hazardous Division: Corrosive Liquid	nos	Packaging Group:
Hazardous Contents:Sodium Hydroxi		actual survey in
	Je, i Allino 2 i Topanoi	
15 Regulatory Information		
Proposition 65: Not Listed.		
* This product is subject to the re	eporting requirements of SARA Titl	le III.
EPA: No		
16 Other Information		
HMIS/NFPA Hazard Rating: Health	2 Flammability 1 React	iivity 0
The information contained herein is based or implied, is made regarding the accuracy information consult distributor, Brady Inc.	of this data or the results to be obtained f	
<b>9/16/2013</b> 0001 1132B		Heavy Duty Stripper Page 3 of 3
0001 11020		