OSHA'S HAZARD COMMUNICATION STANDARD U.S. DEPARTMENT OF LABOR

29 CFR 1910.1200 OMB NO: 1218-0072

IDENTITY NO: MPTFD8032 NAME: MASTERPIECE TRAVERFILL

SECTION 1

DISTRIBUTOR'S NAME: MASTERPIECE INDUSTRIES PRODUCTS **ADDRESS:** 6683 SCHUSTER STREET **PHONE:** (702) 656-9767 **CITY:** LAS VEGAS **STATE:** NEVADA **CONTACT:** KEN WILLIAMS

DATE PREP: 01/16/2012 **EMERGENCY PHONE (CHEMTREC):** (800) 424-9300

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS	CAS# OS	SHA PEL	ACGIH TLV	WEIGHT %
STYRENE	100-42-5	50PPM	50 PPM	15-20
CALCIUM CARBONATE	1317-65-3	15MG/M3	10MG/M3	35-40
TITANIUM DIOXIDE	13463-67-7	15MG/M3	10MG/M3	<5
YELLOW IRON OXIDE	51274-00-1		10MG/M3	<5
NATURAL IRON OXIDE	1332-37-2		10MG/M3	<5
BLACK IRON OXIDE	1317-61-9	15MG/M3	10MG/M3	<5
AMORPHOUS FUMED SILICA	112945-52-5		10MG/M3	<5

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: >295 F

VAPOR PRESSURE: 4.5 mmHg at 68F

VAPOR DENSITY: NOT TESTED

EVAPORATION RATE: NOT TESTED

SOLUBILITY IN WATER: NOT TESTED VOC CONTENT: 15 to 20

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 89F
LEL: NOT TESTED
UEL: NOT TESTED

pH: NOT TESTED

NFPA HAZARD RATING
(0=LEAST, 4=EXTREME)

FLAMMABLE LIMITS: 1.1 TO 6.1

UEL: NOT TESTED

DOT #: NONE

H F R S

EXTINGUISHING MEDIA: WATER SPRAY, FOAM , DRY CHEMICAL, CARBON DIOXIDE OR ANY CLASS B EXTINGUISHING AGENT.

EXPLOSION HAZARDS: AT ELEVATED TEMPERATURES, SUCH AS IN A FIRE, POLYMERIZATION MAY TAKE PLACE. IF POLYMERIZATION TAKES PLACE IN A CLOSED CONTAINER, THERE IS THE POSSIBILITY OF VIOLENT RUPTURE OF THE CONTAINER. PRODUCT VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR.

SPECIAL FIRE FIGHTING PROCEDURES: FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. EQUIPMENT SHOULD BE THOROUGHLY DECONTAMINATED AFTER USE.

SECTION 6 - HEALTH HAZARD DATA

ROUTES OF ENTRY

INHALATION: POSSIBLE INGESTION: POSSIBLE

SKIN: POSSIBLE HEALTH HAZARDS: SAME SIGNS & SYMPTOMS OF EXPOSURE

OSHA CARCINOGENICITY: NONE NTP: NONE

IARC MONOGRAPHS: NONE

SIGNS & SYMPTOMS OF OVER EXPOSURE

EYES: BURNING SENSATION
INGESTION: PAIN AND DISCOMFORT
SKIN: SLIGHT CAN BE SEVERE IRRITATION
INHALATION: PENDING ON EXPOSURE CAN BE

FATAL AND SEVERE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

SAME AS SIGNS AND SYMPTOMS OF OVER EXPOSURE.

EMERGENCY FIRST AID PROCEDURES:

EYES: FLUSH WITH WATER FOR 15 MINUTES. SEEK IMMEDIATE MEDICAL AID.

SKIN: REMOVE CONTAMINATED CLOTHING, WASH WITH SOAP AND WATER.CONSULT A PHY-SICIAN IF ANY SIGNS OR SYMTOMS DECRIBED IN THIS DOCUMENT OCCUR. WASH CLOTHING-**INGESTION:** DO NOT INDUCE VOMITING (ASPIRATION HAZARD) SEEK IMMEDIATE MEDICAL AID.

INHALATION: REMOVE VICTIM FROM EXPOSURE. IF VICTIM IS UNCONSCIOUS, ADMINISTER ARTIFICAL RESPIRATION AND/ OR OXYGEN AS NEEDED. SEEK MEDICAL AID.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE.

GENERAL PROCEDURES: READ AND OBSERVE ALL PRECAUTIONS ON PRODUCT LABEL. REFER TO PORDUCT LABEL OR MANUFACTURERS TECHNICAL BULLETINS FRO THE PROPER USE AND HANDLING OF THIS MATERIAL. DO NOT USE OR STORE NEAR FLAME, SPARKS, OR HOT SURFACES. USE ONLY IN WELL VENTILATED AREA. KEEP CONTAINER CLOSED. DONTO WELD, HEAT, OR DRILL CONTAINER. EMPTIED CONTAINER STILL CONTAINS HAZARDOUS OR EXPLOSIVE VAPOR OR LIQUID.

SECTION 8 - CONTROL MEASURES

RESPIRATORY PROTECTION: OPEN ALL DOORS AND WINDOWS. EXPOSURES ABOVE THE TLV OR PEL REQUIRE A NIOSH APPROVED RESPIRATOR EQUIPPED FOR THE EXPOSURE OR SUITABLE RESPIRATORY PROTECTION PER 29 CFR 1910.134.

PROTECTIVE GLOVES: RUBBER, PLASTICS, CHEMICAL RESISTANT

EYE PROTECTION: GLASSES, GOGGLES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: CHEMICAL RESISTANT CLOTHING WORK HYGENIC PRACTICES: USE COMMON SENSE AND CARE AROUND CHEMICALS. NEVER MIX CHEMICALS. CONSULT YOUR SUPERVISOR FOR OTHER PRACTICES. ALL PRACTICES DEPEND ON YOUR SPECIFIC BUSINESS. DIRECTIONS FOR USE ARE NORMALLY FOUND ON LABEL WHICH WILL DICTATE ENGINEERING AND CONTROL MEASURES.

OTHER SPECIAL REQUIREMENTS: NONE

MPTFD8032