PROCHEM

Crystal Blue

MSDS Number: S800

Revision Date: February 18, 2009

Page

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROCHEM Kärcher North America 325 S. Price Road Chandler, AZ 85224

Contact: Prochem

Telephone Number: 480-899-7000 FAX Number: 480-786-9538 E-Mail: info@prochem.com Web www.prochem.com

Product Name: Revision Date:

Crystal Blue

February 18, 2009

MSDS Number:

S800

Emergency Telephone: (800) 535-5053 [Infotrac]

HAZARDS IDENTIFICATION 2

Route of Entry:

Eyes; Skin; Inhalation; Ingestion;

Target Organs:

Eyes; Skin;

Inhalation:

Minimal respiratory tract irritation may occur with exposure to a large amount of material

Skin Contact: Eye Contact:

May Cause Irritation. May Cause Irritation.

ingestion:

Small amounts swallowed incidental to normal handling operations are not likely to cause injury;

swallowing amounts larger than that may cause temporary injury.

HMIS III-ratings (scale 0-4): Health = 1, Fire = 0, Physical Hazard = 0

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas # Perc. Chemical Name

6834920 | 1-3% | Silicic acid (H2SiO3), disodium salt

OSHA Regulatory Status:

This MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

PROCHEM # + FOR A REASON!

Crystal Blue

Revision Date: February 18, 2009 MSDS Number: \$800

Page 2 of 4

FIRST AID MEASURES

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. Inhalation:

Promptly flush skin with water until all chemical is removed. Skin Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids Eye Contact:

occasionally to facilitate irrigation.

If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured Ingestion:

party is conscious, give two glasses of water. Seek medical attention.

FIRE FIGHTING MEASURES

>212°F Flash Point: Flash Point Method: Closed Cup

6

Use any standard agent - choose the one most appropriate for type of surrounding fire.

ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbant material and place into separate waste container. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

HANDLING AND STORAGE

Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with **Handling Precautions:**

care and avoid spillage on the floor (slippage). Keep away from sources of ignition. Wash

thoroughly after handling.

Store out of reach of children; keep container closed; store in a cool well-ventilated place Storage Requirements:

away from strong oxidizing or alkaline product.

EXPOSURE CONTROLS/PERSONAL PROTECTION 8

Normal room ventilation is satisfactory for limited use. **Engineering Controls:**

HMIS PP, X | Consult your supervisor for special instructions **Protective Equipment:**

PHYSICAL AND CHEMICAL PROPERTIES 9

Clear Blue Appearance:

N/D **Boiling Point:** Liquid Physical State: N/D Freezing/Melting Pt.: Ammonia scent Odor:

Soluble Solubility: 11.2 - 12.5 pH: 9.07 Spec Grav./Density:

N/D Vapor Pressure: N/D Vapor Density:

PROCHEM TOR A REASON!

Crystal Blue

Revision Date: February 18, 2009 MSDS Number: \$800

Page 3 of 4

STABILITY AND REACTIVITY 10

Product is stable under normal conditions. Stability:

None Known Conditions to avoid:

Strong oxidizing or alkaline agents Materials to avoid (incompatability):

Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, **Hazardous Decomposition products:**

and other unidentified thermal decomposition products from this product or its

packaging.

Will not occur. Hazardous Polymerization:

TOXICOLOGICAL INFORMATION 11

Route of Entry: Eye contact, and Skin absorption/contact

Effects of Acute Overexposure to Product:

Eye Contact: Causes eye irritation, redness, tearing and blurred vision

Skin Contact: May cause skin irritation and defatting

Inhalation: Inhalation of mist or vapor may cause temporary respiratory irritation; temporary central nervous system

effects including dizziness, weakness, fatigue, nausea, and headache.

Ingestion: May cause temporary gastrointestinal irritation with nausea, vomiting and diarrhea.

None of the components in this product are listed by NTP, IARC or OSHA as a carcinogen.

ECOLOGICAL INFORMATION 12

Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

DISPOSAL CONSIDERATIONS 13

Dispose of in accordance with local regulations.

TRANSPORT INFORMATION 14

Refer to bill of lading or container label for DOT or other transportation hazard classification. Ship in accordance with 49 CFR parts 100-185.

REGULATORY INFORMATION 15

COMPONENT / (CAS/PERC) / CODES

*Silicic acid (H2SiO3), disodium salt (6834920 1-3%), WHMIS 1%

REGULATORY KEY DESCRIPTIONS

WHMIS= Workforce Hazardous Material Information System



Crystal Blue

MSDS Number: S800

Revision Date: February 18, 2009

Page 4 of 4

16

OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000

END OF MSDS DOCUMENT