

MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	Legend Brands VersaClean Encap Power Plus		
Product code:	W.50091		
Recommended Use	: Cleaning agent		
Supplier:	Legend Brands		
	15180 Josh Wilson Road		
	Burlington, WA 98233		
	800-932-3030		
Information:	800-932-3030		
Emergency:	Infotrac 800-535-5053		
Degree of hazard:	4 = Extreme, 3 = High, 2 = Moderate, 1 = Slight, 0 = Insignificant		
Health:	1; Flammability: 0; Reactivity: 0		

SECTION II a: HAZARDOUS INGREDIENTS >1.0%

This product has not been tested as a whole for health effects on animals or humans. According to the OSHA Hazardous Communications Standard (29 CFR 1910.1200) any hazardous ingredients that comprise >1.0% of the material and any carcinogenic ingredients that comprise >0.1% must be listed on the MSDS. When individually tested at 100% ingredients in the make-up of this product posed the following health hazards.

Chemical Name	CAS #	OSHA PEL	ACGIH TLV	Percentage
Hydrogen Peroxide (35%)	7722-84-1	1 ppm	1 ppm	5-10%
Dipropylene glycol n-butylether	29911-28-2	N/A	N/A	1-5%

SECTION II b: CARCINOGENIC INGREDIENTS AT >0.1%

None.

SECTION III: HAZARDS IDENTIFICATION

EYES:	May cause eye irritation.
SKIN:	None expected if used as directed.
INHALATION:	None expected if used as directed.
INGESTION:	May cause abdominal discomfort, nausea and diarrhea

SECTION IV: FIRST AID PROCEDURES

EYES:	Remove contacts. Flush with water for at least 15 minutes. If irritation persists consult physician.
INGESTION:	Drink 1 to 2 glasses of water. If discomfort persists, consult physician.
INHALED:	Remove to fresh air. If symptoms persist or are severe seek prompt medical assistance.
SKIN:	Remove contaminated clothing. Thoroughly wash exposed area with soap and water.
PHYSICIAN:	Treatment based on judgment of attending physician.

SECTION V: FIRE AND EXPLOSION DATA

FLASH POINT:	N/A
AUTO-IGNITION TEMPERATURE:	N/D
EXPLOSIVE LIMITS -	UEL: N/D LEL: N/D
EXTINGUISHING MEDIA:	Any standard extinguishing media (alcohol foam, water spray or fog, CO2 dry chemical, etc.).
SPECIAL FIRE FIGHTING PROCEDURES:	Use NIOSH/MSHA approved self-contained positive pressure breathing apparatus and protective clothing where this material is involved in a fire.
UNUSUAL FIRE AND EXPLOSION HAZARD:	None known.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Soak up spilled material with absorbent material. Scoop or sweep and dispose according to local, state and federal regulations.

SECTION VII: HANDLING AND STORAGE

Avoid heat, flame, and sparks. Keep container closed to avoid contamination.

SECTION VIII: PROTECTION MEASURES

VENTILATION:	Local exhaust or dilution ventilation is necessary in poorly ventilated areas.
GLOVES:	Chemical resistant gloves.
RESPIRATORY:	When mists or aerosols are anticipated, wear NIOSH/MSHA approved respirator equipped with organic vapor cartridges with high-efficiency particulate filters.
EYE:	Safety glasses. Wear splash goggles when mists or aerosols are anticipated.
OTHER PROTECTIVE EQUIPMENT:	Body-covering clothing should be worn.

SECTION IX: PHYSICAL/CHEMICAL DATA

APPEARANCE AND ODOR: Clear light yellow liquid with low odor.	WATER SOLUBILITY, % BY WT: N/D
% VOLATILE BY WT.: ~10%	pH: 6.7 – 7.7
SPECIFIC GRAVITY: 1.020 g/cc	WT/GAL: 8.50 lbs/gal

SECTION X: REACTIVITY DATA

STABILITY:StableHAZARDOUS POLYMERIZATION:Will not occur.INCOMPATIBILITY:Strong oxidizers and strong acids.HAZARDOUS DECOMPOSITIONOxides of carbon, hydrogen and possibly other unidentified organic compounds.

SECTION XI: TOXICOLOGICAL INFORMATION OF INGREDIENTS

Dipropylene glycol n-butylether: LD50 oral rat: 3700 mg/kg. LD50 dermal rabbit: 5330 mg/kg.

SECTION XII: ECOLOGICAL INFORMATION

Product may not be completely biodegradable. Dipropylene glycol n-butylether: LC50 guppy (96hr): 841mg/L. LC50 daphnia magna: >1000 mg/L

SECTION XIII: SPILL, LEAK AND DISPOSAL PROCEDURES

WASTE DISPOSAL: In accordance with Federal, state and local regulations. NEUTRALIZING CHEMICALS: Water. Encap Power Plus MSDS Rev 1.docx

SECTION XIV: TRANSPORT INFORMATION PER 49 CFR 172.101

Domestic	International:
California Prop 65 Ingredients: Hydrogen Peroxide.	European labeling requirements: Symbol: Xi: Irritant. R-Sentences: R36 S-Sentences: S2, S24, S25, S37, S39 Canadian: WHMIS Hazard Class: D2B

SECTION XVI: OTHER INFORMATION

One should always use chemicals with awareness of potential hazards, known and unknown, and their effect on the human system. We urge users to minimize employee exposure to all chemicals, including this product and to keep the level of exposure commensurate with good industrial hygiene practices.

DISCLAIMER OF LIABILITY

The manufacturer and seller warrants that this product conforms to its standard specifications when used according to directions. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material and the results to be obtained from the use thereof.

Review date: 06/22/2009 Printed: 2/5/2014