

Liquid Slurry

MSDS Number: \$876

Revision Date: February 18, 2009

Page 1 of 4

PRODUCT AND COMPANY IDENTIFICATION

<u>Manufacturer</u>

PROCHEM Kärcher North America 325 S. Price Road Chandler, AZ 85224

Contact: Prochem

Telephone Number: 480-899-7000#3

FAX Number: 480-786-9538 E-Mail: info@prochem.com Web www.prochem.com

Product Name: Revision Date:

Liquid Slurry

February 18, 2009

MSDS Number:

S876

Emergency Telephone: (800) 535-5053 [Infotrac]

HAZARDS IDENTIFICATION

Route of Entry:

Eyes; Skin; Inhalation; Ingestion;

Target Organs:

2

Eyes: Skin;

Inhalation:

Minimal respiratory tract irritation may occur with exposure to a large amount of material

Skin Contact: Eye Contact:

May Cause Irritation. May Cause Irritation.

Ingestion:

Small amounts swallowed incidental to normal handling operations are not likely to cause injury;

swallowing amounts larger than that may cause temporary injury.

HMIS III-ratings (scale 0-4): Health = 1, Fire = 0, Physical Hazard = 0

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas # Perc.

Chemical Name

7320345

| 17-18%

| Diphosphoric acid, tetrapotassium salt

OSHA Regulatory Status: This MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.



Liquid Slurry

MSDS Number: S876 Revision Date: February 18, 2009

Page 2 of 4

4 FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

Skin Contact: Wash with soap and water. If irritation persists consult medical personnel

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids

occasionally to facilitate irrigation. Get immediate medical attention.

Ingestion: If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured

party is conscious, give two glasses of water. Seek medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: >212°F
Flash Point Method: Closed Cup

Wear self contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most

appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbant material and place into separate waste container. Ventilate Area and Wash Spill Site After Material Pickup is Complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with

care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash

thoroughly after handling,

Storage Requirements: Store out of reach of children; keep container closed; store in a cool well-ventilated place

away from strong oxidizing or alkaline product.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Normal room ventilation is satisfactory for limited use.

Protective Equipment: HMIS PP, X | Consult your supervisor for special instructions



Liquid Slurry

MSDS Number: S876

Revision Date: February 18, 2009

Page 3 of 4

pH:

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Clear Blue

Physical State: Odor:

Liquid

Citrus

N/D

9.4 - 9.8

Solubility: Spec Grav./Density:

Freezing/Melting Pt.:

Boiling Point:

N/D Soluble 10.3

N/D

Vapor Pressure: Vapor Density:

N/D

STABILITY AND REACTIVITY

Stability:

10

Product is stable under normal conditions.

Conditions to avoid:

None Known

Materials to avoid (incompatability):

None Known

Hazardous Decomposition products:

Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids,

and other unidentified thermal decomposition products from this product or its

packaging.

Hazardous Polymerization:

Will not occur.

TOXICOLOGICAL INFORMATION

Route of Entry: Eye contact, and Skin absorption/contact

Effects of Acute Overexposure to Product:

Eye Contact: Causes eye irritation, redness, tearing and blurred vision

Skin Contact: Causes skin irritation, defatting and dermatitis

Inhalation: Inhalation of mist or vapor may cause temporary respiratory irritation; temporary central nervous system

effects including dizziness, weakness, fatigue, nausea, and headache.

Ingestion: May cause temporary gastrointestinal irritation with nausea, vomiting and diarrhea

None of the components in this product are listed by NTP, IARC or OSHA as a carcinogen.

ECOLOGICAL INFORMATION

Refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

13

DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.



Liquid Sturry

MSDS Number: \$876 Revision Date: February 18, 2009

Page 4 of 4

14

TRANSPORT INFORMATION

Refer to bill of lading or container label for DOT or other transportation hazard classification; ship in accordance with 49 CFR parts 100-185.

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Diphosphoric acid, tetrapotassium salt (7320345 17-18%)

16

OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000

END OF MSDS DOCUMENT