MSDS

Material Safety Data Sheet Conforms to ANSI Z-400.1-1993 1177

Sneet

Chemtel 24 Hour Emergency Response (800) 255-3924

80 - 17704 MAINTEX 13300 East Nelson Avenue City of Industry, CA 91746

(800) 446-1888

1	Chemical	Product	and	Company	Identification
	Cilellicai	ribuuci	aliu	COMPANY	Iuciiiiii valivii

Product: Slip Control Classification: Concentrated Antislip Cleaner/Degreaser A40

2 Composition/Information on Hazardous Ingredients

Z Composition/mormation on mazardous	ingredients					
Material	CAS#	%	OSHA(PEL)	TLV(ppm)	Other	
Hydroxyacetic Acid	79-14-1	<20	N/E	N/E	N/A	
Propylene Glycol Methyl Ether	107-98-2	<6	150 ppm	150 ppm	N/A	

3 Hazards Identification

Emergency Overview: Causes skin and eye irritation. Avoid skin and eye contact.

Contact with Eyes: May cause moderate irritation, redness, tearing and possible burns, depending on length of contact.

Contact with Skin: Prolonged or repeated contact may cause irritation and drying of skin.

Skin Absorption: No data.

Ingestion Symptoms: Swallowing will irritate throat, esophagus and digestive tract. Product may cause burns to mucous

membranes of the mouth, throat, esophagus and stomach.

Inhalation Symptoms: Airborne concentrations of mist/vapor may cause damage to the upper respiratory tract and even

lung tissue. If the product is heated, vapors are acutely toxic.

Chronic Effects: Overexposure may result in allergic skin reactions.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult,

give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute

remaining residue. Seek medical attention.

1/30/2007 0001 1177 Slip Control Page 1 of 3

Flash Point(F° TCC): >200°F

Flammable Limits: LEL No Data

UEL No Data

Auto ignition Temperature:

No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

If diluted according to directions respirator not required.

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

1/30/2007	0001	1177	Slip Control Page 2 of 3	5
-----------	------	------	--------------------------	---

Boiling Point(F°): >212°F Solubility in Water: Complete Odor: Fresh pH: 1-2 **Specific Gravity:** 1.08 Volatiles(% by Wt.): 80 VOC: 43 g/L Vapor Density: Appearance: >1 Clear Freezing Point(F°): >32°F Vapor Pressure: Evaporation Rate: <1 <17 mm Hg < means less than > means greater than These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specific items. 10 Stability and Reactivity Stability: Stable Conditions to Avoid: Heat Materials to Avoid: Strong Oxidizers **Hazardous Decomposition Products:** Carbon oxides Hazardous Polymerization: Will Not Occur 11 Toxicological Information No Toxicology Information is available. 12 Ecological Information No data available. 13 Disposal Considerations Waste Disposal Method: Dispose of waste in accordance with federal, state and local regulations 14 Transport Information HAZMAT: Yes ID Number: UN3265 Hazard Code: 1177 Hazard Class: 8 Hazardous Division: Corrosive liquid, acidic, organic, n.o.s. Packaging Group: Hazardous Contents: Hydroxyacetic Acid 15 Regulatory Information Proposition 65: Not Listed. EPA: No 16 Other Information Health 2 Flammability 0 Reactivity 0 HMIS/NFPA Hazard Rating: The information contained herein is based on the data available to us. It is believed to be correct. No warranty, expressed or implied, is made regarding the accuracy of this data or the results to be obtained from the use thereof. For further information consult Maintex, Inc. MSDS Approval Date: 1/30/2007 1/30/2007 0001 1177 Slip Control Page 3 of 3