



product

SAF T BOND Series

Specification

OC 024

Non-Flammable Outdoor Carpet Adhesive



- Longer Working Time
- Non-Flammable
- Easy to Trowel

Description: OC 024 Non-Flammable Outdoor Carpet Adhesive

Flammability: Non-Flammable

Open Time: 15 minutes

Working Time: 30 minutes

Clean Up: Clean wet adhesive and tools with white cloth and soap and water.

Shelf Life: One year in closed container.

Limitations: Do not subject to temperatures below 10°F. If frozen, warm to at least 70°F for 24 hours and stir before using.

Packaging:

- 4 Gallon • 1 Gallon • 1 Quart

For The Installation Of:

- ActionBac®/Jute • Latex Unitary • Waffle Backed • Rubber Backed • Urethane • Marine Backed



For Use Over:

- Concrete • Plywood
- APA Grade Particle Board • OSB • Terrazzo
- Hardwood Floors • Latex-Portland Cement Underlayment • Gypsum Cement Underlayment • VCT • Felt Backed Vinyl Sheet

Goods (prime with an acrylic sealer, such as Capitol's LL400 Liquid Latex) • Do not use over existing cutback

Instructions For Use:

1. Condition room and materials at 65°F for 48 hours prior to, during and after installation. Avoid hot and sunny conditions.
2. Sweep floor and remove any dirt or debris prior to installation.
3. Make sure floor is free from grease, oil, paint, or other contaminant that might interfere with the bond of the adhesive.
4. Do not install on floors with high moisture or alkali content.
5. Spread adhesive with the correct trowel making sure to maintain trowel notchings throughout the installation.
6. Allow the adhesive to flash for 15 minutes prior to installing the flooring material.
7. Apply only as much adhesive that can be installed within 30 minutes.
8. Press flooring firmly into adhesive.
9. Roll in both directions according to floor manufacturers recommendations.
10. Clean wet adhesive and tools with white cloth and soap and water.

Caution:

Avoid contact with skin and eyes. If splashed in eyes, flush with copious amounts of water for 15 minutes and call physician. Wash skin thoroughly with soap and water. Use with positive fresh air cross-ventilation. Do not take internally. If swallowed do not induce vomiting, call physician immediately. Keep container closed. **KEEP OUT OF REACH OF CHILDREN**



Material Safety Data Sheet

(38)

Ship
November 2000**OC 024****Non-Flammable Outdoor Carpet Adhesive****SECTION I - PRODUCT IDENTIFICATION**

Manufacturer's Name: Capitol USA, LLC

Address: 300 Cross Plains Blvd.

Dalton, GA 30722

Telephone #: 1-800-831-8381

Emergency Phone: 800-535-5053

Generic ID: Latex Based Outdoor Carpet Adhesive

DOT Hazard Classification: None

Product Identity: Non-Flammable OC024

Outdoor Carpet Adhesive

SECTION II - HAZARDOUS COMPONENTS

None per OSHA Regulation: 29CFR1910.1200

None per SARA Title III, Section 313 and TSCA 40 CRF 372

SECTION III - PHYSICAL DATA

Initial Boiling Point: 212°F; Vapor Pressure:

Same as water; Vapor Density (Air =1.0): Same

as water; Specific Gravity: 1.25; G/L VOC

(calculated): 0.00; Percent Volatiles: 29.6%

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point: NA; Explosive Limit (Product):

NA; Extinguishing Media: NA; Hazardous

Decomposition Products: None; Special Fire

Fighting Procedures: None; Unusual Fire &

Explosion Hazards: None

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: NA; Threshold

Limit Value: NA; Effects Of Exposure: Eyes -

Possible mild irritation. Skin - None known.

Breathing - None known.

SECTION VI - REACTIVITY DATA

Stability: Stable; Incompatibility: None;

Hazardous Decomposition: None; Hazardous

Polymerization: None; Conditions To Avoid:

None Known

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material. Solidified materials accepted for landfill disposal in most locations. Check all local, state, and federal regulations.

SECTION VIII - PROTECTIVE EQUIPMENT

Ventilation: Open all available windows and entrances to insure good ventilation. Respira-

tor Protection: None needed. Protective

Gloves: None needed. Eye Protection: Wear

glasses or protective goggles to avoid

splashes. Other Protective Equipment: None

required. Wash Hands Thoroughly with Soap and Water.

SECTION IX - SPECIAL PRECAUTIONS

Protect from freezing. Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.

Capitol USA believes the data set forth herein is accurate as of the date hereof, and makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.



Capitol USA, LLC
300 Cross Plains Blvd. • PO Box 2023
Dalton, GA 30722
800-831-8381 • Fax: 706-277-5753
Jim Walker ProSeries TechLine 888-234-8400
Website www.capitolusa.com

APR - 2 2001