

MATERIAL SAFETY DATA SHEET

NFPA RATING: Health = 0 Flammability = 0 Reactivity = 0

HMIS RATING: Health = 0 Flammability = 0 Reactivity = 0

SECTION I -- IDENTITY AND MANUFACTURER'S INFORMATION

Manufacturer's Name: HILLYARD INDUSTRIES

Address: 302 North Fourth Street
St. Joseph, MO 64502

Emergency Telephone No.: (800)-424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals.)

*(556N-02F)

Product Name: **STRONG GUARD**

Date Prepared: February 4, 2011 (version 3)

Prepared by: Regulatory Affairs Department

Other information calls: (816) 233-1321 (Ext.8285)

<http://www.hillyard.com>

SECTION II -- INGREDIENTS/IDENTITY INFORMATION

Components

(Specific Chemical Identity: Common Name(s))	CAS#	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
Diethylene Glycol Monobutyl Ether**	112-34-5	none	none	N.A.	2 - 5
Diethylene Glycol Monomethyl Ether**(1)	111-77-3	none	none	N.A.	2 - 5
Water	7732-18-5	none	none	N.A.	---
Acrylate Copolymer	N/A	N/E	N/E	N.A.	---

** This product contains the following chemical subject to reporting requirements of SARA Title III, Sec. 313: Diethylene Glycol Monobutyl Ether and Ethylene Glycol Monomethyl Ether.

(1) Regulated by FL, MA, PA

*SECTION III -- PHYSICAL / CHEMICAL CHARACTERISTICS

*Boiling Point: >200°F Corrected

*Vapor Pressure (mm Hg.): 17.3

*Vapor Density (AIR = 1): 1.09

Solubility in Water: Complete

PH= 7 - 8

Specific Gravity (H₂O = 1): 25°C = 1.03 *Density = 8.61 lbs/gal.

*Percent Volatile by Weight (%): 83.25 - 84.25

Evaporation Rate (ethyl ether = 1): slower than 1

Appearance and Odor: Milky white, mild ammonia odor

*SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

*Flash point: >200° (T.C.C.)

Flammable Limits: LEL = N.A. UEL = N.A.

Extinguishing Media: Not applicable.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear in a fire.

Unusual Fire and Explosion Hazards: Material may spatter if temperatures exceed 100°C / 212°F.

Polymer film can burn. Polymer may decompose at temperatures above 177°C/ 350°F and produce acrylic monomers.

SECTION V -- PHYSICAL HAZARDS

Stability: Stable Conditions to Avoid: N/A

Incompatibility (Materials to Avoid): None known to Hillyard

Hazardous Decomposition Products or Byproducts: None known to Hillyard.

Hazardous Polymerization: Will not Occur Conditions to Avoid: N/A

SECTION VI -- HEALTH HAZARD DATA

Routes of entry: Inhalation? N/A Skin? N/A Ingestion? N/A

HEALTH HAZARDS (1. Acute and 2. Chronic)

1. Mild eye irritation.

2. None known to Hillyard Industries

Chemical listed as Carcinogen or Potential Carcinogen:

National Toxicology Program = No I.A.R.C. Monographs = No OSHA = No

This product has no carcinogens listed by IARC, NTP, NIOSH, OR ACGIH as of this date, greater than or equal to 0.1%.

Signs and Symptoms of Exposure:

None known to Hillyard.

Medical Conditions Generally Aggravated by Exposure:

None known to Hillyard

HEALTH HAZARD DATA (CONTINUED):

Emergency and First Aid Procedures:

If splashed into eyes flush with water for 15 minutes; if irritation persists get medical attention. Flush skin with water.
Ingestion: Drink large quantity of water; consult a physician. Never give anything by mouth to an unconscious person.

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled:

Pick up with mop or wet vac and wash away with water.

Waste Disposal Method:

Observe all applicable Federal, State, and local regulations regarding disposal. Waste from normal product use may be sewerred to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and Local pretreatment requirements. Pick up with mop or wet vac and wash down POTW. Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Precautions To Be Taken In Handling And Storing:

Freezing of product may rupture container. Product shelf life is best retained by storage at 45-100°F temperature.

Other Precautions:

Inhalation exposure to spray mist should be maintained at less than 10 mg/m³ per eight hours exposure (TWA limit est. for nuisance dust).

SECTION VIII -- CONTROL MEASURES:

Respiratory Protection (Specify Type):

None required if good ventilation is maintained.

Ventilation: Local Exhaust = not required Mechanical (General) = suggested

Special = N.A. Other = N.A.

Protective Gloves: none required.

Eye Protection: none required

Other Protective Clothing or Equipment: none required.

Work / Hygienic Practices: Do not take internally; wash contaminated clothing and equipment before reuse.

SECTION IX - TRANSPORTATION INFORMATION:

Applicable regulations: no 49 CFR; no IMCO; no IATA.

Proper shipping name: Liquid Floor Wax & Polish

UN No.: not applicable **Limited Qty.:** not applicable **Hazard Class:** not applicable

Labels required: not required **DOT Exception:** not applicable

EPA Hazardous waste number / code: not listed

Hazardous waste characteristics:

Ignitability = not applicable; **Corrosivity** = not applicable; **Reactivity** = not applicable.

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.

Version 3, * Denotes revisions since last published MSDS. Supersedes Version 2 January 27, 2010