

**MATERIAL SAFETY DATA SHEET**

**NFPA RATING:** Health = 2 Flammability = 2 Reactivity = 0

**HMIS RATING:** Health = 2 Flammability = 2 Reactivity = 0

**SECTION I – IDENTITY AND MANUFACTURER'S INFORMATION**

(0985B)

**Manufacturer's Name:** HILLYARD INDUSTRIES

**Product Name:** KLEEN-UP SOLVENT

**Address:** 302 North Fourth Street

**Date Prepared:** November 25, 2008 (Version 3)

St. Joseph, MO 64502

**Prepared by:** Regulatory Affairs Department

**Emergency Telephone No.:** (800) 424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals.)

**Other information calls:** (816) 233-1321 (Ext. 8285)

<http://www.hillyard.com>

**SECTION II – INGREDIENTS/IDENTITY INFORMATION****Components**

(Specific Chemical Identity:

| Common Name(s)              | CAS#       | OSHA PEL | ACGIH TLV | OTHER LIMITS RECOMMENDED | %     |
|-----------------------------|------------|----------|-----------|--------------------------|-------|
| Stoddard Solvent            | 8052-41-3  | 100 ppm* | 100 ppm*  | 100ppm from mfg.         | 67-72 |
| Petroleum naphtha (1)       | 64742-95-6 | 100 ppm  | 100 ppm   | 50ppm from mfg.          | 26-31 |
| 1,2,4 Trimethyl benzene (2) | 95-63-6    | 25ppm    | 25ppm     | not applicable           | 9-14  |

\* Regulated by OSHA and the following states: FL, IL, LA, MA, NJ, PA, RI. (1) Regulated like Stoddard Solvent. (2) This product contains 1,2,4 Trimethyl benzene which is an EPA 313 – SARA Title III ingredient. This chemical is regulated by MA, NJ, PA. V. O. C. = 802 gm/l.

**SECTION III – PHYSICAL / CHEMICAL CHARACTERISTICS**

|  |  |
|--|--|
| <b>Boiling Point:</b> 330°F            | <b>Specific Gravity (H<sub>2</sub>O= 1):</b> 25°C = 0.80 39°C = 0.80 |
| <b>Vapor Pressure (mm Hg):</b> 3.4     | <b>Percent Volatile by Volume (%):</b> 100%                          |
| <b>Vapor Density (AIR = 1):</b> 4.6    | <b>Evaporation Rate (ethyl ether = 1):</b> slower than 1             |
| <b>Solubility in Water:</b> negligible | <b>Appearance and Odor:</b> thin, clear liquid; mineral spirit odor  |

**SECTION IV – FIRE AND EXPLOSION HAZARD DATA**

**Flash point:** 108°F (T.C.C.) average **Flammable Limits:** LEL = 1.9% UEL = N/A-mixture

**Extinguishing Media:** Use water spray to cool fire-exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, or dry chemical. Use NFPA Class B Extinguishers.

**Special Fire Fighting Procedures:** Treat as any petroleum solvent fire. Avoid spray water directly into storage containers due to danger of boilover. Avoid spreading liquid and fire by water. Wear full protective equipment including self-contained breathing apparatus.

**Unusual Fire and Explosion Hazards:** Keep container closed and isolated from heat, electrical equipment, sparks and flame. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode. Empty drums should be completely drained, properly capped and properly disposed of.

**SECTION V – PHYSICAL HAZARDS**

**Stability:** Stable **Conditions to Avoid:** Elevated temperatures

**Incompatibility (Materials to Avoid):** Avoid contact with strong acids and strong oxidizing agents.

**Hazardous Decomposition Products or Byproducts:** None under normal conditions. Thermal decomposition may produce organic acids, carbon dioxide and carbon monoxide.

**Hazardous Polymerization:** Will not occur **Conditions to Avoid:** N/A

**SECTION VI – HEALTH HAZARD DATA**

**Routes of entry:** Inhalation? Yes Skin? Yes Ingestion? Yes

**HEALTH HAZARDS (1. Acute and 2. Chronic)**

1. Causes skin irritation; prolonged skin contact may cause severe irritation. Harmful or fatal if swallowed. Causes nose and throat irritation. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Reports have associated repeated and prolonged occupational overexposure to solvent with permanent brain and nervous system damage. 2. None known to Hillyard.

**Chemical listed as Carcinogen or Potential Carcinogen:**

**National Toxicology Program =** No **I.A.R.C. Monographs =** No **OSHA =** No

This product has no carcinogens listed by IARC, NTP, NIOSH, or ACGIH as of this date, greater than or equal to 0.1%.

## SECTION VI – HEALTH HAZARD DATA continued

**Signs and Symptoms of Exposure:** Causes skin irritation. May cause nose and throat irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Vapor harmful; overexposure may affect the brain or nervous system causing dizziness, headache or nausea.

**Medical Conditions Generally Aggravated by Exposure:** Skin problems such as industrial dermatitis. Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be adversely affected by exposure to any vapor or airborne particulate matter.

**Emergency and First Aid Procedures:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of skin contact, wash thoroughly with soap and water and get medical assistance immediately; for eye contact immediately flush with plenty of water for at least 15 minutes. If swallowed, do not induce vomiting. Call a physician.

## SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

**Steps To Be Taken In Case Material Is Released Or Spilled:** If spilled, contain spilled material with sand or earth and remove with inert absorbent and non-sparking tools. Do not use combustible materials such as sawdust. Remove all sources of ignition (flames, hot surfaces; electric, static or friction sparks). Avoid breathing vapors. Ventilate area. Emptied containers may retain hazardous residue and explosive vapors. Keep away from heat, sparks, and flames. Do not cut, puncture or weld on or near this container. Follow label warnings until container is thoroughly cleaned or destroyed. Keep container closed when not in use. Do not store at temperatures over 100°F. Do not let spilled or leaking material enter watercourse. Notify authorities if liquid enters nearby water intakes. Notify local health and wildlife officials. Do not smoke when working with product. Do not pick up solution with automatic scrubber or wet pick-up vacuum.

**Waste Disposal Method:** Dispose of contaminated absorbent, container and unused contents in accordance with Federal, State and Local regulations. Incinerate regulated quantities in an approved facility; do not incinerate closed container. EPA Hazardous Waste (per RCRA Classification: Ignitable Liquid (40 CFR 261.21).

**Precautions To Be Taken In Handling And Storing:** Keep containers closed when not in use. Empty container may retain hazardous residue and explosive vapors; do not pressurize, cut, weld, braze, solder, drill or grind on or near container. Follow label warnings until container is thoroughly cleaned or destroyed. **Notice:** Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed, water-filled metal container and immediately remove from building. **Notice:** Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building. **Other Precautions:** Keep away from heat and flame. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **USE ONLY WITH ADEQUATE VENTILATION.** Do not breathe vapors or spray mist. **Ensure fresh air entry during application and drying.** If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor / mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not take internally.

## SECTION VIII – CONTROL MEASURES

**Respiratory Protection (Specify Type):** Wear appropriate, properly fitted respirator (NIOSH and MSHA approved) unless air monitoring demonstrates vapor or mist levels are below applicable limits.

**Ventilation:** At least 10 air changes per hour recommended.

**Local Exhaust =** Recommended      **Mechanical (General) =** Recommended      **Special =** N/A      **Other =** N/A

**Protective Gloves:** Solvent impervious rubber gloves

**Eye Protection:** Safety glasses with splash guards

**Other Protective Clothing or Equipment:** Solvent impermeable clothing

**Work / Hygienic Practices:** Wash clothing before reuse. Thoroughly clean contaminated shoes; if soaked throw them away.

## SECTION IX – TRANSPORTATION INFORMATION

**Applicable regulations:** CFR = no    IMCO = yes    IATA = yes

**Proper shipping name for air and foreign water:** Paint related material, 3, UN1263, III

**Proper shipping name for highway:** Cleaning compound

**UN No.:** not applicable for highway    **Limited Qty.:** not applicable    **Hazard class:** not applicable for highway

**Labels required:** not required for highway    **DOT Exception:** not applicable

**EPA Hazardous waste characteristics:** **Ignitability =** yes;    **Corrosivity =** not applicable;    **Reactivity =** not applicable

### DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. **THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.**