

MATERIAL SAFETY DATA SHEET

NFPA RATING: Health = 1 Flammability = 0 Reactivity = 0

***HMIS RATING:** Health = 1 Flammability = 0 Reactivity = 0

SECTION I – IDENTITY AND MANUFACTURER'S INFORMATION (546N-74B)

Manufacturer's Name: HILLYARD INDUSTRIES

Product Name: Aviator

Address: 302 North Fourth Street
St. Joseph, MO 64501

Date Prepared: February 24, 2010

Prepared by: Regulatory Affairs Department

Emergency Telephone No.: (800) 424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals.)

Other information calls: (816) 233-1321 (Ext. 8285)

<http://www.hillyard.com>

SECTION II – INGREDIENTS/IDENTITY INFORMATION**Components****(Specific Chemical Identity:**

Common Name(s)	CAS#	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
Water	7732-18-5	none	none	STEL = 150	---
Styrene/Butadiene/Acrylic Copolymer Emulsion	Unknown to Hillyard	not established	not established	N/A	---
Diethylene glycol monoethyl ether **	111-90-0	not established	not established	N/A	1-3
Tributoxyethyl Phosphate **	78-51-3	not established	not established	N/A	1-3
Polyethylene emulsion	Unknown to Hillyard	not established	not established	N/A	---

** This product contains the following chemicals subject to reporting requirements of SARA Title III, Section 313: Diethylene Glycol Monoethyl Ether, and Tributoxyethyl Phosphate.

WARNING! This product may contain trace amounts of a chemical known to the state of California to cause cancer and reproductive effects. California Proposition Chemical(s) 1,3-Butadiene, 4-Vinylcyclohexane, and Ethylbenzene.

SECTION III – PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: >200°F	Specific Gravity (H₂O = 1): 25°C = 1.019	Density: 8.49 lb/gal
Vapor Pressure (mm Hg.): 18.3	Percent Volatile by Volume (%): 79.0 %– 80.0%	
Vapor Density (AIR = 1): 1.31	Evaporation Rate (ethyl ether = 1): slower than 1	
Solubility in Water: complete	Appearance and Odor: Milky white liquid, non objectionable odor	
pH (as is) 8.5 – 9.5		

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flash point: None (Tag Closed Cup) **Flammable Limits:** LEL = N/A UEL = N/A

Extinguishing Media: Not applicable

Special Fire Fighting Procedures: Wear self-contained breathing apparatus (pressure demand, MSHA/NIOSH - approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards: Material can spatter above 100°C/212°F. Polymer film can burn.

SECTION V – PHYSICAL HAZARDS

Stability: Stable **Conditions to Avoid:** Onset of decomposition is 77°C/350°F.

Incompatibility (Materials to Avoid): None known to Hillyard Industries

Hazardous Decomposition Products or Byproducts: None known to Hillyard Industries

Hazardous Polymerization: Will not occur **Conditions to Avoid:** None known to Hillyard Industries

SECTION VI – HEALTH HAZARD DATA

Routes of entry: Inhalation? yes Skin? yes Ingestion? yes

HEALTH HAZARDS (1. Acute and 2. Chronic)

1. Not a skin or eye irritant per Federal Hazardous Substance Act. Prolonged exposure may cause moderate skin irritation in sensitive individuals. Prolonged eye contact may cause conjunctivae irritation in sensitive individuals. Overexposure to high airborne levels or liquid splashes of Dipropylene glycol methyl ether may cause eye, nose, throat, or skin irritation. Harmful if swallowed. 2. None known to Hillyard Industries.

Chemical listed as Carcinogen or Potential Carcinogen:

National Toxicology Program = No **I.A.R.C. Monographs =** No **OSHA =** No

This product has no carcinogens listed by IARC, NTP, NIOSH, or ACGIH as of this date, greater than or equal to 0.1%.

SECTION VI – HEALTH HAZARD DATA cont.

Signs and Symptoms of Exposure: Prolonged eye contact with concentrate can cause slight irritation but eyes are expected to clear up in 48 hours. Prolonged skin contact with concentrate can cause moderate skin irritation but is expected to recover in eight days.

Medical Conditions Generally Aggravated by Exposure: Dipropylene glycol methyl ether may aggravate obstructive airway diseases (persons with impaired pulmonary functions and liver and kidney problems. Persons with pre-existing skin disorders may be more susceptible to irritation.

Emergency and First Aid Procedures: FIRST AID: If swallowed, do not induce vomiting unless instructed to do so by medical personnel, seek immediate medical attention. **If inhaled,** move to fresh air. If discomfort persists, seek medical attention.

In case of skin or eye contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and laundry before reuse.

*SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Pick up with mop or wet vac and wash away with water. Absorb large spills with oil-dry or similar inert absorbent. Collect material for proper disposal.

Waste Disposal Method: Wash small quantities down sewer with large amount of water. Contains trace amount of ammonia which may be toxic to aquatic life. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. Large spills should be picked up with wet vac or absorbent material. Landfill or incinerate solids. Dispose of liquid per local, state or federal regulations.

Precautions To Be Taken In Handling And Storing: Freezing of product may rupture container. Do not use if product was frozen. Product shelf life is best retained by storage at 45-100°F temperature.

Other Precautions: Inhalation exposure to vapors should be maintained at less than 10 mg/m³ per eight hours exposure (TWA limit established for nuisance dust). USE WITH ADEQUATE VENTILATION. Avoid prolonged breathing of vapors. Open windows and doors, use exhaust fans or other means to insure fresh air entry during application and drying. Refer to OSHA Standard 29 CFR 1910.94 for technical guidelines on keeping air contamination below acceptable exposure limits. Keep container closed when not in use.

SECTION VIII – CONTROL MEASURES

Respiratory Protection (Specify Type): Wear appropriate, properly fitted respirator NIOSH or MSHA approved) unless air monitoring demonstrates vapor levels are below applicable limits.

Ventilation: Good ventilation for public areas is 10 air changes per hour.

Local Exhaust = Recommended **Mechanical (General) =** Recommended **Special =** N/A **Other =** N/A

Protective Gloves: None needed for normal use. Use solvent resistant rubber or neoprene gloves for prolonged or repeated contact.

Eye Protection: None needed for normal use

Other Protective Clothing or Equipment: None required for normal use.

Work / Hygienic Practices: Wash contaminated clothing before reuse (including shoes).

SECTION IX – TRANSPORTATION INFORMATION

DOT SHIPPING DESCRIPTION ON BILL OF LADING:

Applicable regulations: 49 CFR = no; IMCO = no; IATA = no

Proper shipping name: Liquid Floor Wax & Polish

UN No: not applicable; **Limited Qty.:** not applicable; **Hazard Class:** not applicable

Labels required: not required **DOT Exception:** not applicable

EPA Hazardous waste number/code: not listed

Hazardous waste characteristics:

Ignitability = not applicable; **Corrosivity =** not applicable; **Reactivity =** not applicable

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.