### <u>SECTION 1.</u> COMPANY AND PRODUCT IDENTIFICATION:

MANUFACTURERED FOR: Brady Industries, LLC	EMERGENCY TELEPHONE NUMBER (Chemtrec): (800) 424 – 9300
ADDRESS: 7055 Lindell Road Las Vegas, CA. 89118	TELEPHONE NUMBER FOR INFO: (702) 876-3990
DATE PREPARED: 4/28/2014	FAX NO. (702) 876-1580
PRODUCT NAME: ULTRA BUILT DETERGENT	DESCRIPTION: Economical Built Detergent

### SECTION 2. HAZARDS IDENTIFICATION:

## I. EMERGENCY OVERVIEW

\*Danger!\* Corrosive. Causes eye and skin burns.

May cause irritation and chemical burns to eyes, skin mucous membranes.

### **II. POTENTIAL HEALTH EFFECTS**

**INHALATION:** Breathing of mist may cause damage to the upper respiratory tract and the lung tissue, which could result in chemical pneumonia.

**SKIN CONTACT:** Will cause severe irritation and can cause deep chemical burns.

**EYE CONTACT:** Causes burns that result in damage to the eyes and possibly blindness.

INGESTION: Causes severe burns to mucous membranes of the mouth, throat, esophagus, and stomach.

CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Chronic effects and medical conditions aggravated by overexposure to this product have not been established.

#### SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS:

The identity of individual components of this mixture is proprietary information and regarded to be a trade secret. However, based on the health hazard determination of ingredients present at a concentration greater than 1% and 0.1% or more of a carcinogenic substance, this mixture presents the following hazard:

HAZARDOUS COMPONENTS	% (RANGE)	CAS NO.	OSHA PEL	ACGIH TLV
Sodium Hydroxide	5 - 15	1310-73-2	2 mg/m <sup>3</sup> 8 hr TWA	2 mg/m³ Ceiling

### <u>SECTION 4.</u> FIRST AID MEASURES:

INHALATION: Move the victim to fresh air. Give artificial respiration if not breathing.

**SKIN:** Immediately flush the area with flowing water for at least 15 minutes, while removing contaminated clothing. Wash the area with a nonabrasive soap and plenty of water. Wash clothing separately before reuse.

**EYES:** Immediately flush with plenty of water, alternately lifting the upper and lower eyelids. If appropriate, after 5 minutes, remove contact lenses and continue flushing the eyes for an additional 15 minutes. Get medical attention if irritation persists.

<sup>\*</sup>Target Organs: \*Eyes, skin, mucous membranes.

**INGESTION:** Drink 2-3 glasses of water. Do not induce vomiting or give anything by mouth to an unconscious or convulsing person. Get prompt medical attention.

### SECTION 5. FIRE FIGHTING MEASURES:

**EXTINGUISHING MEDIA:** Foam, CO<sub>2</sub>, water fog, sand/earth

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** This product can react with aluminum producing flammable hydrogen gas. Sealed containers may develop sufficient pressure to cause container to rupture under fire conditions. Use water spray to cool.

**SPECIAL FIRE FIGHTING PROCEDURES:** Must wear NIOSH approved or equivalent self-contained breathing apparatus and protective clothing.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES:

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Containers should be stored in a cool, dry, well-ventilated area. Exercise due caution to prevent damage to or leakage from the container. Avoid contact with strong acids and reactive metals. Keep containers closed when not in use.

## **SECTION 7.** HANDLING AND STORAGE:

**USAGE PRECAUTIONS:** Use as directed. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice.

**STORAGE PRECAUTIONS:** It is recommended that this material be stored in a cool area. Protect containers against damage. Keep closed until used. Store away from heat, sparks, open flame or sunlight. Keep out of reach of children.

**OTHER PRECAUTIONS:** Not applicable

## <u>SECTION 8.</u> EXPOSURE CONTROLS AND PERSONAL PROTECTION:

**ENGINEERING CONTROLS:** Provide adequate mechanical or local exhaust ventilation to minimize exposure levels, particularly in areas where the air contacts open process equipment.

**RESPIRATORY PROTECTION:** Avoid breathing mists. Use a NIOSH/MSHA approved respirator, with a full-facepiece or a full-facepiece respirator with dust/mist cartridges when concentrations are unknown.

**SKIN PROTECTION:** Wear rubber, neoprene, or nitrile gloves, and chemically resistant protective clothing, e.g, apron, or jump-suit and rubber boots.

**EYE PROTECTION:** Wear chemical splash goggles and a full-face shield where there is potential for eye contact. An eyewash fountain should be located in areas where the product is used.

SECTION 9.	PHYSICAL AND CHEMICAL PROPERTIES:			
FLASH POINT: ND				
<b>BOILING POINT</b> : ND				
MELTING POINT: N				
VAPOR PRESSURE (mm Hg): ND				
% VOLATILE BY VO SPECIFIC GRAVITY DENSITY: 8.81 lbs/ga APPEARANCE: Clea ODOR / TASTE: Odo SOLUBILITY IN WAT pH: > 13.0 VISCOSITY: NA	: ~ 1.05 al ar, colorless liquid orless			
SECTION 10.	STABILITY AND REACTIVITY:			
STABILITY	Unstable <u>X</u> Stable			
INCOMPATIBILITY (	(Materials to Avoid): Strong oxidizers and acids. (Aluminum, zinc, tin and their alloys)			
HAZARDOUS DECO	<b>DMPOSITION PRODUCTS:</b> High temperatures and fire conditions can result in the lium oxide.			
HAZARDOUS POLY	MERIZATION:MAY OCCURX WILL NOT OCCUR			
CONDITIONS TO AV	/OID: High temperatures and incompatibles.			
SECTION 11.	TOXICOLOGICAL INFORMATION:			
Toxicological data is i	not available.			
SECTION 12.	ECOLOGICAL INFORMATION:			
Ecological data is not	available.			
SECTION 13.	DISPOSAL CONSIDERATIONS:			
Collect and dispose of	of in accordance with Federal, Stare and Local laws and regulations.			
SECTION 14.	TRANSPORT INFORMATION:			
DOT Proper Shippin	ng Name: UN1760, CORROSIVE LIQUIDS, N.O.S., (SODIUM HYDROXIDE), 8, PGII			
SECTION 15.	REGULATORY INFORMATION:			
This product is not co	onsidered a carcinogen or cancer suspect under NTP, IARC and OSHA.			
SARA (Superfund Amendments and Reauthorization Act of 1986), Title III, Section 313 (Toxic Chemicals): None				
SARA (Superfund A Hazardous Substand None	mendments and Reauthorization Act of 1986), Title III, Section 302 (Extremely ces):			

SUPERFUND REPORTABLE QUANTITY: Sodium Hydroxide (1310-73-2) (RQ = 1,000 lbs).

CALIFORNIA/OSHA DIRECTOR'S LIST OF HAZARDOUS SUBSTANCES (8 CCR 339): Sodium Hydroxide

(1310-73-2)

**CALIFORNIA PROPOSITION 65: None** 

Label: Corrosive

NFPA RATING: Health: 3 Fire: 0 Reactivity: 0

SECTION 16. OTHER INFORMATION:

**SUPERSEDES:** 10/14/2014: DOT information update.

NA: not applicable 
ND: not determined

Disclaimer: Information presented herein is believed to be accurate and reliable to the best of our knowledge. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process. Users should make their own investigations to determine the suitability of the information for their particular purposes.