

## perfecting your image by design

# OSHA'S HAZARD COMMUNICATION STANDARD U.S. DEPARTMENT OF LABOR MATERIAL SAFETY DATA SHEET MSDS

**29 CFR 1910.1200 OMB NO:** 1218-0072

IDENTITY NO: MPGS1000 NAME: MASTERPIECE GOLDSHIELD POROUS PLUS SEALER

SECTION 1

MANUFACTURER'S/SHIPPER'S NAME: MASTERPIECE INDUSTRIES PRODUCTS
ADDRESS: 6683 SCHUSTER STREET PHONE: (702) 656-9767
CITY:LAS VEGAS STATE: NEVADA CONTACT: KEN WILLIAMS

**DATE PREPARED:** 4/15/02 **EMERGENCY PHONE (CHEMTREC):** (800) 424-9300

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS CAS# OSHA PEL ACGIH TLV WEIGHT %

HEPTANE 142825 500 PPM 500 PPM

PETROLEUM NAPHTHA 64741657

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: >212° F SPECIFIC GRAVITY: .745

VAPOR PRESSURE: NOT TESTED MELTING POINT: NOT TESTED

VAPOR DENSITY: NOT TESTED EVAPORATION RATE: NOT TESTED

SOLUBILITY IN WATER: INSOLUBLE

APPEARANCE AND ODOR: CLEAR TO AMBER, SOLVENT ODOR

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: APP- 85° F FLAMMABLE LIMITS: NOT TESTED

LEL: NOT TESTED
ph: NOT TESTED
DOT #: ORM-D

NFPA HAZARD RATING: HFRS HMIS HAZARD RATING: H F R (0=LEAST, 4=EXTREME) 1 20 0

EXTINGUISHING MEDIA: CO2, DRY FOAM

SPECIAL FIRE FIGHTING PROCEDURES: WEAR A SELF CONTAINED BREATHING APPARATUS WITH A FULL FACE PIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WITH APPROPRIATE TURN-OUT GEAR AND CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT.

UNUSUAL FIRE AND EXPLOSION HAZARDS: KEEP PRODUCT AWAY FROM SOURCE OF IGNITION, PILOT LIGHTS, OTHER FLAME, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE, ETC. USE WITH ADEQUATE VENTILATION.

SECTION 5 - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: HEAT AND FLAMES

INCOMPATIBLE MATERIALS TO AVOID: WATER, STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: CO, CO2

HAZARDOUS POLYMERIZATION: NONE



### perfecting your image by design

SECTION 6 - HEALTH HAZARD DATA

MPGS1000 PAGE 2

ROUTES OF ENTRY

INHALATION: POSSIBLE INGESTION: POSSIBLE

SKIN: POSSIBLE HEALTH HAZARDS: SAME SIGNS & SYMPTOMS OF EXPOSURE

NOTE: ALL CHEMICALS IN THIS PRODUCT ARE FOUND ON THE TSCA INVENTORY LIST.

OSHA CARCINOGENICITY: NONE NTP: NONE

IARC MONOGRAPHS: NONE

SIGNS & SYMPTOMS OF OVER EXPOSURE

EYES: BURNING, IRRITATION SKIN: IRRITATION

INGESTION: BURNING, IRRITATION INHALATION: DIZZINESS, HEADACHES, IRRITATION

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

SAME AS SIGNS AND SYMPTOMS OF OVER EXPOSURE.

EMERGENCY FIRST AID PROCEDURES:

EYES: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS CALL PHYSICIAN.

SKIN: WASH WITH SOAP AND WATER, ESPECIALLY BETWEEN NAILS. IF IRRITATION PERSISTS CALL

PHYSICIAN.

INGESTION: DRINK LARGE AMOUNTS OF MILK. DO NOT INDUCE VOMITING. IF IRRITATION

PERSISTSCALL PHYSICIAN.

INHALATION: GET PERSON TO FRESH AIR. IF UNCONSCIOUS CALL PHYSICIAN.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE.

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

ABSORB LIQUID IN VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL. SWEEP UP AND PLACE IN A PROPER WASTE DISPOSAL CONTAINER.

#### WASTE DISPOSAL METHOD:

DISPOSE OF IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE IN COOL, DRY PLACE.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. FOLLOW DIRECTIONS ON THE CONTAINER FOR PROPER USE OF THIS PRODUCT.

#### SECTION 8-CONTROL MEASURES

RESPIRATORY PROTECTION: OPEN ALL DOORS AND WINDOWS. EXPOSURES ABOVE THE TLV OR PEL REQUIRE A NIOSH APPROVED RESPIRATOR EQUIPPED FOR THE EXPOSURE OR SUITABLE RESPIRATORY PROTECTION PER 29 CFR 1910.134.

VENTILATION LOCAL EXHAUST: IF AVAILABLE SPECIAL: NONE

MECHANICAL: IF AVAILABLE OTHER: NONE

PROTECTIVE GLOVES: RUBBER, PLASTICS EYE PROTECTION: GLASSES, GOGGLES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: CHEMICAL RESISTANT CLOTHING

WORK HYGENIC PRACTICES: USE COMMON SENSE AND CARE AROUND CHEMICALS. NEVER MIX CHEMICALS.CONSULT YOUR SUPERVISOR FOR OTHER PRACTICES. ALL PRACTICES DEPEND ON YOUR SPECIFIC BUSINESS. DIRECTIONS FOR USE ARE NORMALLY FOUND ON LABEL WHICH WILL DICTATE ENGINEERING AND CONTROL MEASURES.

OTHER SPECIAL REQUIREMENTS: NONE