

Material Safety Data Sheet



QUIK FILL 530 (NPE-FREE)

Section 1. Chemical product and company identification

Trade name : QUIK FILL 530 (NPE-FREE)
Product use : Degreaser
Supplier : Ecolab Co.
5105 Tomken Road
Mississauga ON L4W 2X5
1-800-352-5326
Code : 903569
Date of issue : 12-October-2007

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

<u>Name</u>	<u>CAS number % by weight</u>	
2-aminoethanol	141-43-5	10 - 30
alcohols, c10-14, ethoxylated	66455-15-0	3 - 7
xylenesulfonic acid, sodium salt	1300-72-7	3 - 7
disodium metasilicate	6834-92-0	1 - 5
acetic acid, (ethylenedinitrilo)tetra-, tetrasodium salt	64-02-8	1 - 5

Section 3. Hazards identification

Physical state : Liquid. [Liquid.]
Emergency overview : DANGER!
CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS.
HARMFUL IF SWALLOWED.
Do not ingest. Do not get in eyes, on skin or on clothing. Do not breathe vapour or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Routes of entry : Skin contact, Eye contact, Inhalation, Ingestion
Potential acute health effects
Eyes : Corrosive to eyes.
Skin : Corrosive to the skin.
Inhalation : Corrosive to the respiratory system.
Ingestion : Harmful if swallowed. Causes burns to mouth, throat and stomach.

See toxicological information (section 11)

Section 4. First-aid measures

Eye contact : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion : Rinse mouth; then drink one or two large glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire-fighting measures

Auto-ignition temperature	: Not available.
Flash point	: > 100°C
Flammable limits	
Upper:	Not available.
Lower:	Not available.
Products of combustion	: Not available.
Fire-fighting media and instructions	: Use an extinguishing agent suitable for the surrounding fire.
	Dyke liquid for later disposal.
	No specific hazard.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Risk of explosion of the product in the presence of mechanical impact: Not available.

Risk of explosion of the product in the presence of static discharge: Not available.

Section 6. Accidental release measures

Personal Precautions	: Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Do not allow to enter drains or watercourses.
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	: If emergency personnel are unavailable, contain spilt material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain material to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal.

Section 7. Handling and storage

Handling	: Do not ingest. Do not get in eyes, on skin or on clothing. Keep container closed. Use only with adequate ventilation. Do not breathe vapour or mist. Wash thoroughly after handling.
Storage	: Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area.
	Store between the following temperatures: 10 and 45°C

Section 8. Exposure controls, personal protection

Engineering measures	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide eyewash and safety shower in area if contact or splash hazard exists.
-----------------------------	---

Personal protection :

Eyes	: Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.
Hands	: Use chemical-resistant, impervious gloves.
Skin	: Use synthetic apron, other protective equipment as necessary to prevent skin contact.
Respiratory	: Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are exceeded.

<u>Name</u>	<u>Exposure limits</u>
--------------------	-------------------------------

2-aminoethanol

ACGIH TLV (United States, 1/2006).

STEL: 15 mg/m³ 15 minute(s).

STEL: 6 ppm 15 minute(s).

TWA: 7.5 mg/m³ 8 hour(s).

TWA: 3 ppm 8 hour(s).

Section 9. Physical and chemical properties

Physical state	: Liquid. [Liquid.]
Colour	: fluorescent [Light]
Odour	: Fragrance-like.
pH	: 13.25 [Conc. (% w/w): 100%]
Boiling/condensation point	: Not available.
Melting/freezing point	: Not available.
Specific gravity	: 1.07
Vapour pressure	: Not available.
Vapour density	: Not available.
Odour threshold	: Not available.
Evaporation rate	: Not available.
LogK _{ow}	: Not available.

Section 10. Stability and reactivity

Stability	: The product is stable.
Conditions of instability	: Not available.
Reactivity	: Extremely reactive or incompatible with acids. Reactive with metals.
Hazardous Decomposition Products	: Not available.

Section 11. Toxicological information

Potential acute health effects

Eyes	: Corrosive to eyes.
Skin	: Corrosive to the skin.
Inhalation	: Corrosive to the respiratory system.
Ingestion	: Harmful if swallowed. Causes burns to mouth, throat and stomach.
Irritation of Product	: Hazardous by WHMIS criteria.

Potential chronic health effects

Carcinogenic effects	: No known significant effects or critical hazards.
Mutagenic effects	: No known significant effects or critical hazards.
Teratogenic effects	: No known significant effects or critical hazards.
Reproductive effects	: No known significant effects or critical hazards.
Sensitization to Product	: No known significant effects or critical hazards.
Synergistic products (toxicologically)	: Not available.

Toxicity data

<u>Ingredient name</u>	<u>Test</u>	<u>Route</u>	<u>Result</u>	<u>Species</u>
2-aminoethanol	LD50	Dermal	1018 mg/kg	Rabbit
	LD50	Oral	1 g/kg	Rabbit
	LD50	Oral	700 mg/kg	Mouse
	LD50	Oral	1720 mg/kg	Rat
disodium metasilicate	LD50	Oral	770 mg/kg	Mouse
	LD50	Oral	1153 mg/kg	Rat
acetic acid, (ethylenedinitrilo)tetra-, tetrasodium salt	LD50	Oral	10 g/kg	Rat
	LD50	Oral	7 g/kg	Rabbit

Target organs : Contains material which causes damage to the following organs: upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Section 12. Ecological information

Ecotoxicity

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
2-aminoethanol	Fish	96 hours	Acute LC50 2070 mg/L
	Fish	96 hours	Acute LC50 329.16 mg/L
	Fish	96 hours	Acute LC50 300 mg/L
	Fish	96 hours	Acute LC50 >300 mg/L
	Fish	96 hours	Acute LC50 >200 mg/L
disodium metasilicate	Fish	96 hours	Acute LC50 150 mg/L
	Daphnia	48 hours	Acute EC50 4857 mg/L
	Fish	96 hours	Acute LC50 3185 mg/L
	Fish	96 hours	Acute LC50 2320 mg/L
	Fish	96 hours	Acute LC50 3092 mg/L
acetic acid, (ethylenedinitrilo)tetra-, tetrasodium salt	Fish	96 hours	Acute LC50 2070 mg/L
	Fish	96 hours	Acute LC50 1030 mg/L
	Fish	96 hours	Acute LC50 486 mg/L

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
TDG Classification	UN2491	ETHANOLAMINE SOLUTION	8	III	<u>Passenger Carrying Road or Rail Index</u> 5

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

WHMIS : Class E: Corrosive material

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*.

Section 16. Other information

Date of issue : 12-October-2007.
Responsible name : Regulatory Affairs
Date of previous issue : 14-October-2004.
Notice to reader

Section 16. Other information

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.