

Material Safety Data Sheet



ABM HIGH-SPEED FLOOR FINISH

Section 1. Chemical product and company identification

Trade name : ABM HIGH-SPEED FLOOR FINISH
Product use : Floor care product
Supplier : Ecolab Inc. Professional Products Division
370 N. Wabasha St.
St. Paul, MN 55102
1-800-247-5362
Code : 933978-06
Date of issue : 29-June-2005

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, Information on Ingredients

Name	CAS number	% by weight
ethanol, 2-(2-ethoxyethoxy)-	111-90-0	3
dibutyl phthalate	84-74-2	1
dipropylene glycol methyl ether	34590-94-8	1 - 5
ethanol, 2-butoxy-, phosphate (3:1)	78-51-3	1 - 5

Section 3. Hazards identification

Physical state : Liquid. (Emulsion liquid.)
Emergency : CAUTION!
overview

MAY CAUSE EYE AND SKIN IRRITATION.
Avoid contact with skin and clothing. Wash thoroughly after handling.

Potential acute health effects

Eyes : Moderately irritating to the eyes.
Skin : Moderately irritating to the skin.
Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

See toxicological Information (section 11)

Section 4. First aid measures

Eye contact : In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention if irritation persists.
Skin contact : Wash with soap and water. Get medical attention if irritation occurs. Wash clothing before reuse.
Inhalation : If inhaled, remove to fresh air.
Ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Section 5. Fire fighting measures

Flash point : > 100°C
Fire fighting media and instructions : Use an extinguishing agent suitable for surrounding fires.

Dike area of fire to prevent product run-off.
No specific hazard.

Special protective equipment for fire-fighters : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions** : Ventilate area of leak or spill. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment (Section 8). Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Methods for cleaning up** : If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.--

Section 7. Handling and storage

- Handling** : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
- Storage** : Keep out of the reach of children. Keep container tightly closed. Keep container in a cool, well-ventilated area.
Store between 10 and 45°C

Section 8. Exposure Controls, Personal Protection

- Engineering controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protection

- Eyes** : Eye protection recommended.
- Hands** : For prolonged or repeated handling, use Impervious gloves.
- Skin** : No protective equipment is needed under normal use conditions.
- Respiratory** : No protective equipment is needed under normal use conditions.

Name

diisopropylene glycol methyl ether

Exposure limits

ACGIH TLV (United States, 1/2004). Skin

STEL: 909 mg/m³ 15 minute(s). Form: All forms

STEL: 150 ppm 15 minute(s). Form: All forms

TWA: 606 mg/m³ 8 hour(s). Form: All forms

TWA: 100 ppm 8 hour(s). Form: All forms

OSHA PEL (United States, 8/1997). Skin

TWA: 600 mg/m³ 8 hour(s). Form: All forms

TWA: 100 ppm 8 hour(s). Form: All forms

dibutyl phthalate

ACGIH TLV (United States, 1/2004).

TWA: 5 mg/m³ 8 hour(s). Form: All forms

NIOSH REL (United States, 12/2001).

TWA: 5 mg/m³ 10 hour(s). Form: All forms

OSHA PEL (United States, 8/1997).

TWA: 5 mg/m³ 8 hour(s). Form: All forms

Section 9. Physical and chemical properties

- Physical state** : Liquid. (Emulsion liquid.)
- Color** : White.
- Odor** : Acrylic.
- pH** : 8.66 (100%)
- Specific gravity** : 1.025 (Water = 1)

Section 10. Stability and reactivity

- Stability** : The product is stable.

Section 11. Toxicological information

Potential acute health effects

- Eyes** : Moderately irritating to the eyes.
Skin : Moderately irritating to the skin.
Inhalation : No known significant effects or critical hazards.
Ingestion : No known significant effects or critical hazards.

Potential chronic health effects

- Chronic effects on humans** : **DEVELOPMENTAL TOXICITY** Classified Reproductive system/toxin/female, Reproductive system/toxin/male [SUSPECTED] [dibutyl phthalate].
 Contains material which causes damage to the following organs: gastrointestinal tract, upper respiratory tract, central nervous system (CNS), eye, lens or cornea.

Section 12. Ecological information

- Products of degradation** : These products are carbon oxides (CO, CO₂) and water, phosphates.

Section 13. Disposal considerations

- Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Class	Packing group	Additional information
DOT Classification	Not regulated.	-	-	-	-

APPLIES ONLY DURING ROAD TRANSPORT

Any variation of the shipping description based on the packaging is not addressed.

Section 15. Regulatory information

- HCS Classification** : Irritating material
 Target organ effects
- U.S. Federal regulations** : SARA 302/304/311/312 extremely hazardous substances: None.
 SARA 302/304 emergency planning and notification: None.
- TSCA 8(b) inventory** : All materials are listed or exempt.
- | SARA 313 | Product name | Concentration |
|----------------------------------|---|----------------------|
| Form R - Reporting requirements: | ethanol, 2-(2-ethoxyethoxy)-dibutyl phthalate | 3.01 |
| California prop. 65 | No products were found. | >0.9999 |

Section 16. Other information

Hazardous Material Information System (U.S.A.) :	Health *	1
	Fire hazard	0
	Reactivity	0
	Personal protection	B

- Date of issue** : 29-June-2005.
Responsible name : Regulatory Affairs
Date of previous issue : No Previous Validation.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.