MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements

U.S. DEPARTMENT OF LABOR

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List)

CUTTING BOARD

SECTION I

Distributor's Name	Emergency Telephone Number
BRADY INDUSTRIES, INC.	(800) 424-9300

Address (Number, Street 4175 SOUTH ARVILLE	. 1	CIP Code)Telephone Number for Information (702) 876-3990
4173 SOOTH ARVITTE		(702) 070 3990
		Date Prepared
<u>las vegas, nevada</u>	89103	03/24/01

Signature of Preparer (optional)

<u>SECTION II - HAZARD</u>	OUS INGREDIENTS/IDENT	<u>CITY INFO</u>	RMATION		
Hazardous Components (Specific C	Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Recommended	% (optional)
MONOETHANOLAMINE	CAS #141-43-5	3ppm	3PPM	Other Limits NONE	<10%
DOT CLASS:	POTASSIUM HYDROXIDE 8, UN1814, PGII	SOLUTION			
HAZARD RATING:	HEALT	'H	= 3		
4-EXTREME	FIRE		= 0		
3-HIGH	REACI	IVITY	= 1		
2-MODERATE 1-SLIGHT 0-INSIGNIFICANT	SPECI	FIC HAZA	RDS = AL	KALI	

SECTION III - PHYSIC	AL/CHEMICAL	CHARACTERIS1	ICS				
Boiling Point		Specific	Gravity (H20) = 1)			
2	12°F			1.0	33		
Vapor Pressure (mm Hg)		Melting H	oint				
	NOT TESTED			N/.	A		
Vapor Density		Evaporat	ion Rate (Bu	tyl Acetate	= 1))	
N	OT TESTED			NOT	TES	STED	
Solubility in Water		pН					
	COMPLETELY S	OLUBLE		13	.0		
Appearance and Odor CLEAR ORANGE LIQUID	WITH A MILD	PLEASANT ODO)R .				
SECTION IV - FIRE AN		HAZARD DATA					
Flash Point (Method Used) NOT FLAMMABLE		Flammak N/A	le Limits		el /A	uel N/A	
Extinguishing Media	FOAM	,			<u>, </u>	,	
Special Fire Fighting Pro USE MEDIA APPROPRIAT		NDING FIRE.	USE SELF	-CONTAINE	d BF	REATHING	J
EQUIPMENT.							
Unusual Fire and Explosio					—		
WHEN STRONGLY HEATED		SOLVENT WILL	EVAPORATE	AND BURN	TO	PRODUCE	CARBON
	DIOXIDE.						
(Reproduce locally)				OSHA 174,	Sept	z. 1985	

Stability Unst Stak	Conditions to AvoidDleXXXHEAT
STRONG ACIDS	(Materials to Avoid)
	osition or Byproducts DE AND CARBON DIOXIDE
Hazardous	
SECTION VI -	HEALTH HAZARD DATA
Route(s) of Entr	NO YES YES
	Acute and Chronic) DERATELY ALKALINE PRODUCT AND WILL CAUSE TISSUE IRRITATION.
Emergency and Fi	rst Aid Procedures
EYES:	RINSE WITH WATER FOR 15 MINUTES, FLUSHING UPPER AND LOWER LIDS. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.
SKIN:	RINSE WITH SOAP AND WATER AND USE SKIN LOTION. IF IRRITATION PERSISTS, CONTACT A PHYSICIAN.
INGESTION:	DO <u>NOT</u> INDUCE VOMITING. DRINK PLENTY OF WATER OR CITRUS JUICE AND GET MEDICAL ATTENTION.
	NOTE: DO <u>NOT</u> GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
	PRECAUTIONS FOR SAFE HANDLING AND USE
	n in Case Material is Released or Spilled SOAK UP IN ABSORBENT CLAY OR SAND AND PLACE IN A D.O.T. APPROVED SALVAGE CONTAINER.
LARGE SPILL:	DIKE TO PREVENT ENTRY INTO SEWER SYSTEMS. CONTACT DISPOSAL COMPANY
	AND PUMP INTO APPROVED SALVAGE CONTAINER.
	AND LOCAL AUTHORITIES FOR DETAILS
STORE IN A CC	e Taken in Handling and Storing OL DRY AREA AND KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precaution KEEP OUT OF R	s EACH OF CHILDREN
	- CONTROL MEASURES
Respiratory Prot <u>NOT REQUIRED</u>	ection (Specify Type)
Ventilation	Local Exhaust Special NONE NONE
	Mechanical (General) Other NONE NONE
Protective Glove RIIBBER (s Eye Protection PR PLASTIC GLOVES GLASSES OR GOGGLES
Other Protective	Clothing or Equipment SOOTS AND RUBBER/PLASTIC APRON
Work/Hygienic Pr USE CARE	actices AND COMMON SENSE
	CUTTING BOARD - Page 2