## MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements

## U.S. DEPARTMENT OF LABOR

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List)

## HOCKING SUPER STRIPPER

## SECTION I

Emergency Telephone Number Distributed by: BRADY INDUSTRIES, INC. (800) 424-9300 Address (Number, Street, City, State & ZIP Code) Telephone Number for Information 4175 SOUTH ARVILLE (702) 876-3990 Date Prepared LAS VEGAS, NEVADA 89103 10/10/03 Signature of Preparer (optional)

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

DECITOR II IRDANDOOD INGNEDIENIS/IDENIIII INFONMATION									
Hazardous Components (Specific Che	emical Identity; Common Name(s))	OSHA PEL ACGIR	TLV	Recommended	% (optional)				
				Other Limits					
MONOETHANOLAMINE	CAS #141-43-5	3PPM	3PPM	NONE	<10%				
2-BUTOXETHANOL	CAS #111-76-2	25PPM	25PPM	NONE	>50%				

HAZARD RATING: HEALTH 2 2 4-EXTREME FIRE 3-HIGH REACTIVITY 0 2-MODERATE SPECIFIC HAZARDS = N/A

1-SLIGHT

0-INSIGNIFICANT

SECTION III - PHYS	ICAL/CHEMICAL	CHARACTERISTICS	
Boiling Point		Specific Gravity	(H20 = 1)
	336-343 F		0.904
Vapor Pressure (mm Hg)		Melting Point	
	NOT TESTED		N/A
Vapor Density		Evaporation Rate	e (Butyl Acetate = 1)
	NOT TESTED		NOT TESTED
Solubility in Water		Нд	
	COMPLETELY	SOLUBLE	12.0

Appearance and Odor

CLEAR COLORLESS LIQUID WITH A SOLVENT ODOR.

SECTION	IV	_	FIRE	AND	EXPLOSION	HAZARD	DATA
---------	----	---	------	-----	-----------	--------	------

Flash Point (Method Used) Flammable Limits LEL UEL 150 F N/AN/A

Extinguishing Media

CO<sup>2</sup>, DRY POWDER, OR FOAM

Special Fire Fighting Procedures

USE MEDIA APPROPRIATE FOR SURROUNDING FIRE. USE SELF-CONTAINED BREATHING EQUIPMENT

Unusual Fire and Explosion Hazards

WHEN STRONGLY HEATED IN A FIRE, SOLVENT WILL EVAPORATE AND BURN TO PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE.

SECTION V - REACTIVITY DATA

Stability Unstable Conditions to Avoid

Stable XXX

HEAT

Incompatibility (Materials to Avoid)

STRONG ACIDS

Hazardous Decomposition or Byproducts

CARBON MONOXIDE AND CARBON DIOXIDE

Hazardous May Occur Conditions to Avoid

Polymerization

Will Not Occur XXX

NONE

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation? Skin? Ingestion?

YES YES YES

Health Hazards (Acute and Chronic)

THIS IS A MODERATELY ALKALINE PRODUCT AND WILL CAUSE TISSUE IRRITATION.

Emergency and First Aid Procedures

EYES: RINSE WITH WATER FOR 15 MINUTES, FLUSHING UPPER AND LOWER LIDS,

IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

SKIN: RINSE WITH SOAP AND WATER AND USE SKIN LOTION. IF IRRITATION

PERSISTS, CONTACT A PHYSICIAN.

INGESTION: DO NOT INDUCE VOMITING. DRINK PLENTY OF WATER OR CITRUS JUICE AND

GET MEDICAL ATTENTION.

Inhalation: BREATHING THIS MATERIAL MAY BE HARMFUL.

NOTE: DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled

SMALL SPILL: SOAK UP IN ABSORBENT CLAY OR SAND AND PLACE IN D.O.T. APPROVED

SALVAGE CONTAINER.

LARGE SPILL: DIKE TO PREVENT ENTRY INTO SEWER SYSTEMS. CONTACT DISPOSAL COMPANY

AND PUMP INTO APPROVED SALVAGE CONTAINER.

Waste Disposal Method

CONTACT STATE AND LOCAL AUTHORITIES FOR DETAILS.

Precautions to Be Taken in Handling and Storing

STORE IN A COOL DRY AREA AND KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions

STORE IN A COOL DRY AREA AND KEEP CONTAINER CLOSED WHEN NOT IN USE.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type)

A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED.

**Ventilation** Local Exhaust Special

YES NONE

Mechanical (General) Other

YES NONE

Protective Gloves Eye Protection

RUBBER OR PLASTIC GLOVES GLASSES OR GOGGLES

Other Protective Clothing or Equipment

RUBBER BOOTS AND RUBBER/PLASTIC APRON

Work/Hygienic Practices

USE CARE AND COMMON SENSE