MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements

U.S. DEPARTMENT OF LABOR

Occupational Safety and Health Administration (Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

BRADY JMD TUB N' TILE

SECTION I

Distributor's Name

BRADY INDUSTRIES, INC.

Address (Number, Street, City, State & ZIP Code) Telephone Number for Information

4175 SOUTH ARVILLE

(702) 876-3990

Date Prepared

LAS VEGAS, NEVADA 89103

Distributor's Name

Emergency Telephone Number

(800) 424-9300

(702) 876-3990

Date Prepared

06/05/2003 Supercedes 08/05/02

Signature of Preparer (optional)

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity; Common Name(s))

*ORTHOPHOSPHORIC ACID CAS #7664-38-2

DOT CLASS: PHOSPHORIC ACID MIXTURE

8, UN1805, PG III

*THIS CHEMICAL IS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF SARA TITLE III.

HAZARD RATING:

4-EXTREME

5-HIGH

2-MODERATE

HEALTH

FIRE

0

REACTIVITY

SPECIFIC HAZARDS

ACID

1-SLIGHT

0-INSIGNIFICANT

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

| Boiling Point | Specific Gravity (H20 = 1) | | |
|------------------------|----------------------------|----------------|------------------------|
| | 212°F | _ | 1.098 |
| Vapor Pressure (mm Hg) | | Melting Point | |
| | NOT TESTED | | 30°F |
| Vapor Density | | Evaporation Ra | te (Butyl Acetate = 1) |
| | NOT TESTED | | NOT TESTED |
| Solubility in Water | | рН | |
| | COMPLETELY | SOLUBLE | 1.2 |
| 7 | | | |

Appearance and Odor

CLEAR PINK LIQUID WITH A FLORAL FRAGRANCE

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)

Flammable Limits LEL UEL

NOT FLAMMABLE N/A N/A N/A

Extinguishing Media

USE MEDIA APPROPRIATE FOR THE SURROUNDING FIRE

Special Fire Fighting Procedures

USE SELF-CONTAINED BREATHING EQUIPMENT AND COVER ALL EXPOSED SKIN

Unusual Fire and Explosion Hazards

EXCESSIVE HEAT CAN PRODUCE ACIDIC FUMES

(Reproduce locally)

OSHA 174, Sept. 1985

SECTION V - REACTIVITY DATA

Stability Unstable Conditions to Avoid

> Stable XXX

> > HEAT AND STRONG ALKALI

Incompatibility (Materials to Avoid)

CAUSTIC ALKALIS SUCH AS CAUSTIC SODA, CAUSTIC POTASH AND SULFIDES

Hazardous Decomposition or Byproducts

NONE

Hazardous May Occur Conditions to Avoid

Polymerization

Will Not Occur XXX

NONE

SECTION VI - HEALTH HAZARD DATA

Inhalation? Skin? Ingestion? Route(s) of Entry: YES YES

NO

Health Hazards (Acute and Chronic)

THIS IS A STRONG ACID PRODUCT AND IS CORROSIVE TO TISSUE

Emergency and First Aid Procedures

EYES: FLUSH WITH WATER FOR 15 MINUTES AND GET IMMEDIATE ATTENTION.

WASH WITH SOAP AND WATER AND GET MEDICAL ATTENTION IF IRRITATION SKIN:

PERSISTS.

MOVE TO FRESH AIR. INHALATION:

INGESTION: DO <u>NOT</u> INDUCE VOMITING. DRINK WATER, MILK, OR MAGNESIA IF

POSSIBLE. GET IMMEDIATE MEDICAL ATTENTION.

NOTE: DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled

NEUTRALIZE WITH SODA ASH. SOAK UP WITH ABSORBENT MATERIAL AND PLACE IN D.O.T. APPROVED DISPOSAL CONTAINER. DIKE IF NECESSARY TO KEEP SPILL FROM ENTERING

SEWERS. GOOD VENTILATION IS NECESSARY AS CARBON DIOXIDE GAS IS PRODUCE.

Waste Disposal Method

CONTACT STATE OF LOCAL AUTHORITIES FOR DETAILS

Precautions to Be Taken in Handling and Storing

STORE IN A COOL DRY AREA AWAY FROM ALKALIS. KEEP CONTAINER TIGHTLY SEALED WHEN NOT IN USE.

Other Precautions

KEEP OUT OF REACH OF CHILDREN

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type)

NOT REQUIRED IF GOOD VENTILATION IS AVAILABLE

Ventilation Local Exhaust Special IF AVAILABLE NONE Mechanical (General) Other IF AVAILABLE NONE

Protective Gloves Eye Protection

GOGGLES, GLASSES, OR FACE SHIELD RUBBER OR PLASTIC GLOVES

Other Protective Clothing or Equipment

RUBBER APRON AND BOOTS

Work/Hygienic Practices

USE CARE AND COMMON SENSE

TUB & TILE CLEANER Page 2